



July 19, 2022

Anchor QEA, LLC.
1201 3rd Avenue, Suite 2600
Seattle, WA 98101

To Whom It May Concern,

MTC approves and authorizes the release and publication of statements, conclusions, and extracts from or regarding our reports to Anchor QEA, LLC.

If you have any other questions, feel free to call us at (360) 755-1990, or email me at alex.eifrig@mtc-inc.net.

Thank you,

A handwritten signature in black ink that reads 'Alex Eifrig'. The signature is written in a cursive, flowing style.

MATERIALS TESTING & CONSULTING, INC.

Alex Eifrig
NW Region Laboratory Manager
WABO Supervising Laboratory Technician



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: September 23, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1427 - 1446
Date sampled: 7-7-21 & 7-8-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT10-GB-0-9 ft Sample #: B21-1428	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Visual Identification Silt with Clay Sample Color brown
---	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						

Plasticity Chart

Liquid Limit

Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT10-GB-9-14 ft Sample #: B21-1429	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Visual Identification Silt with Clay Sample Color brown
--	--	--

Liquid Limit Determination



	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	40.29	42.71	29.23			
Weight of Dry Soils + Pan:	37.17	38.71	25.20			
Weight of Pan:	28.61	28.25	15.04			
Weight of Dry Soils:	8.56	10.46	10.16			
Weight of Moisture:	3.12	4.00	4.03			
% Moisture:	36.5 %	38.2 %	39.7 %			
Number of Blows:	27	16	11			



Liquid Limit @ 25 Blows: 37 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination

	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						




All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo



Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT10-GB-14-19 ft Sample#: B21-1430	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Visual Identification Clayey Silt Sample Color brown																																																																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																																																					
Assumed Sp Gr : 2.65 Sample Weight: 50.30 grams Hydroscopic Moist.: 3.78% Adj. Sample Wgt : 48.47 grams		 ACCREDITED Certificate #: 1366.01																																																																																																																					
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer</th> <th style="text-align: left;">Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>35</td><td>30.5</td><td>72.2%</td><td>0.0444 mm</td></tr> <tr><td>2</td><td>30.5</td><td>24.5</td><td>62.9%</td><td>0.0326 mm</td></tr> <tr><td>4</td><td>24.5</td><td>18.5</td><td>50.5%</td><td>0.0240 mm</td></tr> <tr><td>15</td><td>18.5</td><td>15</td><td>38.2%</td><td>0.0129 mm</td></tr> <tr><td>30</td><td>15</td><td>10.5</td><td>30.9%</td><td>0.0093 mm</td></tr> <tr><td>60</td><td>10.5</td><td>5</td><td>21.7%</td><td>0.0068 mm</td></tr> <tr><td>240</td><td>5</td><td>2.5</td><td>10.3%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>2.5</td><td></td><td>5.2%</td><td>0.0014 mm</td></tr> </tbody> </table>		Hydrometer	Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	35	30.5	72.2%	0.0444 mm	2	30.5	24.5	62.9%	0.0326 mm	4	24.5	18.5	50.5%	0.0240 mm	15	18.5	15	38.2%	0.0129 mm	30	15	10.5	30.9%	0.0093 mm	60	10.5	5	21.7%	0.0068 mm	240	5	2.5	10.3%	0.0035 mm	1440	2.5		5.2%	0.0014 mm	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3" style="text-align: center;">Sieve Analysis</th> </tr> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>98%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>92.0%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>91.4%</td><td>0.074 mm</td></tr> <tr><td></td><td>80.4%</td><td>0.050 mm</td></tr> <tr><td></td><td>46.1%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>15.6%</td><td>0.005 mm</td></tr> <tr><td></td><td>6.6%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>3.6%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Analysis			Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	99%	0.425 mm	#100	98%	0.150 mm	#200	92.0%	0.075 mm	Silts	91.4%	0.074 mm		80.4%	0.050 mm		46.1%	0.020 mm	Clays	15.6%	0.005 mm		6.6%	0.002 mm	Colloids	3.6%	0.001 mm
Hydrometer	Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																			
1	35	30.5	72.2%	0.0444 mm																																																																																																																			
2	30.5	24.5	62.9%	0.0326 mm																																																																																																																			
4	24.5	18.5	50.5%	0.0240 mm																																																																																																																			
15	18.5	15	38.2%	0.0129 mm																																																																																																																			
30	15	10.5	30.9%	0.0093 mm																																																																																																																			
60	10.5	5	21.7%	0.0068 mm																																																																																																																			
240	5	2.5	10.3%	0.0035 mm																																																																																																																			
1440	2.5		5.2%	0.0014 mm																																																																																																																			
Sieve Analysis																																																																																																																							
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																					
3.0"	100%	75.000 mm																																																																																																																					
2.0"	100%	50.000 mm																																																																																																																					
1.5"	100%	37.500 mm																																																																																																																					
1.25"	100%	31.500 mm																																																																																																																					
1.0"	100%	25.000 mm																																																																																																																					
3/4"	100%	19.000 mm																																																																																																																					
5/8"	100%	16.000 mm																																																																																																																					
1/2"	100%	12.500 mm																																																																																																																					
3/8"	100%	9.500 mm																																																																																																																					
1/4"	100%	6.300 mm																																																																																																																					
#4	100%	4.750 mm																																																																																																																					
#10	100%	2.000 mm																																																																																																																					
#20	99%	0.850 mm																																																																																																																					
#40	99%	0.425 mm																																																																																																																					
#100	98%	0.150 mm																																																																																																																					
#200	92.0%	0.075 mm																																																																																																																					
Silts	91.4%	0.074 mm																																																																																																																					
	80.4%	0.050 mm																																																																																																																					
	46.1%	0.020 mm																																																																																																																					
Clays	15.6%	0.005 mm																																																																																																																					
	6.6%	0.002 mm																																																																																																																					
Colloids	3.6%	0.001 mm																																																																																																																					
USDA Soil Textural Classification																																																																																																																							
<table style="width: 100%; border-collapse: collapse;"> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>		% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																																
% Sand:	2.0 - 0.05 mm																																																																																																																						
% Silt:	0.05 - 0.002 mm																																																																																																																						
% Clay:	< 0.002 mm																																																																																																																						
USDA Soil Textural Classification Silt Loam																																																																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1430
 Sample Date: 7/7/2021
 Test Date: 9/20/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT10-GB-14-19 ft
 Visual Soil Description: brown clayey silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0042
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
	45.3	
	Initial	Post-Consolidation
Initial Moisture Content (%):	91.7	95.2
Dry Density (PCF):	0.837	0.770
Void Ratio:	45.6	43.5
Porosity (%):	saturated	saturated
Degree of Saturation (%):		



Summary of Sample Data: $\sigma_n=1000$ PSF		
	40.4	
	Initial	Post-Consolidation
Initial Moisture Content (%):	95.4	102.4
Dry Density (PCF):	0.765	0.646
Void Ratio:	43.4	39.3
Porosity (%):	saturated	saturated
Degree of Saturation (%):		

Summary of Sample Data: $\sigma_n=2000$ PSF		
	37.0	
	Initial	Post-Consolidation
Initial Moisture Content (%):	97.7	106.6
Dry Density (PCF):	0.725	0.581
Void Ratio:	42.0	36.7
Porosity (%):	saturated	saturated
Degree of Saturation (%):		

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	37	33
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	370	840	1430
Residual Horizontal Stress, τ_h (PSF):	290	640	1310



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787


Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT10-GB-19-24 ft Sample#: B21-1431	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: grayish-brown	 ACCREDITED Certificate #: 1366.01
--	--	--	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.014 mm D ₍₁₀₎ = 0.027 mm D ₍₁₅₎ = 0.041 mm D ₍₃₀₎ = 0.079 mm D ₍₅₀₎ = 0.108 mm D ₍₆₀₎ = 0.122 mm D ₍₉₀₎ = 0.298 mm Dust Ratio = 13/47	% Gravel = 0.0% % Sand = 72.5% % Silt & Clay = 27.5% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.85 Coeff. of Uniformity, C _u = 4.47 Fineness Modulus = 0.32 Plastic Limit = n/a Moisture %, as sampled = 35.1% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00		100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		90%	100.0%	0.0%
#60	0.250		86%	100.0%	0.0%
#80	0.180		81%	100.0%	0.0%
#100	0.150	79%	79%	100.0%	0.0%
#140	0.106		49%	100.0%	0.0%
#170	0.090		38%	100.0%	0.0%
#200	0.075	27.5%	27.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT28-GB-0-10 ft Sample #: B21-1434	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Aug-21 Tested By: A. Eifrig	Visual Identification Clay with Silt Sample Color dark brown
--	--	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	33.52	24.84	28.54			
Weight of Dry Soils + Pan:	28.91	21.54	25.61			
Weight of Pan:	19.45	14.96	19.90			
Weight of Dry Soils:	9.46	6.58	5.71			
Weight of Moisture:	4.61	3.30	2.93			
% Moisture:	48.7 %	50.2 %	51.3 %			
Number of Blows:	34	22	19			



Liquid Limit @ 25 Blows: 50 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:	Plastic limit cannot be determined					
Weight of Dry Soils:	Plastic limit cannot be determined					
Weight of Moisture:	Plastic limit cannot be determined					
% Moisture:	Plastic limit cannot be determined					



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic Limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT28-GB-10-15 ft Sample #: B21-1436	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Aug-21 Tested By: A. Eifrig	Visual Identification Silty Clay Sample Color dark brown
---	--	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	30.19	31.68	32.21			
Weight of Dry Soils + Pan:	26.52	27.44	27.75			
Weight of Pan:	19.62	19.54	19.84			
Weight of Dry Soils:	6.90	7.90	7.91			
Weight of Moisture:	3.67	4.24	4.46			
% Moisture:	53.2 %	53.7 %	56.4 %			
Number of Blows:	25	21	12			



Liquid Limit @ 25 Blows: 53 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic Limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT28-GB-15-16.8 ft Sample #: B21-1437	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Aug-21 Tested By: A. Eifrig	Visual Identification Clay and Silt Sample Color dark brown
---	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	31.73	40.08	39.56			
Weight of Dry Soils + Pan:	28.13	36.32	36.04			
Weight of Pan:	19.86	28.17	28.53			
Weight of Dry Soils:	8.27	8.15	7.51			
Weight of Moisture:	3.60	3.76	3.52			
% Moisture:	43.5 %	46.1 %	46.9 %			
Number of Blows:	27	15	12			



Liquid Limit @ 25 Blows: 44 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:	Plastic limit cannot be determined					
Weight of Dry Soils:	Plastic limit cannot be determined					
Weight of Moisture:	Plastic limit cannot be determined					
% Moisture:	Plastic limit cannot be determined					



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic Limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1438
 Sample Date: 7/7/2021
 Test Date: 8/25/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT28-GB-16.8-20 ft
 Visual Soil Description: gray sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	31.3	
	Initial	Post-Consolidation
Dry Density (PCF):	105.4	106.7
Void Ratio:	0.598	0.579
Porosity (%):	37.4	36.7
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	31.0	
	Initial	Post-Consolidation
Dry Density (PCF):	105.6	107.2
Void Ratio:	0.595	0.572
Porosity (%):	37.3	36.4
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	32.9	
	Initial	Post-Consolidation
Dry Density (PCF):	104.0	107.8
Void Ratio:	0.619	0.562
Porosity (%):	38.2	36.0
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	37	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	380	830	1450
Residual Horizontal Stress, τ_h (PSF):	290	720	1230



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT21-GB-0-13 ft Sample #: B21-1441	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Aug-21 Tested By: A. Eifrig	Visual Identification Silty Clay Sample Color dark brown
--	--	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	28.39	31.98	25.34			
Weight of Dry Soils + Pan:	23.97	27.63	21.68			
Weight of Pan:	15.01	19.45	14.80			
Weight of Dry Soils:	8.96	8.18	6.88			
Weight of Moisture:	4.42	4.35	3.66			
% Moisture:	49.3 %	53.2 %	53.2 %			
Number of Blows:	35	17	19			



Liquid Limit @ 25 Blows: 52 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic Limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT21-GB-13-16 ft Sample#: B21-1442	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.017 mm D ₍₁₀₎ = 0.034 mm D ₍₁₅₎ = 0.051 mm D ₍₃₀₎ = 0.096 mm D ₍₅₀₎ = 0.150 mm D ₍₆₀₎ = 0.239 mm D ₍₉₀₎ = 1.216 mm Dust Ratio = 3/11	% Gravel = 0.2% % Sand = 77.9% % Silt & Clay = 22.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.14 Coeff. of Uniformity, C _u = 7.00 Fineness Modulus = 1.12 Plastic Limit = n/a Moisture %, as sampled = 96.5% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00		100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18		90%	100.0%	0.0%
#20	0.850		86%	100.0%	0.0%
#30	0.600		83%	100.0%	0.0%
#40	0.425	81%	81%	100.0%	0.0%
#50	0.300		67%	100.0%	0.0%
#60	0.250		61%	100.0%	0.0%
#80	0.180		53%	100.0%	0.0%
#100	0.150	50%	50%	100.0%	0.0%
#140	0.106		34%	100.0%	0.0%
#170	0.090		28%	100.0%	0.0%
#200	0.075	22.0%	22.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT21-GB-16-21 ft Sample#: B21-1444	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: dark gray	 Certificate #: 1366.01
--	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.019 mm D ₍₁₀₎ = 0.039 mm D ₍₁₅₎ = 0.058 mm D ₍₃₀₎ = 0.104 mm D ₍₅₀₎ = 0.177 mm D ₍₆₀₎ = 0.256 mm D ₍₉₀₎ = 1.188 mm Dust Ratio = 5/21	% Gravel = 0.1% % Sand = 80.5% % Silt & Clay = 19.4% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.10 Coeff. of Uniformity, C _u = 6.61 Fineness Modulus = 1.15 Plastic Limit = n/a Moisture %, as sampled = 38.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00		100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18		90%	100.0%	0.0%
#20	0.850		86%	100.0%	0.0%
#30	0.600		83%	100.0%	0.0%
#40	0.425	81%	81%	100.0%	0.0%
#50	0.300		66%	100.0%	0.0%
#60	0.250		59%	100.0%	0.0%
#80	0.180		50%	100.0%	0.0%
#100	0.150	47%	47%	100.0%	0.0%
#140	0.106		31%	100.0%	0.0%
#170	0.090		25%	100.0%	0.0%
#200	0.075	19.4%	19.4%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1444
 Sample Date: 7/8/2021
 Test Date: 9/13/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT21-GB-16-21 ft
 Visual Soil Description: dark gray sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	26.8	
	Initial	Post-Consolidation
Dry Density (PCF):	107.5	109.1
Void Ratio:	0.568	0.545
Porosity (%):	36.2	35.3
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	26.2	
	Initial	Post-Consolidation
Dry Density (PCF):	107.6	110.8
Void Ratio:	0.566	0.521
Porosity (%):	36.1	34.3
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	24.9	
	Initial	Post-Consolidation
Dry Density (PCF):	108.8	113.7
Void Ratio:	0.549	0.481
Porosity (%):	35.4	32.5
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	40	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	430	860	1670
Residual Horizontal Stress, τ_h (PSF):	260	580	1280



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT21-GB-21-25.7 ft Sample#: B21-1445	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Visual Identification Sandy Silt Sample Color: grayish-brown
--	--	---



ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.005 mm	% Gravel = 0.0%	Coeff. of Curvature, C _c = 2.30
D ₍₁₀₎ = 0.010 mm	% Sand = 30.5%	Coeff. of Uniformity, C _u = 6.70
D ₍₁₅₎ = 0.015 mm	% Silt & Clay = 69.5%	Fineness Modulus = 0.04
D ₍₃₀₎ = 0.040 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.060 mm	Plasticity Index = n/a	Moisture %, as sampled = 35.7%
D ₍₆₀₎ = 0.068 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.130 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 16/23	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00		100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00		100%	100.0%	0.0%
3/4"	19.00		100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50		100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	100%	100%	100.0%	0.0%
#40	0.425	100%	100%	100.0%	0.0%
#50	0.300	99%	99%	100.0%	0.0%
#60	0.250	98%	98%	100.0%	0.0%
#80	0.180	98%	98%	100.0%	0.0%
#100	0.150	97%	97%	100.0%	0.0%
#140	0.106	81%	81%	100.0%	0.0%
#170	0.090	75%	75%	100.0%	0.0%
#200	0.075	69.5%	69.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.


Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo




Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT21-GB-21-25.7 ft Sample#: B21-1445	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Visual Identification Sandy Silt Sample Color grayish-brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Sp Gr : 2.55 Sample Weight: 51.07 grams Hydroscopic Moist.: 0.72% Adj. Sample Wgt : 50.70 grams		 ACCREDITED Certificate #: 1366.01																																																																					
<table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>19.5</td><td>39.2%</td><td>0.0512 mm</td></tr> <tr><td>2</td><td>14</td><td>28.2%</td><td>0.0373 mm</td></tr> <tr><td>4</td><td>12</td><td>24.1%</td><td>0.0266 mm</td></tr> <tr><td>15</td><td>7</td><td>14.1%</td><td>0.0142 mm</td></tr> <tr><td>30</td><td>5</td><td>10.1%</td><td>0.0101 mm</td></tr> <tr><td>60</td><td>3</td><td>6.0%</td><td>0.0072 mm</td></tr> <tr><td>240</td><td>2</td><td>4.0%</td><td>0.0036 mm</td></tr> <tr><td>1440</td><td>1</td><td>2.0%</td><td>0.0015 mm</td></tr> </tbody> </table>			Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	19.5	39.2%	0.0512 mm	2	14	28.2%	0.0373 mm	4	12	24.1%	0.0266 mm	15	7	14.1%	0.0142 mm	30	5	10.1%	0.0101 mm	60	3	6.0%	0.0072 mm	240	2	4.0%	0.0036 mm	1440	1	2.0%	0.0015 mm																																	
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	19.5	39.2%	0.0512 mm																																																																				
2	14	28.2%	0.0373 mm																																																																				
4	12	24.1%	0.0266 mm																																																																				
15	7	14.1%	0.0142 mm																																																																				
30	5	10.1%	0.0101 mm																																																																				
60	3	6.0%	0.0072 mm																																																																				
240	2	4.0%	0.0036 mm																																																																				
1440	1	2.0%	0.0015 mm																																																																				
% Gravel: 0.0% % Sand: 30.5% % Silt: 64.7% % Clay: 4.8%		Sieve Analysis Grain Size Distribution <table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>100%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>100%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>97%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>69.5%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>68.2%</td><td>0.074 mm</td></tr> <tr><td></td><td>33.0%</td><td>0.050 mm</td></tr> <tr><td></td><td>18.8%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>4.8%</td><td>0.005 mm</td></tr> <tr><td></td><td>2.5%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.4%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	100%	0.850 mm	#40	100%	0.425 mm	#100	97%	0.150 mm	#200	69.5%	0.075 mm	Silts	68.2%	0.074 mm		33.0%	0.050 mm		18.8%	0.020 mm	Clays	4.8%	0.005 mm		2.5%	0.002 mm	Colloids	1.4%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	100%	2.000 mm																																																																					
#20	100%	0.850 mm																																																																					
#40	100%	0.425 mm																																																																					
#100	97%	0.150 mm																																																																					
#200	69.5%	0.075 mm																																																																					
Silts	68.2%	0.074 mm																																																																					
	33.0%	0.050 mm																																																																					
	18.8%	0.020 mm																																																																					
Clays	4.8%	0.005 mm																																																																					
	2.5%	0.002 mm																																																																					
Colloids	1.4%	0.001 mm																																																																					
USDA Soil Textural Classification																																																																							
<table border="0" style="width: 100%;"> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </table>		% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																
% Sand:	2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						
USDA Soil Textural Classification Sandy Loam																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT21-GB-26-31 ft Sample#: B21-1446	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 23-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: gray	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.013 mm D ₍₁₀₎ = 0.026 mm D ₍₁₅₎ = 0.039 mm D ₍₃₀₎ = 0.077 mm D ₍₅₀₎ = 0.119 mm D ₍₆₀₎ = 0.140 mm D ₍₉₀₎ = 0.354 mm Dust Ratio = 12/41	% Gravel = 0.0% % Sand = 71.1% % Silt & Clay = 28.9% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.65 Coeff. of Uniformity, C _u = 5.38 Fineness Modulus = 0.53 Plastic Limit = n/a Moisture %, as sampled = 34.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00		100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		99%	100.0%	0.0%
#20	0.850		99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		83%	100.0%	0.0%
#60	0.250		77%	100.0%	0.0%
#80	0.180		69%	100.0%	0.0%
#100	0.150	65%	65%	100.0%	0.0%
#140	0.106		44%	100.0%	0.0%
#170	0.090		36%	100.0%	0.0%
#200	0.075	28.9%	28.9%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: September 28, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1321 - 1335
Date sampled: 7-26-21 & 7-27-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:


	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT24-5-13.6 ft Sample#: B21-1322	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 ACCREDITED Certificate #: 1366.01
--	--	---	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.087$ mm $D_{(10)} = 0.149$ mm $D_{(15)} = 0.176$ mm $D_{(30)} = 0.252$ mm $D_{(50)} = 0.321$ mm $D_{(60)} = 0.355$ mm $D_{(90)} = 0.640$ mm Dust Ratio = 1/20	% Gravel = 0.4% % Sand = 95.6% % Silt & Clay = 4.0% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 1.20$ Coeff. of Uniformity, $C_u = 2.38$ Fineness Modulus = 1.60 Plastic Limit = 0.0% Moisture %, as sampled = 26.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	99%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600	88%	88%	100.0%	0.0%
#40	0.425	81%	81%	100.0%	0.0%
#50	0.300	44%	44%	100.0%	0.0%
#60	0.250	29%	29%	100.0%	0.0%
#80	0.180	16%	16%	100.0%	0.0%
#100	0.150	10%	10%	100.0%	0.0%
#140	0.106	7%	7%	100.0%	0.0%
#170	0.090	5%	5%	100.0%	0.0%
#200	0.075	4.0%	4.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1322
 Sample Date: 7/26/2021
 Test Date: 8/24/2021
 Technician: M. Carrillo


Sample Source: LDW-GT24-5-13.6 ft
 Visual Soil Description: brown sand with silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	26.4	
	Initial	Post-Consolidation
Dry Density (PCF):	108.1	108.3
Void Ratio:	0.559	0.556
Porosity (%):	35.9	35.7
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	27.1	
	Initial	Post-Consolidation
Dry Density (PCF):	107.4	109.3
Void Ratio:	0.569	0.541
Porosity (%):	36.3	35.1
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	29.0	
	Initial	Post-Consolidation
Dry Density (PCF):	105.6	108.6
Void Ratio:	0.595	0.551
Porosity (%):	37.3	35.5
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	39	37
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	350	860	1580
Residual Horizontal Stress, τ_h (PSF):	330	820	1500



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787


Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT24-13.6-29 ft Sample#: B21-1323	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.091 mm D ₍₁₀₎ = 0.163 mm D ₍₁₅₎ = 0.201 mm D ₍₃₀₎ = 0.292 mm D ₍₅₀₎ = 0.389 mm D ₍₆₀₎ = 0.457 mm D ₍₉₀₎ = 0.815 mm Dust Ratio = 1/14	% Gravel = 0.0% % Sand = 95.9% % Silt & Clay = 4.1% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.15 Coeff. of Uniformity, C _u = 2.81 Fineness Modulus = 1.94 Plastic Limit = 0.0% Moisture %, as sampled = 18.4% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	93%	93%	100.0%	0.0%
#20	0.850	93%	93%	100.0%	0.0%
#30	0.600	72%	72%	100.0%	0.0%
#40	0.425	57%	57%	100.0%	0.0%
#50	0.300	32%	32%	100.0%	0.0%
#60	0.250	21%	21%	100.0%	0.0%
#80	0.180	12%	12%	100.0%	0.0%
#100	0.150	8%	8%	100.0%	0.0%
#140	0.106	6%	6%	100.0%	0.0%
#170	0.090	5%	5%	100.0%	0.0%
#200	0.075	4.1%	4.1%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT24-35-43 ft Sample#: B21-1325	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: gray	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.042 mm D ₍₁₀₎ = 0.082 mm D ₍₁₅₎ = 0.114 mm D ₍₃₀₎ = 0.175 mm D ₍₅₀₎ = 0.227 mm D ₍₆₀₎ = 0.257 mm D ₍₉₀₎ = 0.414 mm Dust Ratio = 3/31	% Gravel = 0.0% % Sand = 91.1% % Silt & Clay = 8.9% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.45 Coeff. of Uniformity, C _u = 3.14 Fineness Modulus = 1.17 Plastic Limit = 0.0% Moisture %, as sampled = 27.3% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	99%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600	92%	92%	100.0%	0.0%
#40	0.425	92%	92%	100.0%	0.0%
#50	0.300	68%	68%	100.0%	0.0%
#60	0.250	59%	59%	100.0%	0.0%
#80	0.180	32%	32%	100.0%	0.0%
#100	0.150	21%	21%	100.0%	0.0%
#140	0.106	14%	14%	100.0%	0.0%
#170	0.090	11%	11%	100.0%	0.0%
#200	0.075	8.9%	8.9%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____




Reviewed by:
 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting




ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT24-43-50 ft Sample #: B21-1326	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Aug-21 Tested By: C. Kriss	Visual Identification Silty Sand Sample Color dark brown				
Liquid Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Liquid Limit cannot be established					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I _p : N/A						
Plastic Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic Limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
						
						
						

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.


Reviewed by: 
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT24-53.3-59 ft Sample#: B21-1327	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Visual Identification Sandy Silt Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.007 mm D ₍₁₀₎ = 0.014 mm D ₍₁₅₎ = 0.021 mm D ₍₃₀₎ = 0.042 mm D ₍₅₀₎ = 0.070 mm D ₍₆₀₎ = 0.088 mm D ₍₉₀₎ = 0.161 mm Dust Ratio = 6/11	% Gravel = 0.0% % Sand = 46.3% % Silt & Clay = 53.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.42 Coeff. of Uniformity, C _u = 6.33 Fineness Modulus = 0.15 Plastic Limit = n/a Moisture %, as sampled = 33.1% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	98%	98%	100.0%	0.0%
#60	0.250	97%	97%	100.0%	0.0%
#80	0.180	92%	92%	100.0%	0.0%
#100	0.150	89%	89%	100.0%	0.0%
#140	0.106	68%	68%	100.0%	0.0%
#170	0.090	61%	61%	100.0%	0.0%
#200	0.075	53.7%	53.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT36-3.6-6.2 ft Sample#: B21-1329	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
---	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.016$ mm $D_{(10)} = 0.055$ mm $D_{(15)} = 0.058$ mm $D_{(30)} = 0.069$ mm $D_{(50)} = 0.106$ mm $D_{(60)} = 0.135$ mm $D_{(90)} = 4.129$ mm Dust Ratio = 39/80	% Gravel = 8.6% % Sand = 52.0% % Silt & Clay = 39.4% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 0.64$ Coeff. of Uniformity, $C_u = 2.46$ Fineness Modulus = 1.19 Plastic Limit = n/a Moisture %, as sampled = 15.5% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	99%	99%	100.0%	0.0%
1/2"	12.50	98%	98%	100.0%	0.0%
3/8"	9.50	95%	95%	100.0%	0.0%
1/4"	6.30	92%	92%	100.0%	0.0%
#4	4.75	91%	91%	100.0%	0.0%
#8	2.36	86%	86%	100.0%	0.0%
#10	2.00	85%	85%	100.0%	0.0%
#16	1.18	84%	84%	100.0%	0.0%
#20	0.850	84%	84%	100.0%	0.0%
#30	0.600	82%	82%	100.0%	0.0%
#40	0.425	81%	81%	100.0%	0.0%
#50	0.300	78%	78%	100.0%	0.0%
#60	0.250	77%	77%	100.0%	0.0%
#80	0.180	69%	69%	100.0%	0.0%
#100	0.150	65%	65%	100.0%	0.0%
#140	0.106	50%	50%	100.0%	0.0%
#170	0.090	45%	45%	100.0%	0.0%
#200	0.075	39.4%	39.4%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1329
 Sample Date: 7/26/2021
 Test Date: 8/26/2021
 Technician: M. Carrillo


Sample Source: LDW-GT36-3.6-6.2 ft
 Visual Soil Description: brown silty sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	19.8	
	Initial	Post-Consolidation
Dry Density (PCF):	114.5	115.4
Void Ratio:	0.472	0.460
Porosity (%):	32.1	31.5
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	20.2	
	Initial	Post-Consolidation
Dry Density (PCF):	115.0	117.1
Void Ratio:	0.465	0.439
Porosity (%):	31.7	30.5
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	19.0	
	Initial	Post-Consolidation
Dry Density (PCF):	115.4	120.1
Void Ratio:	0.460	0.403
Porosity (%):	31.5	28.7
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	36	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	400	680	1440
Residual Horizontal Stress, τ_h (PSF):	250	570	1300



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT36-6.2-9.5 ft Sample#: B21-1330	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
---	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.017 mm D ₍₁₀₎ = 0.035 mm D ₍₁₅₎ = 0.052 mm D ₍₃₀₎ = 0.092 mm D ₍₅₀₎ = 0.132 mm D ₍₆₀₎ = 0.152 mm D ₍₉₀₎ = 0.240 mm Dust Ratio = 7/32	% Gravel = 0.0% % Sand = 78.4% % Silt & Clay = 21.6% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.59 Coeff. of Uniformity, C _u = 4.38 Fineness Modulus = 0.47 Plastic Limit = n/a Moisture %, as sampled = 27.5% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		95%	100.0%	0.0%
#60	0.250	93%	93%	100.0%	0.0%
#80	0.180		70%	100.0%	0.0%
#100	0.150	59%	59%	100.0%	0.0%
#140	0.106		37%	100.0%	0.0%
#170	0.090		29%	100.0%	0.0%
#200	0.075	21.6%	21.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT36-11.7-32 ft Sample#: B21-1332	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SP-SM, Poorly graded Sand with Silt Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.053 mm D ₍₁₀₎ = 0.129 mm D ₍₁₅₎ = 0.186 mm D ₍₃₀₎ = 0.285 mm D ₍₅₀₎ = 0.368 mm D ₍₆₀₎ = 0.410 mm D ₍₉₀₎ = 0.738 mm Dust Ratio = 1/9	% Gravel = 0.0% % Sand = 92.9% % Silt & Clay = 7.1% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.53 Coeff. of Uniformity, C _u = 3.18 Fineness Modulus = 1.77 Plastic Limit = n/a Moisture %, as sampled = 15.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600	64%	78%	100.0%	0.0%
#40	0.425	64%	64%	100.0%	0.0%
#50	0.300	34%	34%	100.0%	0.0%
#60	0.250	22%	22%	100.0%	0.0%
#80	0.180	14%	14%	100.0%	0.0%
#100	0.150	11%	11%	100.0%	0.0%
#140	0.106	9%	9%	100.0%	0.0%
#170	0.090	8%	8%	100.0%	0.0%
#200	0.075	7.1%	7.1%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT36-32-34.7 ft Sample #: B21-1333	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Aug-21 Tested By: C. Kriss	Visual Identification Sand with Silt Sample Color brown
--	---	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid Limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic Limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						

Copyright Spears Engineering & Technical Services PS, 1996-98

Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.


Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT36-34.7-50 ft Sample#: B21-1334	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 24-Aug-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SP-SM, Poorly graded Sand with Silt Sample Color: grayish-brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.058 mm D ₍₁₀₎ = 0.096 mm D ₍₁₅₎ = 0.126 mm D ₍₃₀₎ = 0.177 mm D ₍₅₀₎ = 0.226 mm D ₍₆₀₎ = 0.251 mm D ₍₉₀₎ = 0.441 mm Dust Ratio = 6/83	% Gravel = 0.0% % Sand = 93.5% % Silt & Clay = 6.5% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.30 Coeff. of Uniformity, C _u = 2.62 Fineness Modulus = 1.19 Plastic Limit = n/a Moisture %, as sampled = 23.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	94%	94%	100.0%	0.0%
#40	0.425	90%	90%	100.0%	0.0%
#50	0.300	68%	68%	100.0%	0.0%
#60	0.250	60%	60%	100.0%	0.0%
#80	0.180	31%	31%	100.0%	0.0%
#100	0.150	19%	19%	100.0%	0.0%
#140	0.106	12%	12%	100.0%	0.0%
#170	0.090	9%	9%	100.0%	0.0%
#200	0.075	6.5%	6.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting





ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW-GT-36-50.5-61.5 ft Sample #: B21-1335	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Aug-21 Tested By: C. Kriss	Visual Identification Silty Clay Sample Color brown
---	---	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	29.50	30.28	27.77			
Weight of Dry Soils + Pan:	26.95	27.50	24.20			
Weight of Pan:	19.61	19.98	14.98			
Weight of Dry Soils:	7.34	7.52	9.22			
Weight of Moisture:	2.55	2.78	3.57			
% Moisture:	34.7 %	37.0 %	38.7 %			
Number of Blows:	30	21	11			

Liquid Limit @ 25 Blows: 36 %
Plastic Limit: 25 %
Plasticity Index, I_p: 11 %


Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	34.74	35.86				
Weight of Dry Soils + Pan:	33.48	34.32				
Weight of Pan:	28.53	28.24				
Weight of Dry Soils:	4.95	6.08				
Weight of Moisture:	1.26	1.54				
% Moisture:	25.5 %	25.3 %				



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 
 Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: September 29, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1447 - 1466
Date sampled: 7-8-21 & 7-9-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM C566, ASTM D2216


Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: August 31, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-1447	LDW21-GT21-GB-31-32.5 ft	222.3	700.9	590.1	110.8	367.8	30.1%
B21-1448	LDW21-GT12-GB-0-1.5 ft	208.8	636.4	466.8	169.6	258.0	65.7%
B21-1449	LDW21-GT12-GB-0-12 ft	224.0	851.3	609.9	241.4	385.9	62.6%
B21-1450	LDW21-GT12-GB-12-13.5 ft	233.8	567.3	458.5	108.8	224.7	48.4%
B21-1451	LDW21-GT12-GB-18-22 ft	222.9	780.0	643.4	136.6	420.5	32.5%
B21-1452	LDW21-GT12-GB-22-23.5 ft	229.4	723.2	606.3	116.9	376.9	31.0%
B21-1453	LDW21-GT11-GB-0-1.5 ft	221.8	617.6	440.0	177.6	218.2	81.4%
B21-1454	LDW21-GT11-GB-0-8.5 ft	233.8	686.2	473.2	213.0	239.4	89.0%
B21-1455	LDW21-GT11-GB-8.5-10 ft	224.8	616.6	455.4	161.2	230.6	69.9%
B21-1456	LDW21-GT11-GB-8.5-16.7 ft	182.3	495.3	374.9	120.4	192.6	62.5%
B21-1457	LDW21-GT11-GB-16.7-18.5 ft	186.7	993.2	821.5	171.7	634.8	27.0%
B21-1458	LDW21-GT11-GB-18.5-20 ft	220.1	643.5	566.8	76.7	346.7	22.1%
B21-1459	LDW21-GT9-GB-0-1.5 ft	221.4	388.1	331.3	56.8	109.9	51.7%
B21-1460	LDW21-GT9-GB-10-11.5 ft	225.6	534.4	429.8	104.6	204.2	51.2%
B21-1461	LDW21-GT9-GB- 16-20 ft	225.7	665.4	521.2	144.2	295.5	48.8%
B21-1462	LDW21-GT9-GB-20-21.5 ft	235.5	299.4	285.9	13.5	50.4	26.8%
B21-1463	LDW21-GT7-GB-0-1.5 ft	301.1	545.2	480.4	64.8	179.3	36.1%
B21-1464	LDW21-GT7-GB-0-5.7 ft	182.9	988.2	806.6	181.6	623.7	29.1%
B21-1465	LDW21-GT7-GB-8.5-10 ft	217.2	591.3	504.5	86.8	287.3	30.2%
B21-1466	LDW21-GT7-GB-8.5-18.5 ft	233.4	693.2	578.2	115.0	344.8	33.4%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Name correction:
LDW21-GT9-GB-10-20

Reviewed by: 
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT12-GB-0-12 ft Sample #: B21-1449	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Visual Identification Clayey Silt with Sand Sample Color brown
--	---	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo



Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT12-GB-18-22 ft Sample#: B21-1451	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? N/A

D ₍₅₎ = 0.010 mm	% Gravel = 0.2%	Coeff. of Curvature, C _c = 1.73
D ₍₁₀₎ = 0.035 mm	% Sand = 80.4%	Coeff. of Uniformity, C _u = 6.41
D ₍₁₅₎ = 0.062 mm	% Silt & Clay = 19.3%	Fineness Modulus = 0.95
D ₍₃₀₎ = 0.115 mm	Liquid Limit = 0.0%	Plastic Limit = 0.0%
D ₍₅₀₎ = 0.188 mm	Plasticity Index = 0.0%	Moisture %, as sampled = 32.5%
D ₍₆₀₎ = 0.222 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.417 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 7/33	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	98%	98%	100.0%	0.0%
#20	0.850	98%	98%	100.0%	0.0%
#30	0.600	94%	94%	100.0%	0.0%
#40	0.425	91%	91%	100.0%	0.0%
#50	0.300	75%	75%	100.0%	0.0%
#60	0.250	68%	68%	100.0%	0.0%
#80	0.180	48%	48%	100.0%	0.0%
#100	0.150	39%	39%	100.0%	0.0%
#140	0.106	28%	28%	100.0%	0.0%
#170	0.090	23%	23%	100.0%	0.0%
#200	0.075	19.3%	19.3%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo




Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT12-GB-18-22 ft Sample#: B21-1451	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Sp Gr : 2.66 Sample Weight: 102.98 grams Hydroscopic Moist.: 1.38% Adj. Sample Wgt : 101.58 grams		Sieve Analysis Grain Size Distribution <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>99%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>98%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>91%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>39%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>19.3%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>19.0%</td><td>0.074 mm</td></tr> <tr><td></td><td>11.7%</td><td>0.050 mm</td></tr> <tr><td></td><td>7.9%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>2.3%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.1%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.7%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	99%	2.000 mm	#20	98%	0.850 mm	#40	91%	0.425 mm	#100	39%	0.150 mm	#200	19.3%	0.075 mm	Silts	19.0%	0.074 mm		11.7%	0.050 mm		7.9%	0.020 mm	Clays	2.3%	0.005 mm		1.1%	0.002 mm	Colloids	0.7%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	99%	2.000 mm																																																																					
#20	98%	0.850 mm																																																																					
#40	91%	0.425 mm																																																																					
#100	39%	0.150 mm																																																																					
#200	19.3%	0.075 mm																																																																					
Silts	19.0%	0.074 mm																																																																					
	11.7%	0.050 mm																																																																					
	7.9%	0.020 mm																																																																					
Clays	2.3%	0.005 mm																																																																					
	1.1%	0.002 mm																																																																					
Colloids	0.7%	0.001 mm																																																																					
<table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th>Hydrometer Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>12</td><td>11.7%</td><td>0.0516 mm</td></tr> <tr><td>2</td><td>10.5</td><td>10.3%</td><td>0.0370 mm</td></tr> <tr><td>5</td><td>9</td><td>8.8%</td><td>0.0235 mm</td></tr> <tr><td>15</td><td>6.5</td><td>6.3%</td><td>0.0138 mm</td></tr> <tr><td>30</td><td>5</td><td>4.9%</td><td>0.0098 mm</td></tr> <tr><td>60</td><td>3.5</td><td>3.4%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>1.5</td><td>1.5%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.0%</td><td>0.0014 mm</td></tr> </tbody> </table> <table style="width: 100%;"> <tr> <td style="width: 50%;"> % Gravel: 0.2% % Sand: 80.4% % Silt: 17.1% % Clay: 2.3% </td> <td style="width: 50%; text-align: right;"> Liquid Limit: 0.0 % Plastic Limit: 0.0 % Plasticity Index: 0.0 % </td> </tr> </table>	Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	12	11.7%	0.0516 mm	2	10.5	10.3%	0.0370 mm	5	9	8.8%	0.0235 mm	15	6.5	6.3%	0.0138 mm	30	5	4.9%	0.0098 mm	60	3.5	3.4%	0.0070 mm	240	1.5	1.5%	0.0035 mm	1440	1	1.0%	0.0014 mm	% Gravel: 0.2% % Sand: 80.4% % Silt: 17.1% % Clay: 2.3%	Liquid Limit: 0.0 % Plastic Limit: 0.0 % Plasticity Index: 0.0 %																																	
Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	12	11.7%	0.0516 mm																																																																				
2	10.5	10.3%	0.0370 mm																																																																				
5	9	8.8%	0.0235 mm																																																																				
15	6.5	6.3%	0.0138 mm																																																																				
30	5	4.9%	0.0098 mm																																																																				
60	3.5	3.4%	0.0070 mm																																																																				
240	1.5	1.5%	0.0035 mm																																																																				
1440	1	1.0%	0.0014 mm																																																																				
% Gravel: 0.2% % Sand: 80.4% % Silt: 17.1% % Clay: 2.3%	Liquid Limit: 0.0 % Plastic Limit: 0.0 % Plasticity Index: 0.0 %																																																																						
USDA Soil Textural Classification																																																																							
<table style="width: 100%;"> <tr> <td style="width: 50%;">% Sand:</td> <td style="width: 50%;">Particle Size: 2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </table> <p style="text-align: center;">USDA Soil Textural Classification Sand</p>	% Sand:	Particle Size: 2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																	
% Sand:	Particle Size: 2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1451
 Sample Date: 7/8/2021
 Test Date: 8/23/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT12-GB-18-22 ft
 Visual Soil Description: brown clayey silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	34.3	
	Initial	Post-Consolidation
Dry Density (PCF):	104.7	112.4
Void Ratio:	0.609	0.499
Porosity (%):	37.9	33.3
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	32.5	
	Initial	Post-Consolidation
Dry Density (PCF):	106.6	117.5
Void Ratio:	0.580	0.433
Porosity (%):	36.7	30.2
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	34.7	
	Initial	Post-Consolidation
Dry Density (PCF):	104.7	119.6
Void Ratio:	0.609	0.409
Porosity (%):	37.8	29.0
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	33	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	320	680	1300
Residual Horizontal Stress, τ_h (PSF):	260	620	1260



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT11-GB-0-8.5 ft Sample#: B21-1454	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 ML, Sandy Silt Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.004 mm D ₍₁₀₎ = 0.007 mm D ₍₁₅₎ = 0.010 mm D ₍₃₀₎ = 0.041 mm D ₍₅₀₎ = 0.063 mm D ₍₆₀₎ = 0.069 mm D ₍₉₀₎ = 0.146 mm Dust Ratio = 68/97	% Gravel = 0.0% % Sand = 31.3% % Silt & Clay = 68.7% Liquid Limit = 40.6% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 3.47 Coeff. of Uniformity, C _u = 9.80 Fineness Modulus = 0.14 Plastic Limit = 0.0% Moisture %, as sampled = 89.0% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	99%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600	98%	98%	100.0%	0.0%
#40	0.425	98%	98%	100.0%	0.0%
#50	0.300	97%	97%	100.0%	0.0%
#60	0.250	96%	96%	100.0%	0.0%
#80	0.180	93%	93%	100.0%	0.0%
#100	0.150	91%	91%	100.0%	0.0%
#140	0.106	78%	78%	100.0%	0.0%
#170	0.090	73%	73%	100.0%	0.0%
#200	0.075	68.7%	68.7%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo




Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT11-GB-0-8.5 ft Sample#: B21-1454	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 ML, Sandy Silt Sample Color brown																																			
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																			
Assumed Sp Gr : 2.65 Sample Weight: 53.60 grams Hydroscopic Moist.: 4.63% Adj. Sample Wgt : 51.23 grams		Sieve Analysis Grain Size Distribution																																			
 ACCREDITED Certificate #: 1366.01																																					
Hydrometer <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>16</td><td>31.2%</td><td>0.0505 mm</td></tr> <tr><td>2</td><td>15</td><td>29.3%</td><td>0.0359 mm</td></tr> <tr><td>5</td><td>14</td><td>27.3%</td><td>0.0228 mm</td></tr> <tr><td>15</td><td>9.5</td><td>18.5%</td><td>0.0136 mm</td></tr> <tr><td>30</td><td>7.5</td><td>14.6%</td><td>0.0097 mm</td></tr> <tr><td>60</td><td>5</td><td>9.8%</td><td>0.0069 mm</td></tr> <tr><td>240</td><td>2.5</td><td>4.9%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>2.0%</td><td>0.0014 mm</td></tr> </tbody> </table>	Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	16	31.2%	0.0505 mm	2	15	29.3%	0.0359 mm	5	14	27.3%	0.0228 mm	15	9.5	18.5%	0.0136 mm	30	7.5	14.6%	0.0097 mm	60	5	9.8%	0.0069 mm	240	2.5	4.9%	0.0035 mm	1440	1	2.0%	0.0014 mm	
Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																		
1	16	31.2%	0.0505 mm																																		
2	15	29.3%	0.0359 mm																																		
5	14	27.3%	0.0228 mm																																		
15	9.5	18.5%	0.0136 mm																																		
30	7.5	14.6%	0.0097 mm																																		
60	5	9.8%	0.0069 mm																																		
240	2.5	4.9%	0.0035 mm																																		
1440	1	2.0%	0.0014 mm																																		
<table style="width: 100%;"> <tr> <td>% Gravel: 0.0%</td> <td>Liquid Limit: 40.6 %</td> </tr> <tr> <td>% Sand: 31.3%</td> <td>Plastic Limit: 0.0 %</td> </tr> <tr> <td>% Silt: 61.7%</td> <td>Plasticity Index: 0.0 %</td> </tr> <tr> <td>% Clay: 7.0%</td> <td></td> </tr> </table>	% Gravel: 0.0%	Liquid Limit: 40.6 %	% Sand: 31.3%	Plastic Limit: 0.0 %	% Silt: 61.7%	Plasticity Index: 0.0 %	% Clay: 7.0%																														
% Gravel: 0.0%	Liquid Limit: 40.6 %																																				
% Sand: 31.3%	Plastic Limit: 0.0 %																																				
% Silt: 61.7%	Plasticity Index: 0.0 %																																				
% Clay: 7.0%																																					
USDA Soil Textural Classification																																					
<table style="width: 100%;"> <tr> <td>% Sand:</td> <td>Particle Size</td> </tr> <tr> <td>% Silt:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Clay:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td></td> <td>< 0.002 mm</td> </tr> </table>	% Sand:	Particle Size	% Silt:	2.0 - 0.05 mm	% Clay:	0.05 - 0.002 mm		< 0.002 mm																													
% Sand:	Particle Size																																				
% Silt:	2.0 - 0.05 mm																																				
% Clay:	0.05 - 0.002 mm																																				
	< 0.002 mm																																				
USDA Soil Textural Classification Sandy Loam																																					

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____

Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT11-GB-0-8.5 ft Sample #: B21-1454	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 ML, Sandy Silt Sample Color brown
---	---	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	32.18	28.53	30.48			
Weight of Dry Soils + Pan:	28.57	24.52	27.32			
Weight of Pan:	19.55	15.03	19.88			
Weight of Dry Soils:	9.02	9.49	7.44			
Weight of Moisture:	3.61	4.01	3.16			
% Moisture:	40.0%	42.3%	42.5%			
Number of Blows:	28	17	15			



Liquid Limit @ 25 Blows: 41 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling.

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1454
 Sample Date: 7/8/2021
 Test Date: 8/26/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT11-GB-0-8.5 ft
 Visual Soil Description: brown silty clay
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0042
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	58.2	
	Initial	Post-Consolidation
Dry Density (PCF):	76.6	86.1
Void Ratio:	1.201	0.957
Porosity (%):	54.6	48.9
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	54.1	
	Initial	Post-Consolidation
Dry Density (PCF):	78.1	94.3
Void Ratio:	1.157	0.786
Porosity (%):	53.6	44.0
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	57.2	
	Initial	Post-Consolidation
Dry Density (PCF):	78.4	103.4
Void Ratio:	1.149	0.630
Porosity (%):	53.5	38.6
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	34	33
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	270	730	1360
Residual Horizontal Stress, τ_h (PSF):	230	700	1300



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT11-GB-8.5-16.7 ft Sample #: B21-1456	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Visual Identification Clayey Silt Sample Color brown
--	---	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	33.23	29.16	29.46			
Weight of Dry Soils + Pan:	29.57	25.20	25.24			
Weight of Pan:	19.86	15.05	14.81			
Weight of Dry Soils:	9.71	10.15	10.43			
Weight of Moisture:	3.66	3.96	4.22			
% Moisture:	37.7 %	39.0 %	40.5 %			
Number of Blows:	26	17	11			



Liquid Limit @ 25 Blows: 38 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo



Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT11-GB-16.7-18.5 ft Sample#: B21-1457	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: gray	
--	---	--	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.019 mm	% Gravel = 0.0%	Coeff. of Curvature, C _c = 1.50
D ₍₁₀₎ = 0.038 mm	% Sand = 80.2%	Coeff. of Uniformity, C _u = 7.34
D ₍₁₅₎ = 0.057 mm	% Silt & Clay = 19.8%	Fineness Modulus = 1.22
D ₍₃₀₎ = 0.126 mm	Liquid Limit = 0.0%	Plastic Limit = 0.0%
D ₍₅₀₎ = 0.220 mm	Plasticity Index = 0.0%	Moisture %, as sampled = 27.0%
D ₍₆₀₎ = 0.279 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.733 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 23/90	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	96%	96%	100.0%	0.0%
#20	0.850	95%	95%	100.0%	0.0%
#30	0.600	85%	85%	100.0%	0.0%
#40	0.425	77%	77%	100.0%	0.0%
#50	0.300	63%	63%	100.0%	0.0%
#60	0.250	57%	57%	100.0%	0.0%
#80	0.180	41%	41%	100.0%	0.0%
#100	0.150	35%	35%	100.0%	0.0%
#140	0.106	26%	26%	100.0%	0.0%
#170	0.090	23%	23%	100.0%	0.0%
#200	0.075	19.8%	19.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT9-GB-0-1.5 ft Sample #: B21-1459	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Visual Identification Sandy Silt Sample Color brown
--	---	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT9-GB-16-20-R Sample #: B21-1461	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 E. Kriss	Visual Identification Sandy Silt with Clay Sample Color brown					
<div style="border: 1px solid red; padding: 2px; display: inline-block;"> Name correction: LDW21-GT9-GB-10-20 </div>							
Liquid Limit Determination							
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture: Number of Blows:	#1	#2	#3	#4	#5	#6	
Liquid limit cannot be established							
Plastic Limit Determination							
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture:	#1	#2	#3	#4	#5	#6	
Plastic limit cannot be determined							
Plasticity Chart 				Liquid Limit 			



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Copyright: Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT9-GB-20-21.5 ft Sample#: B21-1462	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	
---	---	---	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.006 mm D ₍₁₀₎ = 0.010 mm D ₍₁₅₎ = 0.019 mm D ₍₃₀₎ = 0.058 mm D ₍₅₀₎ = 0.108 mm D ₍₆₀₎ = 0.159 mm D ₍₉₀₎ = 1.026 mm Dust Ratio = 38/73	% Gravel = 1.6% % Sand = 55.5% % Silt & Clay = 43.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 2.18 Coeff. of Uniformity, C _u = 16.63 Fineness Modulus = 0.99 Plastic Limit = n/a Moisture %, as sampled = 26.8% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	99%	99%	100.0%	0.0%
#4	4.75	98%	98%	100.0%	0.0%
#8	2.36	95%	95%	100.0%	0.0%
#10	2.00	94%	94%	100.0%	0.0%
#16	1.18	91%	91%	100.0%	0.0%
#20	0.850	89%	89%	100.0%	0.0%
#30	0.600	85%	85%	100.0%	0.0%
#40	0.425	83%	83%	100.0%	0.0%
#50	0.300	74%	74%	100.0%	0.0%
#60	0.250	70%	70%	100.0%	0.0%
#80	0.180	62%	62%	100.0%	0.0%
#100	0.150	59%	59%	100.0%	0.0%
#140	0.106	50%	50%	100.0%	0.0%
#170	0.090	46%	46%	100.0%	0.0%
#200	0.075	43.0%	43.0%	100.0%	0.0%

Grain Size Distribution

+ Sieve Sizes — Max Specs — Min Specs — Sieve Results

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo



Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT9-GB-20-21.5 ft Sample#: B21-1462	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																																																																																				
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																																																																				
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Assumed Sp Gr :</td> <td style="width: 10%;">2.65</td> <td style="width: 60%;"></td> </tr> <tr> <td>Sample Weight:</td> <td>75.17</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td>1.11%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td>74.34</td> <td>grams</td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>19</td><td>24.0%</td><td>0.0496 mm</td></tr> <tr><td>2</td><td>16.5</td><td>20.8%</td><td>0.0357 mm</td></tr> <tr><td>5</td><td>13.5</td><td>17.1%</td><td>0.0230 mm</td></tr> <tr><td>15</td><td>9.5</td><td>12.0%</td><td>0.0136 mm</td></tr> <tr><td>30</td><td>8</td><td>10.1%</td><td>0.0097 mm</td></tr> <tr><td>60</td><td>5</td><td>6.3%</td><td>0.0069 mm</td></tr> <tr><td>240</td><td>2</td><td>2.5%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.3%</td><td>0.0014 mm</td></tr> </tbody> </table> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 30%;">1.6%</td> <td style="width: 40%;">Liquid Limit: n/a</td> </tr> <tr> <td>% Sand:</td> <td>55.5%</td> <td>Plastic Limit: n/a</td> </tr> <tr> <td>% Silt:</td> <td>38.8%</td> <td>Plasticity Index: n/a</td> </tr> <tr> <td>% Clay:</td> <td>4.2%</td> <td></td> </tr> </table>	Assumed Sp Gr :	2.65		Sample Weight:	75.17	grams	Hydroscopic Moist.:	1.11%		Adj. Sample Wgt :	74.34	grams	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	19	24.0%	0.0496 mm	2	16.5	20.8%	0.0357 mm	5	13.5	17.1%	0.0230 mm	15	9.5	12.0%	0.0136 mm	30	8	10.1%	0.0097 mm	60	5	6.3%	0.0069 mm	240	2	2.5%	0.0035 mm	1440	1	1.3%	0.0014 mm	% Gravel:	1.6%	Liquid Limit: n/a	% Sand:	55.5%	Plastic Limit: n/a	% Silt:	38.8%	Plasticity Index: n/a	% Clay:	4.2%		<p>ACCREDITED Certificate #: 1366.01</p>	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3" style="text-align: center;">Sieve Analysis</th> </tr> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>99%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>98%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>94%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>89%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>83%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>59%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>43.0%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>42.2%</td><td>0.074 mm</td></tr> <tr><td></td><td>30.9%</td><td>0.050 mm</td></tr> <tr><td></td><td>15.4%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>4.2%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.6%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Analysis			Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	99%	6.300 mm	#4	98%	4.750 mm	#10	94%	2.000 mm	#20	89%	0.850 mm	#40	83%	0.425 mm	#100	59%	0.150 mm	#200	43.0%	0.075 mm	Silts	42.2%	0.074 mm		30.9%	0.050 mm		15.4%	0.020 mm	Clays	4.2%	0.005 mm		1.6%	0.002 mm	Colloids	0.9%	0.001 mm
Assumed Sp Gr :	2.65																																																																																																																																					
Sample Weight:	75.17	grams																																																																																																																																				
Hydroscopic Moist.:	1.11%																																																																																																																																					
Adj. Sample Wgt :	74.34	grams																																																																																																																																				
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																																			
1	19	24.0%	0.0496 mm																																																																																																																																			
2	16.5	20.8%	0.0357 mm																																																																																																																																			
5	13.5	17.1%	0.0230 mm																																																																																																																																			
15	9.5	12.0%	0.0136 mm																																																																																																																																			
30	8	10.1%	0.0097 mm																																																																																																																																			
60	5	6.3%	0.0069 mm																																																																																																																																			
240	2	2.5%	0.0035 mm																																																																																																																																			
1440	1	1.3%	0.0014 mm																																																																																																																																			
% Gravel:	1.6%	Liquid Limit: n/a																																																																																																																																				
% Sand:	55.5%	Plastic Limit: n/a																																																																																																																																				
% Silt:	38.8%	Plasticity Index: n/a																																																																																																																																				
% Clay:	4.2%																																																																																																																																					
Sieve Analysis																																																																																																																																						
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																																				
3.0"	100%	75.000 mm																																																																																																																																				
2.0"	100%	50.000 mm																																																																																																																																				
1.5"	100%	37.500 mm																																																																																																																																				
1.25"	100%	31.500 mm																																																																																																																																				
1.0"	100%	25.000 mm																																																																																																																																				
3/4"	100%	19.000 mm																																																																																																																																				
5/8"	100%	16.000 mm																																																																																																																																				
1/2"	100%	12.500 mm																																																																																																																																				
3/8"	100%	9.500 mm																																																																																																																																				
1/4"	99%	6.300 mm																																																																																																																																				
#4	98%	4.750 mm																																																																																																																																				
#10	94%	2.000 mm																																																																																																																																				
#20	89%	0.850 mm																																																																																																																																				
#40	83%	0.425 mm																																																																																																																																				
#100	59%	0.150 mm																																																																																																																																				
#200	43.0%	0.075 mm																																																																																																																																				
Silts	42.2%	0.074 mm																																																																																																																																				
	30.9%	0.050 mm																																																																																																																																				
	15.4%	0.020 mm																																																																																																																																				
Clays	4.2%	0.005 mm																																																																																																																																				
	1.6%	0.002 mm																																																																																																																																				
Colloids	0.9%	0.001 mm																																																																																																																																				
USDA Soil Textural Classification																																																																																																																																						
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Sand:</td> <td style="width: 70%;">2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </table> <p style="text-align: center;">USDA Soil Textural Classification Sandy Loam</p>	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																																																
% Sand:	2.0 - 0.05 mm																																																																																																																																					
% Silt:	0.05 - 0.002 mm																																																																																																																																					
% Clay:	< 0.002 mm																																																																																																																																					

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1462
 Sample Date: 7/8/2021
 Test Date: 8/31/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT9-GB-20-21.5 ft
 Visual Soil Description: brown silty sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0042
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	22.7	
	Initial	Post-Consolidation
Dry Density (PCF):	112.8	114.5
Void Ratio:	0.494	0.471
Porosity (%):	33.0	32.0
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	21.4	
	Initial	Post-Consolidation
Dry Density (PCF):	113.5	120.4
Void Ratio:	0.485	0.399
Porosity (%):	32.7	28.5
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	19.9	
	Initial	Post-Consolidation
Dry Density (PCF):	114.3	123.5
Void Ratio:	0.474	0.364
Porosity (%):	32.1	26.7
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	39	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	400	860	1590
Residual Horizontal Stress, τ_r (PSF):	260	600	1300



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net



Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT7-GB-0-5.7 ft Sample#: B21-1464	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: brown	 Certificate #: 1366.01
---	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.066 mm	% Gravel = 0.2%	Coeff. of Curvature, C _c = 1.24
D ₍₁₀₎ = 0.135 mm	% Sand = 94.1%	Coeff. of Uniformity, C _u = 2.73
D ₍₁₅₎ = 0.170 mm	% Silt & Clay = 5.6%	Fineness Modulus = 1.68
D ₍₃₀₎ = 0.247 mm	Liquid Limit = 0.0%	Plastic Limit = 0.0%
D ₍₅₀₎ = 0.327 mm	Plasticity Index = 0.0%	Moisture %, as sampled = 29.1%
D ₍₆₀₎ = 0.367 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.741 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 4/53	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	95%	96%	100.0%	0.0%
#20	0.850	95%	95%	100.0%	0.0%
#30	0.600		83%	100.0%	0.0%
#40	0.425	75%	75%	100.0%	0.0%
#50	0.300		43%	100.0%	0.0%
#60	0.250	31%	31%	100.0%	0.0%
#80	0.180		17%	100.0%	0.0%
#100	0.150	11%	11%	100.0%	0.0%
#140	0.106		8%	100.0%	0.0%
#170	0.090		7%	100.0%	0.0%
#200	0.075	5.6%	5.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo



Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT7-GB-8.5-18.5 ft Sample#: B21-1466	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? N/A

D ₍₅₎ = 0.022 mm	% Gravel = 0.2%	Coeff. of Curvature, C _c = 1.55
D ₍₁₀₎ = 0.063 mm	% Sand = 85.4%	Coeff. of Uniformity, C _u = 5.61
D ₍₁₅₎ = 0.080 mm	% Silt & Clay = 14.4%	Fineness Modulus = 1.54
D ₍₃₀₎ = 0.186 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.299 mm	Plasticity Index = n/a	Moisture %, as sampled = 33.4%
D ₍₆₀₎ = 0.354 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.799 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 13/66	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		98%	100.0%	0.0%
#10	2.00	97%	97%	100.0%	0.0%
#16	1.18		94%	100.0%	0.0%
#20	0.850	92%	92%	100.0%	0.0%
#30	0.600		81%	100.0%	0.0%
#40	0.425	73%	73%	100.0%	0.0%
#50	0.300		50%	100.0%	0.0%
#60	0.250	41%	41%	100.0%	0.0%
#80	0.180		29%	100.0%	0.0%
#100	0.150	24%	24%	100.0%	0.0%
#140	0.106		18%	100.0%	0.0%
#170	0.090		16%	100.0%	0.0%
#200	0.075	14.4%	14.4%	100.0%	0.0%




All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo




Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT7-GB-8.5-18.5 ft Sample#: B21-1466	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 31-Aug-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Assumed Sp Gr : 2.65 Sample Weight: 75.16 grams Hydroscopic Moist.: 1.29% Adj. Sample Wgt : 74.20 grams		Sieve Analysis Grain Size Distribution																																																																					
																																																																							
Hydrometer <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>5</td><td>6.6%</td><td>0.0537 mm</td></tr> <tr><td>2</td><td>4.5</td><td>5.9%</td><td>0.0381 mm</td></tr> <tr><td>5</td><td>4</td><td>5.2%</td><td>0.0241 mm</td></tr> <tr><td>15</td><td>3</td><td>3.9%</td><td>0.0140 mm</td></tr> <tr><td>30</td><td>2.5</td><td>3.3%</td><td>0.0100 mm</td></tr> <tr><td>60</td><td>2</td><td>2.6%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>1</td><td>1.3%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.3%</td><td>0.0014 mm</td></tr> </tbody> </table>	Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	5	6.6%	0.0537 mm	2	4.5	5.9%	0.0381 mm	5	4	5.2%	0.0241 mm	15	3	3.9%	0.0140 mm	30	2.5	3.3%	0.0100 mm	60	2	2.6%	0.0070 mm	240	1	1.3%	0.0035 mm	1440	1	1.3%	0.0014 mm																																			
Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	5	6.6%	0.0537 mm																																																																				
2	4.5	5.9%	0.0381 mm																																																																				
5	4	5.2%	0.0241 mm																																																																				
15	3	3.9%	0.0140 mm																																																																				
30	2.5	3.3%	0.0100 mm																																																																				
60	2	2.6%	0.0070 mm																																																																				
240	1	1.3%	0.0035 mm																																																																				
1440	1	1.3%	0.0014 mm																																																																				
% Gravel: 0.2% % Sand: 85.4% % Silt: 12.5% % Clay: 1.9%	Liquid Limit: n/a Plastic Limit: n/a Plasticity Index: n/a	<table border="1" style="width: 100%;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>97%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>92%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>73%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>24%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>14.4%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>14.0%</td><td>0.074 mm</td></tr> <tr><td></td><td>6.5%</td><td>0.050 mm</td></tr> <tr><td></td><td>4.7%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>1.9%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.3%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	97%	2.000 mm	#20	92%	0.850 mm	#40	73%	0.425 mm	#100	24%	0.150 mm	#200	14.4%	0.075 mm	Silts	14.0%	0.074 mm		6.5%	0.050 mm		4.7%	0.020 mm	Clays	1.9%	0.005 mm		1.3%	0.002 mm	Colloids	0.9%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	97%	2.000 mm																																																																					
#20	92%	0.850 mm																																																																					
#40	73%	0.425 mm																																																																					
#100	24%	0.150 mm																																																																					
#200	14.4%	0.075 mm																																																																					
Silts	14.0%	0.074 mm																																																																					
	6.5%	0.050 mm																																																																					
	4.7%	0.020 mm																																																																					
Clays	1.9%	0.005 mm																																																																					
	1.3%	0.002 mm																																																																					
Colloids	0.9%	0.001 mm																																																																					
USDA Soil Textural Classification																																																																							
% Sand: % Silt: % Clay:	Particle Size 2.0 - 0.05 mm 0.05 - 0.002 mm < 0.002 mm																																																																						
USDA Soil Textural Classification																																																																							
Sand																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1466
 Sample Date: 7/9/2021
 Test Date: 9/1/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT7-GB-8.5-18.5 ft
 Visual Soil Description: brown silty sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	36.5	
	Initial	Post-Consolidation
Dry Density (PCF):	99.2	102.6
Void Ratio:	0.698	0.642
Porosity (%):	41.1	39.1
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	37.7	
	Initial	Post-Consolidation
Dry Density (PCF):	97.5	105.0
Void Ratio:	0.728	0.605
Porosity (%):	42.1	37.7
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	36.6	
	Initial	Post-Consolidation
Dry Density (PCF):	99.4	106.9
Void Ratio:	0.694	0.576
Porosity (%):	41.0	36.5
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	38	34
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	400	840	1520
Residual Horizontal Stress, τ_r (PSF):	260	670	1350



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: September 30, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1535-1552
Date sampled: July 9, 2021

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
<input checked="" type="checkbox"/>	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
<input checked="" type="checkbox"/>	Moisture Content	Please See Attached Report	<input checked="" type="checkbox"/>	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		<input checked="" type="checkbox"/>	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
<input checked="" type="checkbox"/>	Hydrometer Analysis	Please See Attached Reports			
<input checked="" type="checkbox"/>	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: September 1, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-1535	LDW21-GT7-GB-5.7-8.5 ft	220.0	955.7	691.6	264.1	471.6	56.0%
B21-1536	LDW21-GT7-GB-18.5-23.5 ft	233.7	1022.0	763.2	258.8	529.5	48.9%
B21-1537	LDW21-GT7-GB-23.5-25 ft	229.6	808.5	686.6	121.9	457.0	26.7%
B21-1538	LDW21-GT3-GB-0-1.5 ft	222.7	822.9	608.9	214.0	386.2	55.4%
B21-1539	LDW21-GT3-GB-0-8 ft	223.1	775.1	560.8	214.3	337.7	63.5%
B21-1540	LDW21-GT3-GB-8-9.5 ft	235.0	596.2	499.4	96.8	264.4	36.6%
B21-1541	LDW21-GT3-GB-13.6-18 ft	224.3	840.2	686.6	153.6	462.3	33.2%
B21-1542	LDW21-GT3-GB-18-19.5 ft	208.8	713.1	597.6	115.5	388.8	29.7%
B21-1543	LDW21-GT2-GB-0-1.5 ft	221.9	1015.5	706.7	308.8	484.8	63.7%
B21-1544	LDW21-GT2-GB-0-9 ft	221.9	1057.2	726.4	330.8	504.5	65.6%
B21-1545	LDW21-GT2-GB-9-10.5 ft	234.7	881.9	693.4	188.5	458.7	41.1%
B21-1546	LDW21-GT2-GB-16-19ft	319.9	776.4	594.5	181.9	274.6	66.2%
B21-1547	LDW21-GT1-GB-19-20.5 ft	268.9	932.1	798.3	133.8	529.4	25.3%
B21-1548	LDW21-GT1-GB-0-1.5 ft	270.2	991.8	734.1	257.7	463.9	55.6%
B21-1549	LDW21-GT1-GB-0-10 ft	266.5	951.7	694.7	257.0	428.2	60.0%
B21-1550	LDW21-GT1-GB-10-11.5 ft	303.8	1160.1	875.7	284.4	571.9	49.7%
B21-1551	LDW21-GT1-GB-10-20 ft	311.0	1013.9	756.9	257.0	445.9	57.6%
B21-1552	LDW21-GT1-GB-20-21.5 ft	306.5	1105.1	926.6	178.5	620.1	28.8%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 
 Meghan Blodgett-Carrillo




Moisture Content - ASTM D854

Project: Q.C. - Lower Duwamish Waterway
 Project #: 21B233
 Date Received: July 29, 2021
 Date Tested: September 1, 2021

Client: Anchor QEA
 Sampled by: Client
 Tested by: A. Eifrig

Sample #	Location	Tare	Dry Soil + Tare	Mass of Dry Soil	Pycno ID	Mass of Pycno	Volume of Pycno	Density of Water @ Tx	Mass of Pycno filled w/ water & soils	Mass of Pycno filled w/ water	Temp. of Water, 0.1 *C	SpG of Soils	Temp. Correction Factor	Corrected SpG
B21-1536	LDW21-GT7-GB-18.5-23.5 ft	414.24	485.84	71.6	TSA-010	180.3	499.5	0.99752	753.80	709.46	23.1	2.6265591	0.99931	2.6247467
B21-1541	LDW21-GT3-GB-13.6-18 ft	379.79	481.87	102.1	TSA-011	190.3	499.5	0.99749	752.15	688.62	23.2	2.6482538	0.99929	2.6463735
B21-1546	LDW21-GT2-GB-16-19ft	417.55	468.99	51.4	TSA-017	187.9	499.4	0.99754	717.30	686.06	23.0	2.546361	0.99933	2.5446549
B21-1549	LDW21-GT1-GB-0-10 ft	411.71	488.70	77.0	TSA-022	198.0	499.5	0.99749	742.60	696.19	23.2	2.5179566	0.99929	2.5161689
B21-1551	LDW21-GT1-GB-10-20 ft	380.03	474.50	94.5	TSA-020	195.0	499.5	0.99749	750.48	693.27	23.2	2.5356867	0.99929	2.5338864

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT7-GB-5.7-8.5 ft Sample #: B21-1535	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Visual Identification Sand with Silt and Clay Sample Color brown
--	--	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	34.38	32.59	32.44			
Weight of Dry Soils + Pan:	30.26	28.85	28.70			
Weight of Pan:	19.58	19.73	19.89			
Weight of Dry Soils:	10.68	9.12	8.81			
Weight of Moisture:	4.12	3.74	3.74			
% Moisture:	38.6 %	41.0 %	42.5 %			
Number of Blows:	33	24	13			



Liquid Limit @ 25 Blows: 40 %
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT7-GB-18.5-23.5 ft Sample#: B21-1536	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	
---	--	---	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.009 mm D ₍₁₀₎ = 0.017 mm D ₍₁₅₎ = 0.026 mm D ₍₃₀₎ = 0.052 mm D ₍₅₀₎ = 0.094 mm D ₍₆₀₎ = 0.122 mm D ₍₉₀₎ = 0.372 mm Dust Ratio = 11/24	% Gravel = 0.1% % Sand = 56.4% % Silt & Clay = 43.5% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.27 Coeff. of Uniformity, C _u = 7.08 Fineness Modulus = 0.55 Plastic Limit = 0.0% Moisture %, as sampled = 48.9% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	97%	97%	100.0%	0.0%
#20	0.850	96%	96%	100.0%	0.0%
#30	0.600	95%	95%	100.0%	0.0%
#40	0.425	95%	95%	100.0%	0.0%
#50	0.300	83%	83%	100.0%	0.0%
#60	0.250	79%	79%	100.0%	0.0%
#80	0.180	72%	72%	100.0%	0.0%
#100	0.150	70%	70%	100.0%	0.0%
#140	0.106	54%	54%	100.0%	0.0%
#170	0.090	49%	49%	100.0%	0.0%
#200	0.075	43.5%	43.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT3-GB-0-8 ft Sample #: B21-1539	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Visual Identification Sandy Silt Sample Color brown
--	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT3-GB-8-9.5 ft Sample#: B21-1540	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.017 mm D ₍₁₀₎ = 0.034 mm D ₍₁₅₎ = 0.051 mm D ₍₃₀₎ = 0.100 mm D ₍₅₀₎ = 0.178 mm D ₍₆₀₎ = 0.238 mm D ₍₉₀₎ = 0.417 mm Dust Ratio = 19/78	% Gravel = 0.5% % Sand = 77.3% % Silt & Clay = 22.3% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.25 Coeff. of Uniformity, C _u = 7.06 Fineness Modulus = 0.99 Plastic Limit = 0.0% Moisture %, as sampled = 36.6% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18		95%	100.0%	0.0%
#20	0.850		93%	100.0%	0.0%
#30	0.600		92%	100.0%	0.0%
#40	0.425	91%	91%	100.0%	0.0%
#50	0.300		70%	100.0%	0.0%
#60	0.250		62%	100.0%	0.0%
#80	0.180		50%	100.0%	0.0%
#100	0.150	45%	45%	100.0%	0.0%
#140	0.106		32%	100.0%	0.0%
#170	0.090		27%	100.0%	0.0%
#200	0.075	22.3%	22.3%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1540
 Sample Date: 7/9/2021
 Test Date: 9/24/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT3-GB-8-9.5 ft
 Visual Soil Description: brown silty sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%)	33.7	
	Initial	Post-Consolidation
Dry Density (PCF):	102.4	104.0
Void Ratio:	0.645	0.620
Porosity (%):	39.2	38.3
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%)	31.2	
	Initial	Post-Consolidation
Dry Density (PCF):	104.0	109.1
Void Ratio:	0.620	0.544
Porosity (%):	38.3	35.2
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%)	30.1	
	Initial	Post-Consolidation
Dry Density (PCF):	105.0	110.4
Void Ratio:	0.605	0.526
Porosity (%):	37.7	34.5
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	38	36
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	360	740	1590
Residual Horizontal Stress, τ_h (PSF):	280	670	1470



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT3-GB-13.6-18 ft Sample#: B21-1541	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	
---	--	---	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? N/A

D ₍₅₎ = 0.140 mm	% Gravel = 0.2%	Coeff. of Curvature, C _c = 1.00
D ₍₁₀₎ = 0.157 mm	% Sand = 115.1%	Coeff. of Uniformity, C _u = 2.22
D ₍₁₅₎ = 0.176 mm	% Silt & Clay = -15.2%	Fineness Modulus = 1.74
D ₍₃₀₎ = 0.234 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.311 mm	Plasticity Index = n/a	Moisture %, as sampled = 33.2%
D ₍₆₀₎ = 0.349 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 1.234 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = -17/89	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		89%	100.0%	0.0%
#20	0.850		85%	100.0%	0.0%
#30	0.600		82%	100.0%	0.0%
#40	0.425	80%	80%	100.0%	0.0%
#50	0.300		47%	100.0%	0.0%
#60	0.250		34%	100.0%	0.0%
#80	0.180		16%	100.0%	0.0%
#100	0.150	8%	8%	100.0%	0.0%
#140	0.106		-6%	100.0%	0.0%
#170	0.090		-11%	100.0%	0.0%
#200	0.075	-15.2%	-15.2%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT2-GB-0-9 ft Sample #: B21-1544	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Visual Identification Sandy Silt Sample Color brown
--	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT2-GB-16-19 ft Sample#: B21-1546	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Visual Identification Sandy Silt with Clay Sample Color: brown	 ACCREDITED Certificate #: 1366.01
---	--	---	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.003 mm	% Gravel = 0.3%	Coeff. of Curvature, C _c = 1.57
D ₍₁₀₎ = 0.006 mm	% Sand = 36.4%	Coeff. of Uniformity, C _u = 12.88
D ₍₁₅₎ = 0.009 mm	% Silt & Clay = 63.3%	Fineness Modulus = 0.28
D ₍₃₀₎ = 0.025 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.061 mm	Plasticity Index = n/a	Moisture %, as sampled = 66.2%
D ₍₆₀₎ = 0.072 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.265 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 25/39	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	99%	99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	99%	99%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	92%	92%	100.0%	0.0%
#60	0.250	89%	89%	100.0%	0.0%
#80	0.180	85%	85%	100.0%	0.0%
#100	0.150	84%	84%	100.0%	0.0%
#140	0.106	72%	72%	100.0%	0.0%
#170	0.090	67%	67%	100.0%	0.0%
#200	0.075	63.3%	63.3%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT2-GB-16-19 ft Sample#: B21-1546	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Visual Identification Sandy Silt with Clay Sample Color brown																																																																																																									
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																																									
Sp Gr : 2.54 Sample Weight: 75.85 grams Hydroscopic Moist.: 6.24% Adj. Sample Wgt : 71.39 grams																																																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>27</td><td>38.7%</td><td>0.0494 mm</td></tr> <tr><td>2</td><td>23.5</td><td>33.7%</td><td>0.0358 mm</td></tr> <tr><td>5</td><td>20.5</td><td>29.4%</td><td>0.0231 mm</td></tr> <tr><td>15</td><td>14.5</td><td>20.8%</td><td>0.0138 mm</td></tr> <tr><td>30</td><td>11.5</td><td>16.5%</td><td>0.0099 mm</td></tr> <tr><td>60</td><td>9</td><td>12.9%</td><td>0.0071 mm</td></tr> <tr><td>240</td><td>4.5</td><td>6.4%</td><td>0.0036 mm</td></tr> <tr><td>1440</td><td>1.5</td><td>2.1%</td><td>0.0015 mm</td></tr> </tbody> </table>		Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	27	38.7%	0.0494 mm	2	23.5	33.7%	0.0358 mm	5	20.5	29.4%	0.0231 mm	15	14.5	20.8%	0.0138 mm	30	11.5	16.5%	0.0099 mm	60	9	12.9%	0.0071 mm	240	4.5	6.4%	0.0036 mm	1440	1.5	2.1%	0.0015 mm	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>99%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>84%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>63.3%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>62.3%</td><td>0.074 mm</td></tr> <tr><td></td><td>47.6%</td><td>0.050 mm</td></tr> <tr><td></td><td>26.5%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>9.0%</td><td>0.005 mm</td></tr> <tr><td></td><td>3.1%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.4%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	99%	2.000 mm	#20	99%	0.850 mm	#40	99%	0.425 mm	#100	84%	0.150 mm	#200	63.3%	0.075 mm	Silts	62.3%	0.074 mm		47.6%	0.050 mm		26.5%	0.020 mm	Clays	9.0%	0.005 mm		3.1%	0.002 mm	Colloids	1.4%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																								
1	27	38.7%	0.0494 mm																																																																																																								
2	23.5	33.7%	0.0358 mm																																																																																																								
5	20.5	29.4%	0.0231 mm																																																																																																								
15	14.5	20.8%	0.0138 mm																																																																																																								
30	11.5	16.5%	0.0099 mm																																																																																																								
60	9	12.9%	0.0071 mm																																																																																																								
240	4.5	6.4%	0.0036 mm																																																																																																								
1440	1.5	2.1%	0.0015 mm																																																																																																								
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																									
3.0"	100%	75.000 mm																																																																																																									
2.0"	100%	50.000 mm																																																																																																									
1.5"	100%	37.500 mm																																																																																																									
1.25"	100%	31.500 mm																																																																																																									
1.0"	100%	25.000 mm																																																																																																									
3/4"	100%	19.000 mm																																																																																																									
5/8"	100%	16.000 mm																																																																																																									
1/2"	100%	12.500 mm																																																																																																									
3/8"	100%	9.500 mm																																																																																																									
1/4"	100%	6.300 mm																																																																																																									
#4	100%	4.750 mm																																																																																																									
#10	99%	2.000 mm																																																																																																									
#20	99%	0.850 mm																																																																																																									
#40	99%	0.425 mm																																																																																																									
#100	84%	0.150 mm																																																																																																									
#200	63.3%	0.075 mm																																																																																																									
Silts	62.3%	0.074 mm																																																																																																									
	47.6%	0.050 mm																																																																																																									
	26.5%	0.020 mm																																																																																																									
Clays	9.0%	0.005 mm																																																																																																									
	3.1%	0.002 mm																																																																																																									
Colloids	1.4%	0.001 mm																																																																																																									
USDA Soil Textural Classification																																																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																		
	Particle Size																																																																																																										
% Sand:	2.0 - 0.05 mm																																																																																																										
% Silt:	0.05 - 0.002 mm																																																																																																										
% Clay:	< 0.002 mm																																																																																																										
USDA Soil Textural Classification																																																																																																											
Sandy Loam																																																																																																											

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1546
 Sample Date: 7/9/2021
 Test Date: 9/27/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT2-GB-16-19 ft
 Visual Soil Description: brown sandy silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0042
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%)	38.6	
	Initial	Post-Consolidation
Dry Density (PCF):	100.0	106.5
Void Ratio:	0.684	0.581
Porosity (%):	40.6	36.8
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%)	36.2	
	Initial	Post-Consolidation
Dry Density (PCF):	101.4	111.3
Void Ratio:	0.661	0.514
Porosity (%):	39.8	34.0
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%)	34.6	
	Initial	Post-Consolidation
Dry Density (PCF):	102.5	110.5
Void Ratio:	0.643	0.525
Porosity (%):	39.1	34.4
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	36	33
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	330	680	1490
Residual Horizontal Stress, τ_h (PSF):	280	590	1320



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT1-GB-0-10 ft Sample #: B21-1549	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Visual Identification Silty Sand Sample Color brown
---	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT1-GB-10-20 ft Sample#: B21-1551	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.013 mm	% Gravel = 0.5%	Coeff. of Curvature, C _c = 1.11
D ₍₁₀₎ = 0.037 mm	% Sand = 66.2%	Coeff. of Uniformity, C _u = 3.34
D ₍₁₅₎ = 0.059 mm	% Silt & Clay = 33.4%	Fineness Modulus = 0.42
D ₍₃₀₎ = 0.072 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.106 mm	Plasticity Index = n/a	Moisture %, as sampled = 57.6%
D ₍₆₀₎ = 0.125 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.327 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 33/98	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18		99%	100.0%	0.0%
#20	0.850		99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		87%	100.0%	0.0%
#60	0.250		83%	100.0%	0.0%
#80	0.180		76%	100.0%	0.0%
#100	0.150	73%	73%	100.0%	0.0%
#140	0.106		50%	100.0%	0.0%
#170	0.090		41%	100.0%	0.0%
#200	0.075	33.4%	33.4%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client: Anchor QEA Date Tested: 1-Sep-21 Source: LDW21-GT1-GB-10-20 ft Tested By: C. Kriss Sample#: B21-1551	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																																																																																							
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																																																							
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Sp Gr :</td> <td style="width: 20%;">2.53</td> <td style="width: 50%;"></td> </tr> <tr> <td>Sample Weight:</td> <td>75.48</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td>2.34%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td>73.75</td> <td>grams</td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>8</td><td>11.1%</td><td>0.0554 mm</td></tr> <tr><td>2</td><td>7.5</td><td>10.4%</td><td>0.0394 mm</td></tr> <tr><td>5</td><td>5.5</td><td>7.6%</td><td>0.0252 mm</td></tr> <tr><td>15</td><td>4</td><td>5.5%</td><td>0.0146 mm</td></tr> <tr><td>30</td><td>3</td><td>4.2%</td><td>0.0104 mm</td></tr> <tr><td>60</td><td>1.5</td><td>2.1%</td><td>0.0074 mm</td></tr> <tr><td>240</td><td>1</td><td>1.4%</td><td>0.0037 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.4%</td><td>0.0015 mm</td></tr> </tbody> </table> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 20%;">0.5%</td> <td style="width: 50%;">Liquid Limit: n/a</td> </tr> <tr> <td>% Sand:</td> <td>66.2%</td> <td>Plastic Limit: n/a</td> </tr> <tr> <td>% Silt:</td> <td>31.8%</td> <td>Plasticity Index: n/a</td> </tr> <tr> <td>% Clay:</td> <td>1.6%</td> <td></td> </tr> </table>	Sp Gr :	2.53		Sample Weight:	75.48	grams	Hydroscopic Moist.:	2.34%		Adj. Sample Wgt :	73.75	grams	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	8	11.1%	0.0554 mm	2	7.5	10.4%	0.0394 mm	5	5.5	7.6%	0.0252 mm	15	4	5.5%	0.0146 mm	30	3	4.2%	0.0104 mm	60	1.5	2.1%	0.0074 mm	240	1	1.4%	0.0037 mm	1440	1	1.4%	0.0015 mm	% Gravel:	0.5%	Liquid Limit: n/a	% Sand:	66.2%	Plastic Limit: n/a	% Silt:	31.8%	Plasticity Index: n/a	% Clay:	1.6%		<table style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3" style="text-align: center;">Sieve Analysis</th> </tr> <tr> <th colspan="3" style="text-align: center;">Grain Size Distribution</th> </tr> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>99%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>73%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>33.4%</td><td>0.075 mm</td></tr> <tr><td style="text-align: center;">Silts</td><td>32.2%</td><td>0.074 mm</td></tr> <tr><td></td><td>12.5%</td><td>0.050 mm</td></tr> <tr><td></td><td>6.6%</td><td>0.020 mm</td></tr> <tr><td style="text-align: center;">Clays</td><td>1.6%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.4%</td><td>0.002 mm</td></tr> <tr><td style="text-align: center;">Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </table>	Sieve Analysis			Grain Size Distribution			Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	99%	2.000 mm	#20	99%	0.850 mm	#40	99%	0.425 mm	#100	73%	0.150 mm	#200	33.4%	0.075 mm	Silts	32.2%	0.074 mm		12.5%	0.050 mm		6.6%	0.020 mm	Clays	1.6%	0.005 mm		1.4%	0.002 mm	Colloids	0.9%	0.001 mm
Sp Gr :	2.53																																																																																																																																							
Sample Weight:	75.48	grams																																																																																																																																						
Hydroscopic Moist.:	2.34%																																																																																																																																							
Adj. Sample Wgt :	73.75	grams																																																																																																																																						
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																																					
1	8	11.1%	0.0554 mm																																																																																																																																					
2	7.5	10.4%	0.0394 mm																																																																																																																																					
5	5.5	7.6%	0.0252 mm																																																																																																																																					
15	4	5.5%	0.0146 mm																																																																																																																																					
30	3	4.2%	0.0104 mm																																																																																																																																					
60	1.5	2.1%	0.0074 mm																																																																																																																																					
240	1	1.4%	0.0037 mm																																																																																																																																					
1440	1	1.4%	0.0015 mm																																																																																																																																					
% Gravel:	0.5%	Liquid Limit: n/a																																																																																																																																						
% Sand:	66.2%	Plastic Limit: n/a																																																																																																																																						
% Silt:	31.8%	Plasticity Index: n/a																																																																																																																																						
% Clay:	1.6%																																																																																																																																							
Sieve Analysis																																																																																																																																								
Grain Size Distribution																																																																																																																																								
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																																						
3.0"	100%	75.000 mm																																																																																																																																						
2.0"	100%	50.000 mm																																																																																																																																						
1.5"	100%	37.500 mm																																																																																																																																						
1.25"	100%	31.500 mm																																																																																																																																						
1.0"	100%	25.000 mm																																																																																																																																						
3/4"	100%	19.000 mm																																																																																																																																						
5/8"	100%	16.000 mm																																																																																																																																						
1/2"	100%	12.500 mm																																																																																																																																						
3/8"	100%	9.500 mm																																																																																																																																						
1/4"	100%	6.300 mm																																																																																																																																						
#4	100%	4.750 mm																																																																																																																																						
#10	99%	2.000 mm																																																																																																																																						
#20	99%	0.850 mm																																																																																																																																						
#40	99%	0.425 mm																																																																																																																																						
#100	73%	0.150 mm																																																																																																																																						
#200	33.4%	0.075 mm																																																																																																																																						
Silts	32.2%	0.074 mm																																																																																																																																						
	12.5%	0.050 mm																																																																																																																																						
	6.6%	0.020 mm																																																																																																																																						
Clays	1.6%	0.005 mm																																																																																																																																						
	1.4%	0.002 mm																																																																																																																																						
Colloids	0.9%	0.001 mm																																																																																																																																						
USDA Soil Textural Classification																																																																																																																																								
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 70%; text-align: center;">Particle Size</td> </tr> <tr> <td>% Sand:</td> <td style="text-align: center;">2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td style="text-align: center;">0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td style="text-align: center;">< 0.002 mm</td> </tr> </table> <p style="text-align: center;">USDA Soil Textural Classification Sand</p>		Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																																																
	Particle Size																																																																																																																																							
% Sand:	2.0 - 0.05 mm																																																																																																																																							
% Silt:	0.05 - 0.002 mm																																																																																																																																							
% Clay:	< 0.002 mm																																																																																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1551
 Sample Date: 7/9/2021
 Test Date: 9/23/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT1-GB-10-20 ft
 Visual Soil Description: brown silty sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
	Initial Moisture Content (%)	
	Initial	Post-Consolidation
Dry Density (PCF):	106.5	108.9
Void Ratio:	0.581	0.547
Porosity (%):	36.8	35.4
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
	Initial Moisture Content (%)	
	Initial	Post-Consolidation
Dry Density (PCF):	598.3	612.5
Void Ratio:	-0.718	-0.725
Porosity (%):	-255.1	-263.6
Degree of Saturation (%):	-111.5	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
	Initial Moisture Content (%)	
	Initial	Post-Consolidation
Dry Density (PCF):	107.6	113.2
Void Ratio:	0.566	0.488
Porosity (%):	36.1	32.8
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	38	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	310	760	1560
Residual Horizontal Stress, τ_h (PSF):	260	600	1250



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 1, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1563-1577
Date sampled: 7-12-21 & 7-13-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT13-GB-0-11 ft Sample#: B21-1564	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.008 mm D ₍₁₀₎ = 0.019 mm D ₍₁₅₎ = 0.053 mm D ₍₃₀₎ = 0.121 mm D ₍₅₀₎ = 0.244 mm D ₍₆₀₎ = 0.301 mm D ₍₉₀₎ = 1.175 mm Dust Ratio = 26/87	% Gravel = 0.4% % Sand = 75.2% % Silt & Clay = 24.4% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 2.52 Coeff. of Uniformity, C _u = 15.71 Fineness Modulus = 1.34 Plastic Limit = 0.0% Moisture %, as sampled = 38.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18		90%	100.0%	0.0%
#20	0.850		86%	100.0%	0.0%
#30	0.600		84%	100.0%	0.0%
#40	0.425	82%	82%	100.0%	0.0%
#50	0.300		60%	100.0%	0.0%
#60	0.250		51%	100.0%	0.0%
#80	0.180		39%	100.0%	0.0%
#100	0.150	34%	34%	100.0%	0.0%
#140	0.106		28%	100.0%	0.0%
#170	0.090		26%	100.0%	0.0%
#200	0.075	24.4%	24.4%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo

Hydrometer Report

<p>Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client: Anchor QEA Date Tested: 1-Sep-21 Source: LDW21-GT13-GB-0-11 ft Tested By: C. Kriss Sample#: B21-1564</p>	<p>Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown</p>																																																																																																									
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																									
<p>Sp Gr : 2.61 Sample Weight: 100.15 grams Hydroscopic Moist.: 0.83% Adj. Sample Wgt : 99.33 grams</p> <div style="text-align: center;">  </div> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>14.5</td><td>14.6%</td><td>0.0519 mm</td></tr> <tr><td>2</td><td>13</td><td>13.1%</td><td>0.0369 mm</td></tr> <tr><td>5</td><td>11.5</td><td>11.6%</td><td>0.0236 mm</td></tr> <tr><td>15</td><td>8</td><td>8.1%</td><td>0.0139 mm</td></tr> <tr><td>30</td><td>6.5</td><td>6.6%</td><td>0.0099 mm</td></tr> <tr><td>60</td><td>4</td><td>4.0%</td><td>0.0071 mm</td></tr> <tr><td>240</td><td>1</td><td>1.0%</td><td>0.0036 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.0%</td><td>0.0015 mm</td></tr> </tbody> </table> <p style="margin-top: 10px;"> % Gravel: 0.4% Liquid Limit: 0.0 % % Sand: 75.2% Plastic Limit: 0.0 % % Silt: 22.2% Plasticity Index: 0.0 % % Clay: 2.2% </p>	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	14.5	14.6%	0.0519 mm	2	13	13.1%	0.0369 mm	5	11.5	11.6%	0.0236 mm	15	8	8.1%	0.0139 mm	30	6.5	6.6%	0.0099 mm	60	4	4.0%	0.0071 mm	240	1	1.0%	0.0036 mm	1440	1	1.0%	0.0015 mm	<p style="text-align: center;">Sieve Analysis Grain Size Distribution</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>99%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>86%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>82%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>34%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>24.4%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>24.0%</td><td>0.074 mm</td></tr> <tr><td></td><td>14.6%</td><td>0.050 mm</td></tr> <tr><td></td><td>10.3%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>2.2%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.0%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.7%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	99%	2.000 mm	#20	86%	0.850 mm	#40	82%	0.425 mm	#100	34%	0.150 mm	#200	24.4%	0.075 mm	Silts	24.0%	0.074 mm		14.6%	0.050 mm		10.3%	0.020 mm	Clays	2.2%	0.005 mm		1.0%	0.002 mm	Colloids	0.7%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																							
1	14.5	14.6%	0.0519 mm																																																																																																							
2	13	13.1%	0.0369 mm																																																																																																							
5	11.5	11.6%	0.0236 mm																																																																																																							
15	8	8.1%	0.0139 mm																																																																																																							
30	6.5	6.6%	0.0099 mm																																																																																																							
60	4	4.0%	0.0071 mm																																																																																																							
240	1	1.0%	0.0036 mm																																																																																																							
1440	1	1.0%	0.0015 mm																																																																																																							
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																								
3.0"	100%	75.000 mm																																																																																																								
2.0"	100%	50.000 mm																																																																																																								
1.5"	100%	37.500 mm																																																																																																								
1.25"	100%	31.500 mm																																																																																																								
1.0"	100%	25.000 mm																																																																																																								
3/4"	100%	19.000 mm																																																																																																								
5/8"	100%	16.000 mm																																																																																																								
1/2"	100%	12.500 mm																																																																																																								
3/8"	100%	9.500 mm																																																																																																								
1/4"	100%	6.300 mm																																																																																																								
#4	100%	4.750 mm																																																																																																								
#10	99%	2.000 mm																																																																																																								
#20	86%	0.850 mm																																																																																																								
#40	82%	0.425 mm																																																																																																								
#100	34%	0.150 mm																																																																																																								
#200	24.4%	0.075 mm																																																																																																								
Silts	24.0%	0.074 mm																																																																																																								
	14.6%	0.050 mm																																																																																																								
	10.3%	0.020 mm																																																																																																								
Clays	2.2%	0.005 mm																																																																																																								
	1.0%	0.002 mm																																																																																																								
Colloids	0.7%	0.001 mm																																																																																																								
USDA Soil Textural Classification																																																																																																										
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Sand:</td> <td>Particle Size</td> </tr> <tr> <td>% Silt:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Clay:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td></td> <td>< 0.002 mm</td> </tr> </table> <p style="text-align: center; margin-top: 10px;"> USDA Soil Textural Classification Loamy Sand </p>	% Sand:	Particle Size	% Silt:	2.0 - 0.05 mm	% Clay:	0.05 - 0.002 mm		< 0.002 mm																																																																																																		
% Sand:	Particle Size																																																																																																									
% Silt:	2.0 - 0.05 mm																																																																																																									
% Clay:	0.05 - 0.002 mm																																																																																																									
	< 0.002 mm																																																																																																									

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____

Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1564
 Sample Date: 7/12/2021
 Test Date: 9/20/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT13-GB-0-11 ft
 Visual Soil Description: brown sand with silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	32.6	
	Initial	Post-Consolidation
Dry Density (PCF):	104.7	106.1
Void Ratio:	0.608	0.589
Porosity (%):	37.8	37.0
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	30.5	
	Initial	Post-Consolidation
Dry Density (PCF):	105.5	108.0
Void Ratio:	0.597	0.560
Porosity (%):	37.4	35.9
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	31.4	
	Initial	Post-Consolidation
Dry Density (PCF):	105.7	113.8
Void Ratio:	0.595	0.481
Porosity (%):	37.3	32.5
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	35	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	330	790	1360
Residual Horizontal Stress, τ_h (PSF):	290	700	1230



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787


Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT13-GB-11-21 ft Sample#: B21-1566	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.020 mm D ₍₁₀₎ = 0.040 mm D ₍₁₅₎ = 0.060 mm D ₍₃₀₎ = 0.107 mm D ₍₅₀₎ = 0.177 mm D ₍₆₀₎ = 0.230 mm D ₍₉₀₎ = 0.388 mm Dust Ratio = 17/88	% Gravel = 0.3% % Sand = 81.0% % Silt & Clay = 18.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.25 Coeff. of Uniformity, C _u = 5.74 Fineness Modulus = 0.87 Plastic Limit = n/a Moisture %, as sampled = 36.0% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18		98%	100.0%	0.0%
#20	0.850		98%	100.0%	0.0%
#30	0.600		97%	100.0%	0.0%
#40	0.425	97%	97%	100.0%	0.0%
#50	0.300		73%	100.0%	0.0%
#60	0.250		64%	100.0%	0.0%
#80	0.180		51%	100.0%	0.0%
#100	0.150	45%	45%	100.0%	0.0%
#140	0.106		30%	100.0%	0.0%
#170	0.090		24%	100.0%	0.0%
#200	0.075	18.7%	18.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT13-GB-21-31 ft Sample#: B21-1568	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.021 mm D ₍₁₀₎ = 0.042 mm D ₍₁₅₎ = 0.063 mm D ₍₃₀₎ = 0.109 mm D ₍₅₀₎ = 0.177 mm D ₍₆₀₎ = 0.229 mm D ₍₉₀₎ = 0.385 mm Dust Ratio = 13/71	% Gravel = 0.1% % Sand = 82.1% % Silt & Clay = 17.9% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.23 Coeff. of Uniformity, C _u = 5.46 Fineness Modulus = 0.85 Plastic Limit = n/a Moisture %, as sampled = 34.3% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	100.0%	100.0%	0.0%
#20	0.850	98%	100.0%	100.0%	0.0%
#30	0.600	98%	100.0%	100.0%	0.0%
#40	0.425	98%	98%	100.0%	0.0%
#50	0.300	74%	74%	100.0%	0.0%
#60	0.250	64%	64%	100.0%	0.0%
#80	0.180	51%	51%	100.0%	0.0%
#100	0.150	45%	45%	100.0%	0.0%
#140	0.106	29%	29%	100.0%	0.0%
#170	0.090	23%	23%	100.0%	0.0%
#200	0.075	17.9%	17.9%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT19-GB-0-6.9 ft Sample#: B21-1571	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 ML, Silt with Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.004 mm D ₍₁₀₎ = 0.007 mm D ₍₁₅₎ = 0.009 mm D ₍₃₀₎ = 0.019 mm D ₍₅₀₎ = 0.051 mm D ₍₆₀₎ = 0.062 mm D ₍₉₀₎ = 0.186 mm Dust Ratio = 59/79	% Gravel = 1.2% % Sand = 27.1% % Silt & Clay = 71.7% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.88 Coeff. of Uniformity, C _u = 9.46 Fineness Modulus = 0.29 Plastic Limit = 0.0% Moisture %, as sampled = 78.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	99%	99%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	98%	98%	100.0%	0.0%
#10	2.00	98%	98%	100.0%	0.0%
#16	1.18	97%	97%	100.0%	0.0%
#20	0.850	96%	96%	100.0%	0.0%
#30	0.600	96%	96%	100.0%	0.0%
#40	0.425	96%	96%	100.0%	0.0%
#50	0.300	93%	93%	100.0%	0.0%
#60	0.250	92%	92%	100.0%	0.0%
#80	0.180	90%	90%	100.0%	0.0%
#100	0.150	89%	89%	100.0%	0.0%
#140	0.106	79%	79%	100.0%	0.0%
#170	0.090	75%	75%	100.0%	0.0%
#200	0.075	71.7%	71.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo



Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT19-GB-0-6.9 ft Sample#: B21-1571 Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 ML, Silt with Sand Sample Color brown																																																																																																																																	
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																																																	
<table style="width: 100%;"> <tr> <td style="width: 30%;">Sp Gr :</td> <td style="width: 30%;">2.61</td> <td style="width: 40%;"></td> </tr> <tr> <td>Sample Weight:</td> <td>50.97</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td>2.35%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td>49.80</td> <td>grams</td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>24.5</td><td>48.4%</td><td>0.0488 mm</td></tr> <tr><td>2</td><td>19.5</td><td>38.6%</td><td>0.0356 mm</td></tr> <tr><td>5</td><td>17.5</td><td>34.6%</td><td>0.0228 mm</td></tr> <tr><td>15</td><td>12</td><td>23.7%</td><td>0.0135 mm</td></tr> <tr><td>30</td><td>9</td><td>17.8%</td><td>0.0097 mm</td></tr> <tr><td>60</td><td>5.5</td><td>10.9%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>2.5</td><td>4.9%</td><td>0.0036 mm</td></tr> <tr><td>1440</td><td>1</td><td>2.0%</td><td>0.0015 mm</td></tr> </tbody> </table> <table style="width: 100%;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 30%;">1.2%</td> <td style="width: 40%;">Liquid Limit: 0.0 %</td> </tr> <tr> <td>% Sand:</td> <td>27.1%</td> <td>Plastic Limit: 0.0 %</td> </tr> <tr> <td>% Silt:</td> <td>64.3%</td> <td>Plasticity Index: 0.0 %</td> </tr> <tr> <td>% Clay:</td> <td>7.4%</td> <td></td> </tr> </table>	Sp Gr :	2.61		Sample Weight:	50.97	grams	Hydroscopic Moist.:	2.35%		Adj. Sample Wgt :	49.80	grams	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	24.5	48.4%	0.0488 mm	2	19.5	38.6%	0.0356 mm	5	17.5	34.6%	0.0228 mm	15	12	23.7%	0.0135 mm	30	9	17.8%	0.0097 mm	60	5.5	10.9%	0.0070 mm	240	2.5	4.9%	0.0036 mm	1440	1	2.0%	0.0015 mm	% Gravel:	1.2%	Liquid Limit: 0.0 %	% Sand:	27.1%	Plastic Limit: 0.0 %	% Silt:	64.3%	Plasticity Index: 0.0 %	% Clay:	7.4%		<table style="width: 100%;"> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>99%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>99%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>98%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>96%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>96%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>89%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>71.7%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>70.8%</td><td>0.074 mm</td></tr> <tr><td></td><td>56.9%</td><td>0.050 mm</td></tr> <tr><td></td><td>31.3%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>7.4%</td><td>0.005 mm</td></tr> <tr><td></td><td>2.7%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.3%</td><td>0.001 mm</td></tr> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	99%	6.300 mm	#4	99%	4.750 mm	#10	98%	2.000 mm	#20	96%	0.850 mm	#40	96%	0.425 mm	#100	89%	0.150 mm	#200	71.7%	0.075 mm	Silts	70.8%	0.074 mm		56.9%	0.050 mm		31.3%	0.020 mm	Clays	7.4%	0.005 mm		2.7%	0.002 mm	Colloids	1.3%	0.001 mm
Sp Gr :	2.61																																																																																																																																	
Sample Weight:	50.97	grams																																																																																																																																
Hydroscopic Moist.:	2.35%																																																																																																																																	
Adj. Sample Wgt :	49.80	grams																																																																																																																																
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																															
1	24.5	48.4%	0.0488 mm																																																																																																																															
2	19.5	38.6%	0.0356 mm																																																																																																																															
5	17.5	34.6%	0.0228 mm																																																																																																																															
15	12	23.7%	0.0135 mm																																																																																																																															
30	9	17.8%	0.0097 mm																																																																																																																															
60	5.5	10.9%	0.0070 mm																																																																																																																															
240	2.5	4.9%	0.0036 mm																																																																																																																															
1440	1	2.0%	0.0015 mm																																																																																																																															
% Gravel:	1.2%	Liquid Limit: 0.0 %																																																																																																																																
% Sand:	27.1%	Plastic Limit: 0.0 %																																																																																																																																
% Silt:	64.3%	Plasticity Index: 0.0 %																																																																																																																																
% Clay:	7.4%																																																																																																																																	
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																																
3.0"	100%	75.000 mm																																																																																																																																
2.0"	100%	50.000 mm																																																																																																																																
1.5"	100%	37.500 mm																																																																																																																																
1.25"	100%	31.500 mm																																																																																																																																
1.0"	100%	25.000 mm																																																																																																																																
3/4"	100%	19.000 mm																																																																																																																																
5/8"	100%	16.000 mm																																																																																																																																
1/2"	100%	12.500 mm																																																																																																																																
3/8"	100%	9.500 mm																																																																																																																																
1/4"	99%	6.300 mm																																																																																																																																
#4	99%	4.750 mm																																																																																																																																
#10	98%	2.000 mm																																																																																																																																
#20	96%	0.850 mm																																																																																																																																
#40	96%	0.425 mm																																																																																																																																
#100	89%	0.150 mm																																																																																																																																
#200	71.7%	0.075 mm																																																																																																																																
Silts	70.8%	0.074 mm																																																																																																																																
	56.9%	0.050 mm																																																																																																																																
	31.3%	0.020 mm																																																																																																																																
Clays	7.4%	0.005 mm																																																																																																																																
	2.7%	0.002 mm																																																																																																																																
Colloids	1.3%	0.001 mm																																																																																																																																
USDA Soil Textural Classification																																																																																																																																		
<table style="width: 100%;"> <tr> <td style="width: 30%;"></td> <td style="width: 70%;">Particle Size</td> </tr> <tr> <td>% Sand:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </table> <p style="text-align: center;">USDA Soil Textural Classification Silt Loam</p>		Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																																										
	Particle Size																																																																																																																																	
% Sand:	2.0 - 0.05 mm																																																																																																																																	
% Silt:	0.05 - 0.002 mm																																																																																																																																	
% Clay:	< 0.002 mm																																																																																																																																	

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT19-GB-0-6.9 ft Sample #: B21-1571	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 ML, Silt with Sand Sample Color brown
---	--	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT19-GB-6.9-8.5 ft Sample#: B21-1572	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: brown	 Certificate #: 1366.01
--	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.068 mm D ₍₁₀₎ = 0.168 mm D ₍₁₅₎ = 0.215 mm D ₍₃₀₎ = 0.356 mm D ₍₅₀₎ = 0.749 mm D ₍₆₀₎ = 1.006 mm D ₍₉₀₎ = 1.777 mm Dust Ratio = 9/61	% Gravel = 0.3% % Sand = 94.2% % Silt & Clay = 5.5% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.75 Coeff. of Uniformity, C _u = 5.98 Fineness Modulus = 2.59 Plastic Limit = n/a Moisture %, as sampled = 27.9% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18		67%	100.0%	0.0%
#20	0.850		54%	100.0%	0.0%
#30	0.600		44%	100.0%	0.0%
#40	0.425	37%	37%	100.0%	0.0%
#50	0.300		24%	100.0%	0.0%
#60	0.250		19%	100.0%	0.0%
#80	0.180		11%	100.0%	0.0%
#100	0.150	8%	8%	100.0%	0.0%
#140	0.106		7%	100.0%	0.0%
#170	0.090		6%	100.0%	0.0%
#200	0.075	5.5%	5.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT19-GB-8.5-18.5 ft Sample#: B21-1574	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	ACCREDITED Certificate #: 1366.01
---	--	---	--------------------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs <p style="text-align: center;">Sample Meets Specs ? N/A</p>	D ₍₅₎ = 0.103 mm D ₍₁₀₎ = 0.155 mm D ₍₁₅₎ = 0.177 mm D ₍₃₀₎ = 0.242 mm D ₍₅₀₎ = 0.328 mm D ₍₆₀₎ = 0.372 mm D ₍₉₀₎ = 1.435 mm Dust Ratio = 2/53	% Gravel = 0.0% % Sand = 97.3% % Silt & Clay = 2.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.01 Coeff. of Uniformity, C _u = 2.40 Fineness Modulus = 1.87 Plastic Limit = n/a Moisture %, as sampled = 25.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	86%	86%	100.0%	0.0%
#20	0.850	80%	80%	100.0%	0.0%
#30	0.600	72%	75%	100.0%	0.0%
#40	0.425	72%	72%	100.0%	0.0%
#50	0.300	43%	43%	100.0%	0.0%
#60	0.250	32%	32%	100.0%	0.0%
#80	0.180	16%	16%	100.0%	0.0%
#100	0.150	9%	9%	100.0%	0.0%
#140	0.106	5%	5%	100.0%	0.0%
#170	0.090	4%	4%	100.0%	0.0%
#200	0.075	2.7%	2.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1574
 Sample Date: 7/13/2021
 Test Date: 9/21/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT19-GB-8.5-18.5 ft
 Visual Soil Description: brown sand with silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	27.5	
	Initial	Post-Consolidation
Dry Density (PCF):	106.2	107.3
Void Ratio:	0.586	0.570
Porosity (%):	37.0	36.3
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	26.1	
	Initial	Post-Consolidation
Dry Density (PCF):	108.0	109.7
Void Ratio:	0.560	0.536
Porosity (%):	35.9	34.9
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	24.7	
	Initial	Post-Consolidation
Dry Density (PCF):	109.2	111.5
Void Ratio:	0.543	0.511
Porosity (%):	35.2	33.8
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	38	34
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	400	800	1580
Residual Horizontal Stress, τ_h (PSF):	370	700	1340



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT19-GB-18.5-28.5 ft Sample#: B21-1576	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 1-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: brown	 Certificate #: 1366.01
--	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.058$ mm $D_{(10)} = 0.092$ mm $D_{(15)} = 0.117$ mm $D_{(30)} = 0.185$ mm $D_{(50)} = 0.271$ mm $D_{(60)} = 0.314$ mm $D_{(90)} = 0.882$ mm Dust Ratio = 5/67	% Gravel = 0.0% % Sand = 93.6% % Silt & Clay = 6.4% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 1.18$ Coeff. of Uniformity, $C_u = 3.40$ Fineness Modulus = 1.41 Plastic Limit = n/a Moisture %, as sampled = 27.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		93%	100.0%	0.0%
#20	0.850		90%	100.0%	0.0%
#30	0.600		87%	100.0%	0.0%
#40	0.425	86%	86%	100.0%	0.0%
#50	0.300		57%	100.0%	0.0%
#60	0.250		45%	100.0%	0.0%
#80	0.180		29%	100.0%	0.0%
#100	0.150	22%	22%	100.0%	0.0%
#140	0.106		13%	100.0%	0.0%
#170	0.090		10%	100.0%	0.0%
#200	0.075	6.4%	6.4%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 5, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1693-1706
Date sampled: July 14, 2021

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: September 13, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-1693	LDW21-GT37-GB-0-1.5 ft	233.7	583.3	440.8	142.5	207.1	68.8%
B21-1694	LDW21-GT37-GB-10-11.5 ft	302.0	688.9	534.6	154.3	232.6	66.3%
B21-1695	LDW21-GT37-GB-10-20 ft	234.3	678.9	534.1	144.8	299.8	48.3%
B21-1696	LDW21-GT37-GB-20-21.5 ft	341.8	864.9	644.8	220.1	303.0	72.6%
B21-1697	LDW21-GT37-GB-20-30 ft	316.0	945.0	766.3	178.7	450.3	39.7%
B21-1698	LDW21-GT37-GB-30-31.5 ft	346.9	1041.2	892.0	149.2	545.1	27.4%
B21-1699	LDW21-GT18-GB-0-1.5 ft	360.3	577.1	507.3	69.8	147.0	47.5%
B21-1700	LDW21-GT18-GB-0-6.5 ft	233.5	726.8	590.5	136.3	357.0	38.2%
B21-1701	LDW21-GT18-GB-6.5-8 ft	357.0	752.8	656.6	96.2	299.6	32.1%
B21-1702	LDW21-GT18-GB-6.5-16.5 ft	217.3	795.2	684.7	110.5	467.4	23.6%
B21-1703	LDW21-GT18-GB-16.5-18 ft	354.3	1016.0	893.3	122.7	539.0	22.8%
B21-1704	LDW21-GT18-GB-16.5-21.4 ft	10.2	159.2	118.5	40.7	108.3	37.6%
B21-1705	LDW21-GT18-GB-21.4-26.5 ft	690.5	1366.5	1179.1	187.4	488.6	38.4%
B21-1706	LDW21-GT18-GB-26.5-28 ft	359.5	929.9	801.2	128.7	441.7	29.1%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: *Meghan Blodgett Carrillo*
 Meghan Blodgett-Carrillo




Moisture Content - ASTM D854

Project: Q.C. - Lower Duwamish Waterway
 Project #: 21B233
 Date Received: July 29, 2021
 Date Tested: September 13, 2021

Client: Anchor QEA
 Sampled by: Client
 Tested by: A. Eifrig

Sample #	Location	Tare	Dry Soil + Tare	Mass of Dry Soil	Pycno ID	Mass of Pycno	Volume of Pycno	Density of Water @ Tx	Mass of Pycno filled w/ water & soils	Mass of Pycno filled w/ water	Temp. of Water, 0.1 *C	SpG of Soils	Temp. Correction Factor	Corrected SpG
B21-1695	LDW21-GT37-GB-10-20 ft	493.21	568.13	74.9	TSA-013	184.0	499.7	0.99756	728.81	682.44	22.9	2.6240964	0.99936	2.6224169
B21-1697	LDW21-GT37-GB-20-30 ft	497.94	575.45	77.5	TSA-011	190.3	499.5	0.99752	736.61	688.63	23.1	2.624687	0.99931	2.6228759
B21-1700	LDW21-GT18-GB-0-6.5 ft	600.24	700.15	99.9	TSA-020	195.0	499.5	0.99752	753.52	693.28	23.1	2.5184539	0.99931	2.5167161
B21-1702	LDW21-GT18-GB-6.5-16.5 ft	510.32	612.20	101.9	TSA-010	180.3	499.5	0.99754	742.28	678.62	23.0	2.6655395	0.99933	2.6637535
B21-1705	LDW21-GT18-GB-21.4-26.5 ft	501.27	576.59	75.3	TSA-021	183.4	499.4	0.99745	727.11	681.56	23.4	2.5303609	0.99924	2.5284379

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT37-GB-10-20 ft Sample#: B21-1695	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.003 mm	% Gravel = 0.5%	Coeff. of Curvature, C _c = 3.61
	D ₍₁₀₎ = 0.007 mm	% Sand = 57.8%	Coeff. of Uniformity, C _u = 17.03
	D ₍₁₅₎ = 0.016 mm	% Silt & Clay = 41.7%	Fineness Modulus = 0.59
	D ₍₃₀₎ = 0.057 mm	Liquid Limit = 0.0%	Plastic Limit = 0.0%
	D ₍₅₀₎ = 0.097 mm	Plasticity Index = 0.0%	Moisture %, as sampled = 48.3%
	D ₍₆₀₎ = 0.124 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
	D ₍₉₀₎ = 0.386 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
	Dust Ratio = 21/47	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	99%	99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	96%	96%	100.0%	0.0%
#20	0.850	95%	95%	100.0%	0.0%
#30	0.600	94%	94%	100.0%	0.0%
#40	0.425	93%	93%	100.0%	0.0%
#50	0.300	83%	83%	100.0%	0.0%
#60	0.250	78%	78%	100.0%	0.0%
#80	0.180	72%	72%	100.0%	0.0%
#100	0.150	69%	69%	100.0%	0.0%
#140	0.106	53%	53%	100.0%	0.0%
#170	0.090	47%	47%	100.0%	0.0%
#200	0.075	41.7%	41.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 

 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT37-GB-10-20 ft Sample#: B21-1695	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																																																																
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																																																
Sp Gr : 2.62 Sample Weight: 74.76 grams Hydroscopic Moist.: 2.84% Adj. Sample Wgt : 72.70 grams		Sieve Analysis Grain Size Distribution																																																																																																																
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>18.5</td><td>25.6%</td><td>0.0505 mm</td></tr> <tr><td>2</td><td>15.5</td><td>21.4%</td><td>0.0364 mm</td></tr> <tr><td>5</td><td>13.5</td><td>18.7%</td><td>0.0234 mm</td></tr> <tr><td>15</td><td>10</td><td>13.8%</td><td>0.0137 mm</td></tr> <tr><td>30</td><td>9</td><td>12.4%</td><td>0.0097 mm</td></tr> <tr><td>60</td><td>7</td><td>9.7%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>4</td><td>5.5%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.4%</td><td>0.0015 mm</td></tr> </tbody> </table> <table style="width: 100%;"> <tr> <td>% Gravel: 0.5%</td> <td>Liquid Limit: 0.0 %</td> </tr> <tr> <td>% Sand: 57.8%</td> <td>Plastic Limit: 0.0 %</td> </tr> <tr> <td>% Silt: 34.4%</td> <td>Plasticity Index: 0.0 %</td> </tr> <tr> <td>% Clay: 7.3%</td> <td></td> </tr> </table>	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	18.5	25.6%	0.0505 mm	2	15.5	21.4%	0.0364 mm	5	13.5	18.7%	0.0234 mm	15	10	13.8%	0.0137 mm	30	9	12.4%	0.0097 mm	60	7	9.7%	0.0070 mm	240	4	5.5%	0.0035 mm	1440	1	1.4%	0.0015 mm	% Gravel: 0.5%	Liquid Limit: 0.0 %	% Sand: 57.8%	Plastic Limit: 0.0 %	% Silt: 34.4%	Plasticity Index: 0.0 %	% Clay: 7.3%		<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>99%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>99%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>95%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>93%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>69%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>41.7%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>41.1%</td><td>0.074 mm</td></tr> <tr><td></td><td>24.3%</td><td>0.050 mm</td></tr> <tr><td></td><td>17.0%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>7.3%</td><td>0.005 mm</td></tr> <tr><td></td><td>2.5%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	99%	4.750 mm	#10	99%	2.000 mm	#20	95%	0.850 mm	#40	93%	0.425 mm	#100	69%	0.150 mm	#200	41.7%	0.075 mm	Silts	41.1%	0.074 mm		24.3%	0.050 mm		17.0%	0.020 mm	Clays	7.3%	0.005 mm		2.5%	0.002 mm	Colloids	0.9%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																															
1	18.5	25.6%	0.0505 mm																																																																																																															
2	15.5	21.4%	0.0364 mm																																																																																																															
5	13.5	18.7%	0.0234 mm																																																																																																															
15	10	13.8%	0.0137 mm																																																																																																															
30	9	12.4%	0.0097 mm																																																																																																															
60	7	9.7%	0.0070 mm																																																																																																															
240	4	5.5%	0.0035 mm																																																																																																															
1440	1	1.4%	0.0015 mm																																																																																																															
% Gravel: 0.5%	Liquid Limit: 0.0 %																																																																																																																	
% Sand: 57.8%	Plastic Limit: 0.0 %																																																																																																																	
% Silt: 34.4%	Plasticity Index: 0.0 %																																																																																																																	
% Clay: 7.3%																																																																																																																		
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																
3.0"	100%	75.000 mm																																																																																																																
2.0"	100%	50.000 mm																																																																																																																
1.5"	100%	37.500 mm																																																																																																																
1.25"	100%	31.500 mm																																																																																																																
1.0"	100%	25.000 mm																																																																																																																
3/4"	100%	19.000 mm																																																																																																																
5/8"	100%	16.000 mm																																																																																																																
1/2"	100%	12.500 mm																																																																																																																
3/8"	100%	9.500 mm																																																																																																																
1/4"	100%	6.300 mm																																																																																																																
#4	99%	4.750 mm																																																																																																																
#10	99%	2.000 mm																																																																																																																
#20	95%	0.850 mm																																																																																																																
#40	93%	0.425 mm																																																																																																																
#100	69%	0.150 mm																																																																																																																
#200	41.7%	0.075 mm																																																																																																																
Silts	41.1%	0.074 mm																																																																																																																
	24.3%	0.050 mm																																																																																																																
	17.0%	0.020 mm																																																																																																																
Clays	7.3%	0.005 mm																																																																																																																
	2.5%	0.002 mm																																																																																																																
Colloids	0.9%	0.001 mm																																																																																																																
USDA Soil Textural Classification																																																																																																																		
<table style="width: 100%;"> <tr> <td>% Sand:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </table> USDA Soil Textural Classification Loamy Sand	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																												
% Sand:	2.0 - 0.05 mm																																																																																																																	
% Silt:	0.05 - 0.002 mm																																																																																																																	
% Clay:	< 0.002 mm																																																																																																																	

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1695
 Sample Date: 7/14/2021
 Test Date: 9/16/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT37-GB-10-20 ft
 Visual Soil Description: brown silty sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	35.3	
	Initial	Post-Consolidation
Dry Density (PCF):	100.7	102.8
Void Ratio:	0.673	0.639
Porosity (%):	40.2	39.0
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	36.0	
	Initial	Post-Consolidation
Dry Density (PCF):	100.9	110.5
Void Ratio:	0.670	0.525
Porosity (%):	40.1	34.4
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	35.4	
	Initial	Post-Consolidation
Dry Density (PCF):	101.4	114.5
Void Ratio:	0.662	0.471
Porosity (%):	39.8	32.0
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	36	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	370	740	1460
Residual Horizontal Stress, τ_h (PSF):	310	620	1230



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net



Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT37-GB-20-30 ft Sample#: B21-1697	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.013 mm	% Gravel = 0.2%	Coeff. of Curvature, C _c = 1.00
D ₍₁₀₎ = 0.025 mm	% Sand = 70.3%	Coeff. of Uniformity, C _u = 9.20
D ₍₁₅₎ = 0.038 mm	% Silt & Clay = 29.5%	Fineness Modulus = 1.03
D ₍₃₀₎ = 0.077 mm	Liquid Limit = 0.0%	Plastic Limit = 0.0%
D ₍₅₀₎ = 0.165 mm	Plasticity Index = 0.0%	Moisture %, as sampled = 39.7%
D ₍₆₀₎ = 0.234 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.767 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 1/3	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		98%	100.0%	0.0%
#10	2.00	98%	98%	100.0%	0.0%
#16	1.18		93%	100.0%	0.0%
#20	0.850		91%	100.0%	0.0%
#30	0.600		89%	100.0%	0.0%
#40	0.425	88%	88%	100.0%	0.0%
#50	0.300		70%	100.0%	0.0%
#60	0.250		62%	100.0%	0.0%
#80	0.180		52%	100.0%	0.0%
#100	0.150	48%	48%	100.0%	0.0%
#140	0.106		37%	100.0%	0.0%
#170	0.090		33%	100.0%	0.0%
#200	0.075	29.5%	29.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by:
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT37-GB-20-30 ft Sample #: B21-1697	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color brown
---	---	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by: _____
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT18-GB-0-6.5 ft Sample #: B21-1700	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Visual Identification Sand with Silt Sample Color brown
---	---	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by: _____
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT18-GB-6.5-16.5 ft Sample#: B21-1702	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
---	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.136 mm D ₍₁₀₎ = 0.168 mm D ₍₁₅₎ = 0.190 mm D ₍₃₀₎ = 0.255 mm D ₍₅₀₎ = 0.342 mm D ₍₆₀₎ = 0.385 mm D ₍₉₀₎ = 1.497 mm Dust Ratio = 1/54	% Gravel = 0.0% % Sand = 98.7% % Silt & Clay = 1.3% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.00 Coeff. of Uniformity, C _u = 2.29 Fineness Modulus = 1.97 Plastic Limit = n/a Moisture %, as sampled = 23.6% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		84%	100.0%	0.0%
#20	0.850		77%	100.0%	0.0%
#30	0.600		73%	100.0%	0.0%
#40	0.425	69%	69%	100.0%	0.0%
#50	0.300		40%	100.0%	0.0%
#60	0.250		29%	100.0%	0.0%
#80	0.180		13%	100.0%	0.0%
#100	0.150	6%	6%	100.0%	0.0%
#140	0.106		3%	100.0%	0.0%
#170	0.090		2%	100.0%	0.0%
#200	0.075	1.3%	1.3%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT18-GB-16.5-21.4 ft Sample#: B21-1704	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.005$ mm $D_{(10)} = 0.014$ mm $D_{(15)} = 0.038$ mm $D_{(30)} = 0.081$ mm $D_{(50)} = 0.122$ mm $D_{(60)} = 0.142$ mm $D_{(90)} = 0.351$ mm Dust Ratio = 3/11	% Gravel = 0.0% % Sand = 72.8% % Silt & Clay = 27.2% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 3.31$ Coeff. of Uniformity, $C_u = 10.24$ Fineness Modulus = 0.53 Plastic Limit = 0.0% Moisture %, as sampled = 37.6% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	100%	100%	100.0%	0.0%
#40	0.425	100%	100%	100.0%	0.0%
#50	0.300	83%	83%	100.0%	0.0%
#60	0.250	77%	77%	100.0%	0.0%
#80	0.180	68%	68%	100.0%	0.0%
#100	0.150	64%	64%	100.0%	0.0%
#140	0.106	42%	42%	100.0%	0.0%
#170	0.090	35%	35%	100.0%	0.0%
#200	0.075	27.2%	27.2%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

<p>Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client: Anchor QEA Date Tested: 1-Sep-21 Source: LDW21-GT18-GB-16.5-21.4 ft Tested By: C. Kriss Sample#: B21-1704</p>	<p>Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown</p>																																																																																																									
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																									
<p>Sp Gr : 2.53 Sample Weight: 99.41 grams Hydroscopic Moist.: 2.98% Adj. Sample Wgt : 96.53 grams</p> <div style="text-align: center;">  </div> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>17</td><td>18.1%</td><td>0.0526 mm</td></tr> <tr><td>2</td><td>14</td><td>14.9%</td><td>0.0379 mm</td></tr> <tr><td>5</td><td>12.5</td><td>13.3%</td><td>0.0242 mm</td></tr> <tr><td>15</td><td>9.5</td><td>10.1%</td><td>0.0142 mm</td></tr> <tr><td>30</td><td>8</td><td>8.5%</td><td>0.0101 mm</td></tr> <tr><td>60</td><td>6.5</td><td>6.9%</td><td>0.0072 mm</td></tr> <tr><td>240</td><td>4</td><td>4.3%</td><td>0.0036 mm</td></tr> <tr><td>1440</td><td>2</td><td>2.1%</td><td>0.0015 mm</td></tr> </tbody> </table> <p style="margin-top: 10px;"> % Gravel: 0.0% Liquid Limit: 0.0 % % Sand: 72.8% Plastic Limit: 0.0 % % Silt: 21.9% Plasticity Index: 0.0 % % Clay: 5.3% </p>	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	17	18.1%	0.0526 mm	2	14	14.9%	0.0379 mm	5	12.5	13.3%	0.0242 mm	15	9.5	10.1%	0.0142 mm	30	8	8.5%	0.0101 mm	60	6.5	6.9%	0.0072 mm	240	4	4.3%	0.0036 mm	1440	2	2.1%	0.0015 mm	<p style="text-align: center;">Sieve Analysis Grain Size Distribution</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>100%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>100%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>64%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>27.2%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>26.8%</td><td>0.074 mm</td></tr> <tr><td></td><td>16.4%</td><td>0.050 mm</td></tr> <tr><td></td><td>12.0%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>5.3%</td><td>0.005 mm</td></tr> <tr><td></td><td>2.6%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.4%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	100%	0.850 mm	#40	100%	0.425 mm	#100	64%	0.150 mm	#200	27.2%	0.075 mm	Silts	26.8%	0.074 mm		16.4%	0.050 mm		12.0%	0.020 mm	Clays	5.3%	0.005 mm		2.6%	0.002 mm	Colloids	1.4%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																							
1	17	18.1%	0.0526 mm																																																																																																							
2	14	14.9%	0.0379 mm																																																																																																							
5	12.5	13.3%	0.0242 mm																																																																																																							
15	9.5	10.1%	0.0142 mm																																																																																																							
30	8	8.5%	0.0101 mm																																																																																																							
60	6.5	6.9%	0.0072 mm																																																																																																							
240	4	4.3%	0.0036 mm																																																																																																							
1440	2	2.1%	0.0015 mm																																																																																																							
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																								
3.0"	100%	75.000 mm																																																																																																								
2.0"	100%	50.000 mm																																																																																																								
1.5"	100%	37.500 mm																																																																																																								
1.25"	100%	31.500 mm																																																																																																								
1.0"	100%	25.000 mm																																																																																																								
3/4"	100%	19.000 mm																																																																																																								
5/8"	100%	16.000 mm																																																																																																								
1/2"	100%	12.500 mm																																																																																																								
3/8"	100%	9.500 mm																																																																																																								
1/4"	100%	6.300 mm																																																																																																								
#4	100%	4.750 mm																																																																																																								
#10	100%	2.000 mm																																																																																																								
#20	100%	0.850 mm																																																																																																								
#40	100%	0.425 mm																																																																																																								
#100	64%	0.150 mm																																																																																																								
#200	27.2%	0.075 mm																																																																																																								
Silts	26.8%	0.074 mm																																																																																																								
	16.4%	0.050 mm																																																																																																								
	12.0%	0.020 mm																																																																																																								
Clays	5.3%	0.005 mm																																																																																																								
	2.6%	0.002 mm																																																																																																								
Colloids	1.4%	0.001 mm																																																																																																								
USDA Soil Textural Classification																																																																																																										
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Sand:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </table> <p style="text-align: center; margin-top: 10px;"> USDA Soil Textural Classification Loamy Sand </p>	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																				
% Sand:	2.0 - 0.05 mm																																																																																																									
% Silt:	0.05 - 0.002 mm																																																																																																									
% Clay:	< 0.002 mm																																																																																																									

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____
Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1704
 Sample Date: 7/14/2021
 Test Date: 9/17/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT18-GB-16.5-21.4 ft
 Visual Soil Description: brown silty sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	29.4	
	Initial	Post-Consolidation
Dry Density (PCF):	107.0	107.9
Void Ratio:	0.575	0.562
Porosity (%):	36.5	36.0
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	28.3	
	Initial	Post-Consolidation
Dry Density (PCF):	107.4	109.9
Void Ratio:	0.569	0.533
Porosity (%):	36.3	34.8
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	29.0	
	Initial	Post-Consolidation
Dry Density (PCF):	106.9	110.5
Void Ratio:	0.576	0.525
Porosity (%):	36.5	34.4
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	39	30
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	350	810	1600
Residual Horizontal Stress, τ_h (PSF):	290	590	1170



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT18-GB-21.4-26.5 ft Sample#: B21-1705	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 13-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.013 mm D ₍₁₀₎ = 0.025 mm D ₍₁₅₎ = 0.038 mm D ₍₃₀₎ = 0.076 mm D ₍₅₀₎ = 0.128 mm D ₍₆₀₎ = 0.162 mm D ₍₉₀₎ = 0.393 mm Dust Ratio = 23/73	% Gravel = 0.7% % Sand = 69.6% % Silt & Clay = 29.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.41 Coeff. of Uniformity, C _u = 6.40 Fineness Modulus = 0.74 Plastic Limit = n/a Moisture %, as sampled = 38.4% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	99%	99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	96%	96%	100.0%	0.0%
#20	0.850	95%	95%	100.0%	0.0%
#30	0.600	95%	95%	100.0%	0.0%
#40	0.425	94%	94%	100.0%	0.0%
#50	0.300	78%	78%	100.0%	0.0%
#60	0.250	71%	71%	100.0%	0.0%
#80	0.180	62%	62%	100.0%	0.0%
#100	0.150	58%	58%	100.0%	0.0%
#140	0.106	42%	42%	100.0%	0.0%
#170	0.090	35%	35%	100.0%	0.0%
#200	0.075	29.7%	29.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 6, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1787-1803
Date sampled: 7-12-21 & 7-14-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: September 20, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-1787	LDW21-GT15-GB-0-7.5 ft	233.4	1016.2	787.2	229.0	553.8	41.4%
B21-1788	LDW21-GT15-GB-7.5-9 ft	306.7	450.8	422.5	28.3	115.8	24.4%
B21-1789	LDW21-GT15-GB-7.5-15 ft	236.2	1288.2	1043.0	245.2	806.8	30.4%
B21-1790	LDW21-GT15-GB-15-17.5 ft	303.3	997.2	810.9	186.3	507.6	36.7%
B21-1791	LDW21-GT15-GB-17.5-19 ft	311.1	465.1	434.0	31.1	122.9	25.3%
B21-1792	LDW21-GT15-GB-17.5-25.4 ft	270.2	882.6	747.4	135.2	477.2	28.3%
B21-1793	LDW21-GT15-GB-25.4-27.5 ft	260.6	1270.0	1036.1	233.9	775.5	30.2%
B21-1794	LDW21-GT15-GB-27.5-29 ft	222.9	616.1	520.8	95.3	297.9	32.0%
B21-1795	LDW21-GT29-GB-0-1.5 ft	225.1	949.8	644.5	305.3	419.4	72.8%
B21-1796	LDW21-GT29-GB-0-10.6 ft	221.7	746.6	548.6	198.0	326.9	60.6%
B21-1797	LDW21-GT29-GB-11-12.5 ft	221.4	1082.5	801.0	281.5	579.6	48.6%
B21-1798	LDW21-GT29-GB-11-21 ft	224.4	738.0	646.6	91.4	422.2	21.6%
B21-1799	LDW21-GT29-GB-21-22.5 ft	222.3	408.6	349.3	59.3	127.0	46.7%
B21-1800	LDW21-GT29-GB-21-26 ft	233.8	1031.7	903.6	128.1	669.8	19.1%
B21-1801	LDW21-GT29-GB-26-28.9 ft	229.1	776.5	629.0	147.5	399.9	36.9%
B21-1802	LDW21-GT29-GB-28.9-31 ft	188.4	1285.9	988.6	297.3	800.2	37.2%
B21-1803	LDW21-GT29-GB-31-32.5 ft	225.3	925.7	756.5	169.2	531.2	31.9%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 
Meghan Blodgett-Carrillo



Moisture Content - ASTM D854

Project: Q.C. - Lower Duwamish Waterway

Project #: 21B233

Date Received: July 29, 2021

Date Tested: September 20, 2021


Client: Anchor QEA

Sampled by: Client

Tested by: A. Eifrig

Sample #	Location	Tare	Dry Soil + Tare	Mass of Dry Soil	Pycno ID	Mass of Pycno	Volume of Pycno	Density of Water @ Tx	Mass of Pycno filled w/ water & soils	Mass of Pycno filled w/ water	Temp. of Water, 0.1 *C	SpG of Soils	Temp. Correction Factor	Corrected SpG
B21-1787	LDW21-GT15-GB-0-7.5 ft	584.26	658.50	74.2	TSA-014	192.3	499.5	0.99749	735.04	690.54	23.2	2.4966051	0.99929	2.4948325
B21-1792	LDW21-GT15-GB-17.5-25.4 ft	493.62	594.11	100.5	TSA-016	197.2	499.5	0.99754	757.82	695.45	23.0	2.6360571	0.99933	2.634291
B21-1793	LDW21-GT15-GB-25.4-27.5 ft	500.82	575.98	75.2	TSA-022	198.0	499.5	0.99749	740.87	696.19	23.2	2.4661721	0.99929	2.4644211
B21-1796	LDW21-GT29-GB-0-10.6 ft	600.79	675.86	75.1	TSA-012	180.4	499.5	0.99752	722.04	678.65	23.1	2.3695318	0.99931	2.3678968
B21-1798	LDW21-GT29-GB-11-21 ft	584.33	685.35	101.0	TSA-017	187.9	499.4	0.99749	749.71	686.04	23.2	2.7049457	0.99929	2.7030252

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 
Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT15-GB-0-7.5 ft Sample #: B21-1787	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Visual Identification Silt with Sand and Clay Sample Color brown
---	---	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Liquid limit cannot be established					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Plastic limit cannot be determined					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit cup without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by: _____
 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT15-GB-7.5-15 ft Sample#: B21-1789	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
---	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.076 mm D ₍₁₀₎ = 0.113 mm D ₍₁₅₎ = 0.150 mm D ₍₃₀₎ = 0.220 mm D ₍₅₀₎ = 0.313 mm D ₍₆₀₎ = 0.359 mm D ₍₉₀₎ = 1.522 mm Dust Ratio = 2/31	% Gravel = 1.6% % Sand = 93.6% % Silt & Clay = 4.8% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.19 Coeff. of Uniformity, C _u = 3.17 Fineness Modulus = 1.81 Plastic Limit = n/a Moisture %, as sampled = 30.4% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		99%	100.0%	0.0%
1/2"	12.50	99%	99%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30		99%	100.0%	0.0%
#4	4.75	98%	98%	100.0%	0.0%
#8	2.36		97%	100.0%	0.0%
#10	2.00	97%	97%	100.0%	0.0%
#16	1.18		85%	100.0%	0.0%
#20	0.850		80%	100.0%	0.0%
#30	0.600		77%	100.0%	0.0%
#40	0.425	74%	74%	100.0%	0.0%
#50	0.300		47%	100.0%	0.0%
#60	0.250		37%	100.0%	0.0%
#80	0.180		21%	100.0%	0.0%
#100	0.150	15%	15%	100.0%	0.0%
#140	0.106		9%	100.0%	0.0%
#170	0.090		7%	100.0%	0.0%
#200	0.075	4.8%	4.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1789
 Sample Date: 7/12/2021
 Test Date: 9/28/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT15-GB-7.5-15 ft
 Visual Soil Description: brown sand with silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	26.1	
	Initial	Post-Consolidation
Dry Density (PCF):	109.2	110.2
Void Ratio:	0.543	0.528
Porosity (%):	35.2	34.6
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	25.9	
	Initial	Post-Consolidation
Dry Density (PCF):	108.7	110.2
Void Ratio:	0.550	0.529
Porosity (%):	35.5	34.6
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	25.9	
	Initial	Post-Consolidation
Dry Density (PCF):	110.0	114.4
Void Ratio:	0.532	0.473
Porosity (%):	34.7	32.1
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	32	28
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	270	620	1290
Residual Horizontal Stress, τ_h (PSF):	180	500	1110



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT15-GB-15-17.5 ft Sample#: B21-1790	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Visual Identification Sandy Silt with Clay Sample Color: brown
--	---	---



ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.004 mm	% Gravel = 1.3%	Coeff. of Curvature, C _c = 2.92
D ₍₁₀₎ = 0.006 mm	% Sand = 41.6%	Coeff. of Uniformity, C _u = 12.63
D ₍₁₅₎ = 0.012 mm	% Silt & Clay = 57.1%	Fineness Modulus = 0.29
D ₍₃₀₎ = 0.039 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.067 mm	Plasticity Index = n/a	Moisture %, as sampled = 36.7%
D ₍₆₀₎ = 0.082 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.193 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 47/80	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	99%	99%	100.0%	0.0%
5/8"	16.00		99%	100.0%	0.0%
1/2"	12.50	99%	99%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30		99%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36		98%	100.0%	0.0%
#10	2.00	98%	98%	100.0%	0.0%
#16	1.18		97%	100.0%	0.0%
#20	0.850		97%	100.0%	0.0%
#30	0.600		97%	100.0%	0.0%
#40	0.425	97%	97%	100.0%	0.0%
#50	0.300		93%	100.0%	0.0%
#60	0.250		92%	100.0%	0.0%
#80	0.180		90%	100.0%	0.0%
#100	0.150	89%	89%	100.0%	0.0%
#140	0.106		70%	100.0%	0.0%
#170	0.090		63%	100.0%	0.0%
#200	0.075	57.1%	57.1%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by:
 Meghan Blodgett-Carrillo



Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client: Anchor QEA Date Tested: 20-Sep-21 Source: LDW21-GT15-GB-15-17.5 ft Tested By: C. Kriss Sample#: B21-1790		Visual Identification Sandy Silt with Clay Sample Color brown																																																																																	
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																	
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Assumed Sp Gr :</td> <td style="width: 20%;">2.65</td> <td style="width: 50%;"></td> </tr> <tr> <td>Sample Weight:</td> <td>75.02</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td>1.96%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td>73.58</td> <td>grams</td> </tr> </table>		Assumed Sp Gr :	2.65		Sample Weight:	75.02	grams	Hydroscopic Moist.:	1.96%		Adj. Sample Wgt :	73.58	grams																																																																						
Assumed Sp Gr :	2.65																																																																																		
Sample Weight:	75.02	grams																																																																																	
Hydroscopic Moist.:	1.96%																																																																																		
Adj. Sample Wgt :	73.58	grams																																																																																	
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>25.5</td><td>33.8%</td><td>0.0477 mm</td></tr> <tr><td>2</td><td>21</td><td>27.8%</td><td>0.0347 mm</td></tr> <tr><td>5</td><td>17</td><td>22.5%</td><td>0.0224 mm</td></tr> <tr><td>15</td><td>12</td><td>15.9%</td><td>0.0133 mm</td></tr> <tr><td>30</td><td>10</td><td>13.3%</td><td>0.0096 mm</td></tr> <tr><td>60</td><td>8</td><td>10.6%</td><td>0.0068 mm</td></tr> <tr><td>240</td><td>3.5</td><td>4.6%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>2</td><td>2.7%</td><td>0.0014 mm</td></tr> </tbody> </table>		Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	25.5	33.8%	0.0477 mm	2	21	27.8%	0.0347 mm	5	17	22.5%	0.0224 mm	15	12	15.9%	0.0133 mm	30	10	13.3%	0.0096 mm	60	8	10.6%	0.0068 mm	240	3.5	4.6%	0.0035 mm	1440	2	2.7%	0.0014 mm																																														
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																
1	25.5	33.8%	0.0477 mm																																																																																
2	21	27.8%	0.0347 mm																																																																																
5	17	22.5%	0.0224 mm																																																																																
15	12	15.9%	0.0133 mm																																																																																
30	10	13.3%	0.0096 mm																																																																																
60	8	10.6%	0.0068 mm																																																																																
240	3.5	4.6%	0.0035 mm																																																																																
1440	2	2.7%	0.0014 mm																																																																																
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 20%;">1.3%</td> <td style="width: 50%;">Liquid Limit: n/a</td> </tr> <tr> <td>% Sand:</td> <td>41.6%</td> <td>Plastic Limit: n/a</td> </tr> <tr> <td>% Silt:</td> <td>49.7%</td> <td>Plasticity Index: n/a</td> </tr> <tr> <td>% Clay:</td> <td>7.3%</td> <td></td> </tr> </table>		% Gravel:	1.3%	Liquid Limit: n/a	% Sand:	41.6%	Plastic Limit: n/a	% Silt:	49.7%	Plasticity Index: n/a	% Clay:	7.3%		<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>99%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>99%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>99%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>99%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>99%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>99%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>98%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>97%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>97%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>89%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>57.1%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>56.2%</td><td>0.074 mm</td></tr> <tr><td></td><td>42.6%</td><td>0.050 mm</td></tr> <tr><td></td><td>20.8%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>7.3%</td><td>0.005 mm</td></tr> <tr><td></td><td>3.2%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.8%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	99%	19.000 mm	5/8"	99%	16.000 mm	1/2"	99%	12.500 mm	3/8"	99%	9.500 mm	1/4"	99%	6.300 mm	#4	99%	4.750 mm	#10	98%	2.000 mm	#20	97%	0.850 mm	#40	97%	0.425 mm	#100	89%	0.150 mm	#200	57.1%	0.075 mm	Silts	56.2%	0.074 mm		42.6%	0.050 mm		20.8%	0.020 mm	Clays	7.3%	0.005 mm		3.2%	0.002 mm	Colloids	1.8%	0.001 mm
% Gravel:	1.3%	Liquid Limit: n/a																																																																																	
% Sand:	41.6%	Plastic Limit: n/a																																																																																	
% Silt:	49.7%	Plasticity Index: n/a																																																																																	
% Clay:	7.3%																																																																																		
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																	
3.0"	100%	75.000 mm																																																																																	
2.0"	100%	50.000 mm																																																																																	
1.5"	100%	37.500 mm																																																																																	
1.25"	100%	31.500 mm																																																																																	
1.0"	100%	25.000 mm																																																																																	
3/4"	99%	19.000 mm																																																																																	
5/8"	99%	16.000 mm																																																																																	
1/2"	99%	12.500 mm																																																																																	
3/8"	99%	9.500 mm																																																																																	
1/4"	99%	6.300 mm																																																																																	
#4	99%	4.750 mm																																																																																	
#10	98%	2.000 mm																																																																																	
#20	97%	0.850 mm																																																																																	
#40	97%	0.425 mm																																																																																	
#100	89%	0.150 mm																																																																																	
#200	57.1%	0.075 mm																																																																																	
Silts	56.2%	0.074 mm																																																																																	
	42.6%	0.050 mm																																																																																	
	20.8%	0.020 mm																																																																																	
Clays	7.3%	0.005 mm																																																																																	
	3.2%	0.002 mm																																																																																	
Colloids	1.8%	0.001 mm																																																																																	
USDA Soil Textural Classification																																																																																			
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Sand:</td> <td style="width: 70%;">Particle Size</td> </tr> <tr> <td>% Silt:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Clay:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td></td> <td>< 0.002 mm</td> </tr> </table>		% Sand:	Particle Size	% Silt:	2.0 - 0.05 mm	% Clay:	0.05 - 0.002 mm		< 0.002 mm																																																																										
% Sand:	Particle Size																																																																																		
% Silt:	2.0 - 0.05 mm																																																																																		
% Clay:	0.05 - 0.002 mm																																																																																		
	< 0.002 mm																																																																																		
USDA Soil Textural Classification Sandy Loam																																																																																			

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____

Meghan Blodgett-Carrillo


Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT15-GB-17.5-19 ft Sample#: B21-1791	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	--	----------------------------

Specifications No Specs <p style="text-align: center;">Sample Meets Specs ? N/A</p>	ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281 D ₍₅₎ = 0.007 mm % Gravel = 2.2% D ₍₁₀₎ = 0.056 mm % Sand = 82.3% D ₍₁₅₎ = 0.073 mm % Silt & Clay = 15.5% D ₍₃₀₎ = 0.142 mm Liquid Limit = n/a D ₍₅₀₎ = 0.287 mm Plasticity Index = n/a D ₍₆₀₎ = 0.362 mm Sand Equivalent = n/a D ₍₉₀₎ = 1.662 mm Fracture %, 1 Face = n/a Dust Ratio = 22/97 Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.98 Coeff. of Uniformity, C _u = 6.42 Fineness Modulus = 1.71 Plastic Limit = n/a Moisture %, as sampled = 25.3% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =
---	---	--

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	98%	98%	100.0%	0.0%
1/4"	6.30		98%	100.0%	0.0%
#4	4.75	98%	98%	100.0%	0.0%
#8	2.36		96%	100.0%	0.0%
#10	2.00	96%	96%	100.0%	0.0%
#16	1.18		82%	100.0%	0.0%
#20	0.850		76%	100.0%	0.0%
#30	0.600		71%	100.0%	0.0%
#40	0.425	68%	68%	100.0%	0.0%
#50	0.300		52%	100.0%	0.0%
#60	0.250		45%	100.0%	0.0%
#80	0.180		36%	100.0%	0.0%
#100	0.150	32%	32%	100.0%	0.0%
#140	0.106		22%	100.0%	0.0%
#170	0.090		19%	100.0%	0.0%
#200	0.075	15.5%	15.5%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo



Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client : Anchor QEA Source: LDW21-GT15-GB-17.5-19 ft Sample#: B21-1791	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Assumed Sp Gr : 2.65 Sample Weight: 74.97 grams Hydrosopic Moist.: 1.06% Adj. Sample Wgt : 74.18 grams		Sieve Analysis Grain Size Distribution																																																																					
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>98%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>98%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>98%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>96%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>76%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>68%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>32%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>15.5%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>15.2%</td><td>0.074 mm</td></tr> <tr><td></td><td>10.2%</td><td>0.050 mm</td></tr> <tr><td></td><td>7.3%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>3.0%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.3%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	98%	9.500 mm	1/4"	98%	6.300 mm	#4	98%	4.750 mm	#10	96%	2.000 mm	#20	76%	0.850 mm	#40	68%	0.425 mm	#100	32%	0.150 mm	#200	15.5%	0.075 mm	Silts	15.2%	0.074 mm		10.2%	0.050 mm		7.3%	0.020 mm	Clays	3.0%	0.005 mm		1.3%	0.002 mm	Colloids	0.9%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	98%	9.500 mm																																																																					
1/4"	98%	6.300 mm																																																																					
#4	98%	4.750 mm																																																																					
#10	96%	2.000 mm																																																																					
#20	76%	0.850 mm																																																																					
#40	68%	0.425 mm																																																																					
#100	32%	0.150 mm																																																																					
#200	15.5%	0.075 mm																																																																					
Silts	15.2%	0.074 mm																																																																					
	10.2%	0.050 mm																																																																					
	7.3%	0.020 mm																																																																					
Clays	3.0%	0.005 mm																																																																					
	1.3%	0.002 mm																																																																					
Colloids	0.9%	0.001 mm																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>7</td><td>9.1%</td><td>0.0532 mm</td></tr> <tr><td>2</td><td>7</td><td>9.1%</td><td>0.0376 mm</td></tr> <tr><td>5</td><td>6</td><td>7.8%</td><td>0.0239 mm</td></tr> <tr><td>15</td><td>5</td><td>6.5%</td><td>0.0139 mm</td></tr> <tr><td>30</td><td>4.5</td><td>5.8%</td><td>0.0098 mm</td></tr> <tr><td>60</td><td>4</td><td>5.2%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>1</td><td>1.3%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.3%</td><td>0.0014 mm</td></tr> </tbody> </table>		Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	7	9.1%	0.0532 mm	2	7	9.1%	0.0376 mm	5	6	7.8%	0.0239 mm	15	5	6.5%	0.0139 mm	30	4.5	5.8%	0.0098 mm	60	4	5.2%	0.0070 mm	240	1	1.3%	0.0035 mm	1440	1	1.3%	0.0014 mm																																		
Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	7	9.1%	0.0532 mm																																																																				
2	7	9.1%	0.0376 mm																																																																				
5	6	7.8%	0.0239 mm																																																																				
15	5	6.5%	0.0139 mm																																																																				
30	4.5	5.8%	0.0098 mm																																																																				
60	4	5.2%	0.0070 mm																																																																				
240	1	1.3%	0.0035 mm																																																																				
1440	1	1.3%	0.0014 mm																																																																				
% Gravel: 2.2% % Sand: 82.3% % Silt: 12.6% % Clay: 3.0%																																																																							
USDA Soil Textural Classification <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr> <td>% Sand:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																														
	Particle Size																																																																						
% Sand:	2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						
USDA Soil Textural Classification Sand																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 

 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT15-GB-17.5-25.4 ft Sample#: B21-1792	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	ACCREDITED Certificate #: 1366.01
--	---	---	--------------------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs <p style="text-align: center;">Sample Meets Specs ? N/A</p>	D ₍₅₎ = 0.023 mm D ₍₁₀₎ = 0.046 mm D ₍₁₅₎ = 0.069 mm D ₍₃₀₎ = 0.125 mm D ₍₅₀₎ = 0.234 mm D ₍₆₀₎ = 0.299 mm D ₍₉₀₎ = 1.927 mm Dust Ratio = 7/34	% Gravel = 8.2% % Sand = 75.4% % Silt & Clay = 16.4% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.13 Coeff. of Uniformity, C _u = 6.52 Fineness Modulus = 1.71 Plastic Limit = n/a Moisture %, as sampled = 28.3% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		98%	100.0%	0.0%
1.50"	37.50		96%	100.0%	0.0%
1.25"	31.50		94%	100.0%	0.0%
1.00"	25.00	92%	92%	100.0%	0.0%
3/4"	19.00	92%	92%	100.0%	0.0%
5/8"	16.00		92%	100.0%	0.0%
1/2"	12.50	92%	92%	100.0%	0.0%
3/8"	9.50	92%	92%	100.0%	0.0%
1/4"	6.30		92%	100.0%	0.0%
#4	4.75	92%	92%	100.0%	0.0%
#8	2.36		91%	100.0%	0.0%
#10	2.00	91%	91%	100.0%	0.0%
#16	1.18		85%	100.0%	0.0%
#20	0.850		83%	100.0%	0.0%
#30	0.600		81%	100.0%	0.0%
#40	0.425	80%	80%	100.0%	0.0%
#50	0.300		60%	100.0%	0.0%
#60	0.250		52%	100.0%	0.0%
#80	0.180		42%	100.0%	0.0%
#100	0.150	37%	37%	100.0%	0.0%
#140	0.106		25%	100.0%	0.0%
#170	0.090		20%	100.0%	0.0%
#200	0.075	16.4%	16.4%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT15-GB-25.4-27.5 ft Sample#: B21-1793	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.006 mm D ₍₁₀₎ = 0.010 mm D ₍₁₅₎ = 0.022 mm D ₍₃₀₎ = 0.066 mm D ₍₅₀₎ = 0.104 mm D ₍₆₀₎ = 0.125 mm D ₍₉₀₎ = 0.331 mm Dust Ratio = 29/79	% Gravel = 0.0% % Sand = 63.6% % Silt & Clay = 36.4% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 3.56 Coeff. of Uniformity, C _u = 12.70 Fineness Modulus = 0.42 Plastic Limit = n/a Moisture %, as sampled = 30.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850		99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		87%	100.0%	0.0%
#60	0.250		82%	100.0%	0.0%
#80	0.180		75%	100.0%	0.0%
#100	0.150	72%	72%	100.0%	0.0%
#140	0.106		51%	100.0%	0.0%
#170	0.090		44%	100.0%	0.0%
#200	0.075	36.4%	36.4%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT15-GB-25.4-27.5 ft Sample#: B21-1793	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Sp Gr : 2.46 Sample Weight: 76.16 grams Hydrosopic Moist.: 4.72% Adj. Sample Wgt : 72.73 grams		Sieve Analysis Grain Size Distribution																																																																					
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>72%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>36.4%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>35.7%</td><td>0.074 mm</td></tr> <tr><td></td><td>22.4%</td><td>0.050 mm</td></tr> <tr><td></td><td>14.5%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>4.6%</td><td>0.005 mm</td></tr> <tr><td></td><td>2.5%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.4%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	99%	0.425 mm	#100	72%	0.150 mm	#200	36.4%	0.075 mm	Silts	35.7%	0.074 mm		22.4%	0.050 mm		14.5%	0.020 mm	Clays	4.6%	0.005 mm		2.5%	0.002 mm	Colloids	1.4%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	100%	2.000 mm																																																																					
#20	99%	0.850 mm																																																																					
#40	99%	0.425 mm																																																																					
#100	72%	0.150 mm																																																																					
#200	36.4%	0.075 mm																																																																					
Silts	35.7%	0.074 mm																																																																					
	22.4%	0.050 mm																																																																					
	14.5%	0.020 mm																																																																					
Clays	4.6%	0.005 mm																																																																					
	2.5%	0.002 mm																																																																					
Colloids	1.4%	0.001 mm																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>15</td><td>21.7%</td><td>0.0541 mm</td></tr> <tr><td>2</td><td>13.5</td><td>19.5%</td><td>0.0388 mm</td></tr> <tr><td>5</td><td>11</td><td>15.9%</td><td>0.0248 mm</td></tr> <tr><td>15</td><td>9</td><td>13.0%</td><td>0.0145 mm</td></tr> <tr><td>30</td><td>7.5</td><td>10.8%</td><td>0.0104 mm</td></tr> <tr><td>60</td><td>4.5</td><td>6.5%</td><td>0.0074 mm</td></tr> <tr><td>240</td><td>2.5</td><td>3.6%</td><td>0.0038 mm</td></tr> <tr><td>1440</td><td>1.5</td><td>2.2%</td><td>0.0015 mm</td></tr> </tbody> </table>		Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	15	21.7%	0.0541 mm	2	13.5	19.5%	0.0388 mm	5	11	15.9%	0.0248 mm	15	9	13.0%	0.0145 mm	30	7.5	10.8%	0.0104 mm	60	4.5	6.5%	0.0074 mm	240	2.5	3.6%	0.0038 mm	1440	1.5	2.2%	0.0015 mm																																		
Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	15	21.7%	0.0541 mm																																																																				
2	13.5	19.5%	0.0388 mm																																																																				
5	11	15.9%	0.0248 mm																																																																				
15	9	13.0%	0.0145 mm																																																																				
30	7.5	10.8%	0.0104 mm																																																																				
60	4.5	6.5%	0.0074 mm																																																																				
240	2.5	3.6%	0.0038 mm																																																																				
1440	1.5	2.2%	0.0015 mm																																																																				
% Gravel: 0.0% % Sand: 63.6% % Silt: 31.8% % Clay: 4.6%		Liquid Limit: n/a Plastic Limit: n/a Plasticity Index: n/a																																																																					
USDA Soil Textural Classification																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																														
	Particle Size																																																																						
% Sand:	2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						
USDA Soil Textural Classification																																																																							
Loamy Sand																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____
 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT29-0-10.6 ft Sample #: B21-1796	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 21-Sep-21 Tested By: C. Kriss	Visual Identification Silt Sample Color brown
---	---	--


Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	32.74	33.79	36.07			
Weight of Dry Soils + Pan:	28.61	29.18	30.52			
Weight of Pan:	19.91	19.73	19.61			
Weight of Dry Soils:	8.70	9.45	10.91			
Weight of Moisture:	4.13	4.61	5.55			
% Moisture:	47.5 %	48.8 %	50.9 %			
Number of Blows:	25	16	11			

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Plastic limit cannot be determined					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						


Liquid Limit @ 25 Blows: 47 %

Plastic Limit: N/A


Plasticity Index, I_p: N/A



ACCREDITED
Certificate #: 1366.01, 1366.02 & 1366.04



Copyright Spears Engineering & Technical Services PS, 1996-98



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by: 
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT29-GB-11-21 ft Sample#: B21-1798	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.156 mm D ₍₁₀₎ = 0.197 mm D ₍₁₅₎ = 0.237 mm D ₍₃₀₎ = 0.358 mm D ₍₅₀₎ = 0.737 mm D ₍₆₀₎ = 1.003 mm D ₍₉₀₎ = 1.801 mm Dust Ratio = 3/56	% Gravel = 0.5% % Sand = 97.4% % Silt & Clay = 2.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.65 Coeff. of Uniformity, C _u = 5.10 Fineness Modulus = 2.64 Plastic Limit = n/a Moisture %, as sampled = 21.6% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36		98%	100.0%	0.0%
#10	2.00	97%	97%	100.0%	0.0%
#16	1.18		67%	100.0%	0.0%
#20	0.850		54%	100.0%	0.0%
#30	0.600		45%	100.0%	0.0%
#40	0.425	38%	38%	100.0%	0.0%
#50	0.300		23%	100.0%	0.0%
#60	0.250		17%	100.0%	0.0%
#80	0.180		8%	100.0%	0.0%
#100	0.150	4%	4%	100.0%	0.0%
#140	0.106		3%	100.0%	0.0%
#170	0.090		2%	100.0%	0.0%
#200	0.075	2.0%	2.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT29-GB-21-26 ft Sample#: B21-1800	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: gray	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.153 mm D ₍₁₀₎ = 0.185 mm D ₍₁₅₎ = 0.218 mm D ₍₃₀₎ = 0.314 mm D ₍₅₀₎ = 0.527 mm D ₍₆₀₎ = 0.883 mm D ₍₉₀₎ = 1.952 mm Dust Ratio = 3/80	% Gravel = 4.9% % Sand = 93.3% % Silt & Clay = 1.8% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.60 Coeff. of Uniformity, C _u = 4.77 Fineness Modulus = 2.67 Plastic Limit = n/a Moisture %, as sampled = 18.8% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	97%	97%	100.0%	0.0%
5/8"	16.00		97%	100.0%	0.0%
1/2"	12.50	97%	97%	100.0%	0.0%
3/8"	9.50	96%	96%	100.0%	0.0%
1/4"	6.30		95%	100.0%	0.0%
#4	4.75	95%	95%	100.0%	0.0%
#8	2.36		92%	100.0%	0.0%
#10	2.00	91%	91%	100.0%	0.0%
#16	1.18		68%	100.0%	0.0%
#20	0.850		59%	100.0%	0.0%
#30	0.600		52%	100.0%	0.0%
#40	0.425	47%	47%	100.0%	0.0%
#50	0.300		28%	100.0%	0.0%
#60	0.250		20%	100.0%	0.0%
#80	0.180		9%	100.0%	0.0%
#100	0.150	5%	5%	100.0%	0.0%
#140	0.106		3%	100.0%	0.0%
#170	0.090		2%	100.0%	0.0%
#200	0.075	1.8%	1.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1800
 Sample Date: 7/14/2021
 Test Date: 9/29/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT29-GB-21-26 ft
 Visual Soil Description: gray sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	23.0	
	Initial	Post-Consolidation
Dry Density (PCF):	107.5	108.1
Void Ratio:	0.567	0.558
Porosity (%):	36.2	35.8
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	22.3	
	Initial	Post-Consolidation
Dry Density (PCF):	107.1	108.5
Void Ratio:	0.572	0.552
Porosity (%):	36.4	35.6
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	21.8	
	Initial	Post-Consolidation
Dry Density (PCF):	108.8	110.9
Void Ratio:	0.548	0.519
Porosity (%):	35.4	34.2
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	36	34
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	270	700	1490
Residual Horizontal Stress, τ_h (PSF):	200	640	1390



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787


Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT29-GB-26-28.9 ft Sample#: B21-1801	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.008 mm D ₍₁₀₎ = 0.040 mm D ₍₁₅₎ = 0.061 mm D ₍₃₀₎ = 0.094 mm D ₍₅₀₎ = 0.135 mm D ₍₆₀₎ = 0.167 mm D ₍₉₀₎ = 0.375 mm Dust Ratio = 15/71	% Gravel = 0.0% % Sand = 79.4% % Silt & Clay = 20.6% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.33 Coeff. of Uniformity, C _u = 4.18 Fineness Modulus = 0.67 Plastic Limit = n/a Moisture %, as sampled = 36.9% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	100%	100.0%	0.0%
#20	0.850	98%	100%	100.0%	0.0%
#30	0.600	98%	100%	100.0%	0.0%
#40	0.425	97%	97%	100.0%	0.0%
#50	0.300	79%	79%	100.0%	0.0%
#60	0.250	72%	72%	100.0%	0.0%
#80	0.180	62%	62%	100.0%	0.0%
#100	0.150	58%	58%	100.0%	0.0%
#140	0.106	36%	36%	100.0%	0.0%
#170	0.090	28%	28%	100.0%	0.0%
#200	0.075	20.6%	20.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report


Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client : Anchor QEA Source: LDW21-GT29-GB-26-28.9 ft Sample#: B21-1801	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Assumed Sp Gr : 2.65 Sample Weight: 100.10 grams Hydrosopic Moist.: 1.34% Adj. Sample Wgt : 98.78 grams		Sieve Analysis Grain Size Distribution																																																																					
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>98%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>97%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>58%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>20.6%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>20.2%</td><td>0.074 mm</td></tr> <tr><td></td><td>10.1%</td><td>0.050 mm</td></tr> <tr><td></td><td>8.7%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>3.8%</td><td>0.005 mm</td></tr> <tr><td></td><td>2.1%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.1%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	98%	0.850 mm	#40	97%	0.425 mm	#100	58%	0.150 mm	#200	20.6%	0.075 mm	Silts	20.2%	0.074 mm		10.1%	0.050 mm		8.7%	0.020 mm	Clays	3.8%	0.005 mm		2.1%	0.002 mm	Colloids	1.1%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	100%	2.000 mm																																																																					
#20	98%	0.850 mm																																																																					
#40	97%	0.425 mm																																																																					
#100	58%	0.150 mm																																																																					
#200	20.6%	0.075 mm																																																																					
Silts	20.2%	0.074 mm																																																																					
	10.1%	0.050 mm																																																																					
	8.7%	0.020 mm																																																																					
Clays	3.8%	0.005 mm																																																																					
	2.1%	0.002 mm																																																																					
Colloids	1.1%	0.001 mm																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>11.5</td><td>11.6%</td><td>0.0520 mm</td></tr> <tr><td>2</td><td>9.5</td><td>9.6%</td><td>0.0371 mm</td></tr> <tr><td>5</td><td>9</td><td>9.1%</td><td>0.0235 mm</td></tr> <tr><td>15</td><td>8</td><td>8.1%</td><td>0.0137 mm</td></tr> <tr><td>30</td><td>6</td><td>6.1%</td><td>0.0097 mm</td></tr> <tr><td>60</td><td>4</td><td>4.0%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>3.5</td><td>3.5%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1.5</td><td>1.5%</td><td>0.0014 mm</td></tr> </tbody> </table>		Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	11.5	11.6%	0.0520 mm	2	9.5	9.6%	0.0371 mm	5	9	9.1%	0.0235 mm	15	8	8.1%	0.0137 mm	30	6	6.1%	0.0097 mm	60	4	4.0%	0.0070 mm	240	3.5	3.5%	0.0035 mm	1440	1.5	1.5%	0.0014 mm																																		
Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	11.5	11.6%	0.0520 mm																																																																				
2	9.5	9.6%	0.0371 mm																																																																				
5	9	9.1%	0.0235 mm																																																																				
15	8	8.1%	0.0137 mm																																																																				
30	6	6.1%	0.0097 mm																																																																				
60	4	4.0%	0.0070 mm																																																																				
240	3.5	3.5%	0.0035 mm																																																																				
1440	1.5	1.5%	0.0014 mm																																																																				
% Gravel: 0.0% % Sand: 79.4% % Silt: 16.8% % Clay: 3.8%																																																																							
USDA Soil Textural Classification <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr> <td>% Sand:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																														
	Particle Size																																																																						
% Sand:	2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						
USDA Soil Textural Classification Sand																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT29-GB-28.9-31 ft Sample#: B21-1802	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 20-Sep-21 Tested By: C. Kriss	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	
--	---	---	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.009 mm	% Gravel = 0.0%	Coeff. of Curvature, C _c = 1.57
D ₍₁₀₎ = 0.019 mm	% Sand = 60.4%	Coeff. of Uniformity, C _u = 5.75
D ₍₁₅₎ = 0.028 mm	% Silt & Clay = 39.6%	Fineness Modulus = 0.24
D ₍₃₀₎ = 0.057 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.092 mm	Plasticity Index = n/a	Moisture %, as sampled = 37.2%
D ₍₆₀₎ = 0.109 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.249 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 2/5	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		93%	100.0%	0.0%
#60	0.250		90%	100.0%	0.0%
#80	0.180		86%	100.0%	0.0%
#100	0.150	85%	85%	100.0%	0.0%
#140	0.106		58%	100.0%	0.0%
#170	0.090		49%	100.0%	0.0%
#200	0.075	39.6%	39.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by: 
Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 14, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1812 - 1832
Date sampled: July 15, 2021

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
<input checked="" type="checkbox"/>	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
<input checked="" type="checkbox"/>	Moisture Content	Please See Attached Report	<input checked="" type="checkbox"/>	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		<input checked="" type="checkbox"/>	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
<input checked="" type="checkbox"/>	Hydrometer Analysis	Please See Attached Reports			
<input checked="" type="checkbox"/>	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM D854

Project: Q.C. - Lower Duwamish Waterway

Client: Anchor QEA

Project #: 21B233

Date Received: July 29, 2021

Sampled by: Client

Date Tested: September 20, 2021

Tested by: A. Eifrig

Table with 15 columns: Sample #, Location, Tare, Dry Soil + Tare, Mass of Dry Soil, Pycno ID, Mass of Pycno, Volume of Pycno, Density of Water @ Tx, Mass of Pycno filled w/ water & soils, Mass of Pycno filled w/ water, Temp. of Water, 0.1 °C, SpG of Soils, Temp. Correction Factor, Corrected SpG. Contains 3 rows of data and many empty rows.

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: [Signature] Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT25-GB-0-8.5 ft Sample #: B21-1813	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Silt with Clay Sample Color brown
--	--	--


Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	29.60	25.42	26.01			
Weight of Dry Soils + Pan:	25.96	21.62	21.93			
Weight of Pan:	19.65	15.20	15.00			
Weight of Dry Soils:	6.31	6.42	6.93			
Weight of Moisture:	3.64	3.80	4.08			
% Moisture:	57.7 %	59.2 %	58.9 %			
Number of Blows:	28	22	17			

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	35.15	34.29				
Weight of Dry Soils + Pan:	33.00	32.39				
Weight of Pan:	28.27	28.20				
Weight of Dry Soils:	4.73	4.19				
Weight of Moisture:	2.15	1.90				
% Moisture:	45.5 %	45.4 %				


Liquid Limit @ 25 Blows: 58 %

Plastic Limit: 45 %


Plasticity Index, I_p: 13 %



Certificate #: 1366.01, 1366.02 & 1366.04



Copyright Spears Engineering & Technical Services PS, 1996-98



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____



Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT25-GB-8.5-16.2 ft Sample#: B21-1815	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.216 mm D ₍₁₀₎ = 0.395 mm D ₍₁₅₎ = 0.501 mm D ₍₃₀₎ = 0.773 mm D ₍₅₀₎ = 1.137 mm D ₍₆₀₎ = 1.318 mm D ₍₉₀₎ = 1.864 mm Dust Ratio = 17/97	% Gravel = 1.1% % Sand = 97.0% % Silt & Clay = 1.9% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.15 Coeff. of Uniformity, C _u = 3.34 Fineness Modulus = 3.20 Plastic Limit = n/a Moisture %, as sampled = 24.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	99%	99%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36		98%	100.0%	0.0%
#10	2.00	97%	97%	100.0%	0.0%
#16	1.18		52%	100.0%	0.0%
#20	0.850		34%	100.0%	0.0%
#30	0.600		20%	100.0%	0.0%
#40	0.425	11%	11%	100.0%	0.0%
#50	0.300		7%	100.0%	0.0%
#60	0.250		6%	100.0%	0.0%
#80	0.180		4%	100.0%	0.0%
#100	0.150	3%	3%	100.0%	0.0%
#140	0.106		2%	100.0%	0.0%
#170	0.090		2%	100.0%	0.0%
#200	0.075	1.9%	1.9%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1815
 Sample Date: 7/15/2021
 Test Date: 9/30/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT25-GB-8.5-16.2 ft
 Visual Soil Description: brown sand with silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	25.1	
	Initial	Post-Consolidation
Dry Density (PCF):	108.7	109.7
Void Ratio:	0.550	0.536
Porosity (%):	35.5	34.9
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	24.7	
	Initial	Post-Consolidation
Dry Density (PCF):	107.3	108.8
Void Ratio:	0.571	0.549
Porosity (%):	36.3	35.4
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	25.6	
	Initial	Post-Consolidation
Dry Density (PCF):	107.7	110.3
Void Ratio:	0.564	0.527
Porosity (%):	36.0	34.5
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	37	35
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	380	810	1480
Residual Horizontal Stress, τ_h (PSF):	300	640	1430



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787




Visit our website: www.mtc-inc.net

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT25-GB-16.2-18.5 ft Sample #: B21-1816	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Sand Sample Color grayish-brown			
Liquid Limit Determination					
#1 #2 #3 #4 #5 #6					
Weight of Wet Soils + Pan:					
Weight of Dry Soils + Pan:	Unable to establish liquid limit				
Weight of Pan:					
Weight of Dry Soils:					
Weight of Moisture:					
% Moisture:					
Number of Blows:					
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A					
Plastic Limit Determination					
#1 #2 #3 #4 #5 #6					
Weight of Wet Soils + Pan:					
Weight of Dry Soils + Pan:	Cannot determined plastic limit				
Weight of Pan:					
Weight of Dry Soils:					
Weight of Moisture:					
% Moisture:					
 <small>Certificate #: 1366.01, 1366.02 & 1366.04</small>					
					
					

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by: 
 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT25-GB-18.5-24.4 ft Sample #: B21-1818	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Sand Sample Color grayish-brown
--	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Unable to establish liquid limit					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Cannot determined plastic limit					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						

Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT25-GB-26-28.5 ft Sample#: B21-1820	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Sandy Silt with Clay Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.003 mm	% Gravel = 0.0%	Coeff. of Curvature, C _c = 3.28
D ₍₁₀₎ = 0.008 mm	% Sand = 39.1%	Coeff. of Uniformity, C _u = 9.69
D ₍₁₅₎ = 0.013 mm	% Silt & Clay = 60.9%	Fineness Modulus = 0.16
D ₍₃₀₎ = 0.043 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.065 mm	Plasticity Index = n/a	Moisture %, as sampled = 34.2%
D ₍₆₀₎ = 0.074 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.167 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 11/18	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	100%	100%	100.0%	0.0%
#40	0.425	100%	100%	100.0%	0.0%
#50	0.300	95%	95%	100.0%	0.0%
#60	0.250	93%	93%	100.0%	0.0%
#80	0.180	90%	90%	100.0%	0.0%
#100	0.150	89%	89%	100.0%	0.0%
#140	0.106	73%	73%	100.0%	0.0%
#170	0.090	67%	67%	100.0%	0.0%
#200	0.075	60.9%	60.9%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT33-GB-0-10.4 ft Sample #: B21-1823	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Silt with Clay Sample Color brown
---	--	--


Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	28.38	32.44	32.76			
Weight of Dry Soils + Pan:	24.50	28.64	28.74			
Weight of Pan:	15.01	19.79	19.63			
Weight of Dry Soils:	9.49	8.85	9.11			
Weight of Moisture:	3.88	3.80	4.02			
% Moisture:	40.9 %	42.9 %	44.1 %			
Number of Blows:	32	21	15			

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	35.43	35.12				
Weight of Dry Soils + Pan:	33.78	33.45				
Weight of Pan:	28.65	28.27				
Weight of Dry Soils:	5.13	5.18				
Weight of Moisture:	1.65	1.67				
% Moisture:	32.2 %	32.2 %				


Liquid Limit @ 25 Blows: 42 %

Plastic Limit: 32 %


Plasticity Index, I_p: 10 %



Certificate #: 1366.01, 1366.02 & 1366.04



Copyright Spears Engineering & Technical Services PS, 1996-98



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT33-GB-11-18.5 ft Sample#: B21-1825	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.128 mm D ₍₁₀₎ = 0.189 mm D ₍₁₅₎ = 0.234 mm D ₍₃₀₎ = 0.368 mm D ₍₅₀₎ = 0.772 mm D ₍₆₀₎ = 1.025 mm D ₍₉₀₎ = 1.786 mm Dust Ratio = 5/54	% Gravel = 0.1% % Sand = 96.5% % Silt & Clay = 3.4% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.70 Coeff. of Uniformity, C _u = 5.43 Fineness Modulus = 2.64 Plastic Limit = n/a Moisture %, as sampled = 22.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	98%	98%	100.0%	0.0%
#16	1.18		66%	100.0%	0.0%
#20	0.850		53%	100.0%	0.0%
#30	0.600		43%	100.0%	0.0%
#40	0.425	36%	36%	100.0%	0.0%
#50	0.300		22%	100.0%	0.0%
#60	0.250		17%	100.0%	0.0%
#80	0.180		9%	100.0%	0.0%
#100	0.150	6%	6%	100.0%	0.0%
#140	0.106		4%	100.0%	0.0%
#170	0.090		4%	100.0%	0.0%
#200	0.075	3.4%	3.4%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1825
 Sample Date: 7/15/2021
 Test Date: 10/1/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT33-GB-11-18.5 ft
 Visual Soil Description: brown sand with silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	27.4	
	Initial	Post-Consolidation
Dry Density (PCF):	105.9	106.9
Void Ratio:	0.591	0.577
Porosity (%):	37.2	36.6
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	27.4	
	Initial	Post-Consolidation
Dry Density (PCF):	106.2	107.7
Void Ratio:	0.586	0.564
Porosity (%):	36.9	36.1
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	26.6	
	Initial	Post-Consolidation
Dry Density (PCF):	106.1	108.6
Void Ratio:	0.589	0.551
Porosity (%):	37.0	35.5
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	38	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	290	720	1480
Residual Horizontal Stress, τ_h (PSF):	290	570	1300



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT23-GB-18.5-21 ft Sample #: B21-1826	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Silty Sand Sample Color brown											
<div style="border: 1px solid red; padding: 2px; display: inline-block; color: red; font-weight: bold;"> NAME CORRECTION: LDW21-GT33-18.5-21 </div>													
Liquid Limit Determination													
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture: Number of Blows:	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>#1</th> <th>#2</th> <th>#3</th> <th>#4</th> <th>#5</th> <th>#6</th> </tr> </thead> <tbody> <tr> <td colspan="6" style="text-align: center; background-color: yellow;">Unable to establish liquid limit</td> </tr> </tbody> </table>	#1	#2	#3	#4	#5	#6	Unable to establish liquid limit					
#1	#2	#3	#4	#5	#6								
Unable to establish liquid limit													
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A													
Plastic Limit Determination													
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture:	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>#1</th> <th>#2</th> <th>#3</th> <th>#4</th> <th>#5</th> <th>#6</th> </tr> </thead> <tbody> <tr> <td colspan="6" style="text-align: center; background-color: yellow;">Cannot determined plastic limit</td> </tr> </tbody> </table>	#1	#2	#3	#4	#5	#6	Cannot determined plastic limit					
#1	#2	#3	#4	#5	#6								
Cannot determined plastic limit													

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.


Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT33-GB-21-26.8 ft Sample#: B21-1828	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Unified Soils Classification System, ASTM D-2487 ML, Sandy Silt Sample Color: brown	 ACCREDITED Certificate #: 1366.01
--	--	--	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.004 mm D ₍₁₀₎ = 0.007 mm D ₍₁₅₎ = 0.010 mm D ₍₃₀₎ = 0.036 mm D ₍₅₀₎ = 0.064 mm D ₍₆₀₎ = 0.074 mm D ₍₉₀₎ = 0.141 mm Dust Ratio = 43/70	% Gravel = 0.0% % Sand = 38.9% % Silt & Clay = 61.1% Liquid Limit = 0.0% Plasticity Index = 0.0% Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 2.51 Coeff. of Uniformity, C _u = 10.39 Fineness Modulus = 0.10 Plastic Limit = 0.0% Moisture %, as sampled = 34.4% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	100%	100%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	97%	97%	100.0%	0.0%
#60	0.250	96%	96%	100.0%	0.0%
#80	0.180	94%	94%	100.0%	0.0%
#100	0.150	94%	94%	100.0%	0.0%
#140	0.106	75%	75%	100.0%	0.0%
#170	0.090	68%	68%	100.0%	0.0%
#200	0.075	61.1%	61.1%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT33-GB-21-26.8 ft Sample#: B21-1828	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Unified Soils Classification System, ASTM D-2487 ML, Sandy Silt Sample Color brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Assumed Sp Gr : 2.65 Sample Weight: 75.85 grams Hydroscopic Moist.: 3.68% Adj. Sample Wgt : 73.16 grams																																																																							
<table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>25</td><td>34.2%</td><td>0.0477 mm</td></tr> <tr><td>2</td><td>21.5</td><td>29.4%</td><td>0.0347 mm</td></tr> <tr><td>5</td><td>17.5</td><td>23.9%</td><td>0.0224 mm</td></tr> <tr><td>15</td><td>12.5</td><td>17.1%</td><td>0.0133 mm</td></tr> <tr><td>30</td><td>10.5</td><td>14.4%</td><td>0.0096 mm</td></tr> <tr><td>60</td><td>7</td><td>9.6%</td><td>0.0069 mm</td></tr> <tr><td>240</td><td>3.5</td><td>4.8%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>2.5</td><td>3.4%</td><td>0.0014 mm</td></tr> </tbody> </table>			Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	25	34.2%	0.0477 mm	2	21.5	29.4%	0.0347 mm	5	17.5	23.9%	0.0224 mm	15	12.5	17.1%	0.0133 mm	30	10.5	14.4%	0.0096 mm	60	7	9.6%	0.0069 mm	240	3.5	4.8%	0.0035 mm	1440	2.5	3.4%	0.0014 mm																																	
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	25	34.2%	0.0477 mm																																																																				
2	21.5	29.4%	0.0347 mm																																																																				
5	17.5	23.9%	0.0224 mm																																																																				
15	12.5	17.1%	0.0133 mm																																																																				
30	10.5	14.4%	0.0096 mm																																																																				
60	7	9.6%	0.0069 mm																																																																				
240	3.5	4.8%	0.0035 mm																																																																				
1440	2.5	3.4%	0.0014 mm																																																																				
% Gravel: 0.0% % Sand: 38.9% % Silt: 54.2% % Clay: 6.9%		<table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>100%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>94%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>61.1%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>60.1%</td><td>0.074 mm</td></tr> <tr><td></td><td>44.4%</td><td>0.050 mm</td></tr> <tr><td></td><td>22.1%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>6.9%</td><td>0.005 mm</td></tr> <tr><td></td><td>3.8%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>2.4%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	100%	0.850 mm	#40	99%	0.425 mm	#100	94%	0.150 mm	#200	61.1%	0.075 mm	Silts	60.1%	0.074 mm		44.4%	0.050 mm		22.1%	0.020 mm	Clays	6.9%	0.005 mm		3.8%	0.002 mm	Colloids	2.4%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	100%	2.000 mm																																																																					
#20	100%	0.850 mm																																																																					
#40	99%	0.425 mm																																																																					
#100	94%	0.150 mm																																																																					
#200	61.1%	0.075 mm																																																																					
Silts	60.1%	0.074 mm																																																																					
	44.4%	0.050 mm																																																																					
	22.1%	0.020 mm																																																																					
Clays	6.9%	0.005 mm																																																																					
	3.8%	0.002 mm																																																																					
Colloids	2.4%	0.001 mm																																																																					
USDA Soil Textural Classification																																																																							
<table border="0" style="width: 100%;"> <tr><td style="width: 50%;"></td><td style="text-align: center;">Particle Size</td></tr> <tr><td>% Sand:</td><td style="text-align: center;">2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td style="text-align: center;">0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td style="text-align: center;">< 0.002 mm</td></tr> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																														
	Particle Size																																																																						
% Sand:	2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						
USDA Soil Textural Classification																																																																							
Sandy Loam																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 




 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT33-GB-21-26.8 ft Sample #: B21-1828	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Unified Soils Classification System, ASTM D-2487 ML, Sandy Silt Sample Color brown				
Liquid Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Unable to establish liquid limit					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A						
Plastic Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Cannot determined plastic limit					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
						
						

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.




Reviewed by: 
 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils


Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT33-GB-26.8-28.8 ft Sample #: B21-1829	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Silty Sand Sample Color brown				
Liquid Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Unable to establish liquid limit					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A						
Plastic Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Cannot determined plastic limit					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
 ACCREDITED <small>Certificate #: 1366.01, 1366.02 & 1366.04</small>						
						
						

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.


Reviewed by: 
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT33-GB-28.8-29.5 ft Sample#: B21-1830	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 ACCREDITED Certificate #: 1366.01
--	--	---	--


ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D₍₅₎ = 0.010 mm D₍₁₀₎ = 0.047 mm D₍₁₅₎ = 0.061 mm D₍₃₀₎ = 0.096 mm D₍₅₀₎ = 0.158 mm D₍₆₀₎ = 0.213 mm D₍₉₀₎ = 0.378 mm Dust Ratio = 7/30	% Gravel = 0.0% % Sand = 77.0% % Silt & Clay = 23.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.90 Coeff. of Uniformity, C _u = 4.50 Fineness Modulus = 0.78 Plastic Limit = n/a Moisture %, as sampled = 33.6% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	99%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	76%	76%	100.0%	0.0%
#60	0.250	67%	67%	100.0%	0.0%
#80	0.180	54%	54%	100.0%	0.0%
#100	0.150	48%	48%	100.0%	0.0%
#140	0.106	34%	34%	100.0%	0.0%
#170	0.090	28%	28%	100.0%	0.0%
#200	0.075	23.0%	23.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.


Comments: _____

Reviewed by: 

 Meghan Blodgett-Carrillo



Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT33-GB-28.8-29.5 ft Sample#: B21-1830	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Assumed Sp Gr : 2.65 Sample Weight: 80.02 grams Hydroscopic Moist.: 4.80% Adj. Sample Wgt : 76.35 grams		Sieve Analysis Grain Size Distribution																																																																					
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>48%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>23.0%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>22.4%</td><td>0.074 mm</td></tr> <tr><td></td><td>10.9%</td><td>0.050 mm</td></tr> <tr><td></td><td>6.9%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>2.2%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.5%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	99%	0.425 mm	#100	48%	0.150 mm	#200	23.0%	0.075 mm	Silts	22.4%	0.074 mm		10.9%	0.050 mm		6.9%	0.020 mm	Clays	2.2%	0.005 mm		1.5%	0.002 mm	Colloids	0.9%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	100%	2.000 mm																																																																					
#20	99%	0.850 mm																																																																					
#40	99%	0.425 mm																																																																					
#100	48%	0.150 mm																																																																					
#200	23.0%	0.075 mm																																																																					
Silts	22.4%	0.074 mm																																																																					
	10.9%	0.050 mm																																																																					
	6.9%	0.020 mm																																																																					
Clays	2.2%	0.005 mm																																																																					
	1.5%	0.002 mm																																																																					
Colloids	0.9%	0.001 mm																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>8</td><td>10.5%</td><td>0.0529 mm</td></tr> <tr><td>2</td><td>7</td><td>9.2%</td><td>0.0376 mm</td></tr> <tr><td>5</td><td>5.5</td><td>7.2%</td><td>0.0240 mm</td></tr> <tr><td>15</td><td>5</td><td>6.5%</td><td>0.0139 mm</td></tr> <tr><td>30</td><td>4</td><td>5.2%</td><td>0.0098 mm</td></tr> <tr><td>60</td><td>2</td><td>2.6%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>1.5</td><td>2.0%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.3%</td><td>0.0014 mm</td></tr> </tbody> </table>		Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	8	10.5%	0.0529 mm	2	7	9.2%	0.0376 mm	5	5.5	7.2%	0.0240 mm	15	5	6.5%	0.0139 mm	30	4	5.2%	0.0098 mm	60	2	2.6%	0.0070 mm	240	1.5	2.0%	0.0035 mm	1440	1	1.3%	0.0014 mm																																		
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	8	10.5%	0.0529 mm																																																																				
2	7	9.2%	0.0376 mm																																																																				
5	5.5	7.2%	0.0240 mm																																																																				
15	5	6.5%	0.0139 mm																																																																				
30	4	5.2%	0.0098 mm																																																																				
60	2	2.6%	0.0070 mm																																																																				
240	1.5	2.0%	0.0035 mm																																																																				
1440	1	1.3%	0.0014 mm																																																																				
% Gravel: 0.0% Liquid Limit: n/a % Sand: 77.0% Plastic Limit: n/a % Silt: 20.8% Plasticity Index: n/a % Clay: 2.2%																																																																							
USDA Soil Textural Classification																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																														
	Particle Size																																																																						
% Sand:	2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						
USDA Soil Textural Classification																																																																							
Sand																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____

Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT33-GB-29.5-31 ft Sample #: B21-1831	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 25-Sep-21 Tested By: K. Mendez	Visual Identification Sandy Silt Sample Color brown				
Liquid Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Unable to establish liquid limit					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A						
Plastic Limit Determination						
#1 #2 #3 #4 #5 #6						
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Cannot determined plastic limit					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
<small>Certificate #: 1366.01, 1366.02 & 1366.04</small>						

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 19, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-1948 - 1965
Date sampled: July 16, 2021

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: October 1, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-1948	LDW21-GT39-GB-0-1.5 ft	182.2	359.3	304.7	54.6	122.5	44.6%
B21-1949	LDW21-GT39-GB-0-8.8 ft	229.5	1120.6	890.6	230.0	661.1	34.8%
B21-1950	LDW21-GT39-GB-8.8-10.5 ft	234.3	1839.1	1517.6	321.5	1283.3	25.1%
B21-1951	LDW21-GT39-GB-10.5-12 ft	222.9	1270.1	1072.1	198.0	849.2	23.3%
B21-1952	LDW21-GT39-GB-10.5-20.5 ft	228.8	652.9	584.6	68.3	355.8	19.2%
B21-1953	LDW21-GT39-GB-20.5-21 ft	225.2	577.3	508.6	68.7	283.4	24.2%
B21-1954	LDW21-GT39-GB-20.5-30.5 ft	234.4	1327.0	1148.4	178.6	914.0	19.5%
B21-1955	LDW21-GT39-GB-30.5-32 ft	233.2	876.4	747.6	128.8	514.4	25.0%
B21-1956	LDW21-GT23-GB-0-1.5 ft	223.0	462.7	361.7	101.0	138.7	72.8%
B21-1957	LDW21-GT23-GB-0-8.2 ft	221.9	900.9	625.0	275.9	403.1	68.4%
B21-1958	LDW21-GT23-GB-8.5-10 ft	215.4	919.5	775.8	143.7	560.4	25.6%
B21-1959	LDW21-GT23-GB-8.5-17.6 ft	234.7	1060.0	934.4	125.6	699.7	18.0%
B21-1960	LDW21-GT23-GB-17.6-18.5 ft	217.3	972.1	771.5	200.6	554.2	36.2%
B21-1961	LDW21-GT23-GB-18.5-20 ft	270.1	687.9	581.4	106.5	311.3	34.2%
B21-1962	LDW21-GT23-GB-21.1-22.8 ft	222.3	1022.4	815.3	207.1	593.0	34.9%
B21-1963	LDW21-GT23-GB-22.8-26.8 ft	266.3	870.9	724.1	146.8	457.8	32.1%
B21-1964	LDW21-GT23-GB-27.7-28.5 ft	224.7	963.8	779.9	183.9	555.2	33.1%
B21-1965	LDW21-GT23-GB-30.5-32 ft	235.2	627.7	539.1	88.6	303.9	29.2%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 

Meghan Blodgett-Carrillo



Moisture Content - ASTM D854

Project: Q.C. - Lower Duwamish Waterway

Client: Anchor QEA

Project #: 21B233

Date Received: July 29, 2021

Sampled by: Client

Date Tested: September 20, 2021

Tested by: A. Eifrig

Table with 15 columns: Sample #, Location, Tare, Dry Soil + Tare, Mass of Dry Soil, Pycno ID, Mass of Pycno, Volume of Pycno, Density of Water @ Tx, Mass of Pycno filled w/ water & soils, Mass of Pycno filled w/ water, Temp. of Water, 0.1 °C, SpG of Soils, Temp. Correction Factor, Corrected SpG. Includes data for samples B21-1952 and B21-1957.

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: [Signature] Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT39-GB-0-8.8 ft Sample #: B21-1949	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: C. Kriss	Visual Identification Silt with Sand Sample Color brown				
Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Unable to determine					
Weight of Dry Soils + Pan:	Unable to determine					
Weight of Pan:	Unable to determine					
Weight of Dry Soils:	Unable to determine					
Weight of Moisture:	Unable to determine					
% Moisture:	Unable to determine					
Number of Blows:	Unable to determine					
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A						
Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Unable to establish					
Weight of Dry Soils + Pan:	Unable to establish					
Weight of Pan:	Unable to establish					
Weight of Dry Soils:	Unable to establish					
Weight of Moisture:	Unable to establish					
% Moisture:	Unable to establish					
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p style="font-size: small;">Copyright Spears Engineering & Technical Services PS, 1996-98</p> </div> <div style="width: 35%;"> </div> </div>						

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be determined as the material displays rapid dilation. At lower moistures the sample does not spread into the cup without tearing the soil cake. Unable to establish plastic limit as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT39-GB-8.8-10.5 ft Sample#: B21-1950	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 4-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: grayish-brown	 Certificate #: 1366.01
---	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.157 mm D ₍₁₀₎ = 0.187 mm D ₍₁₅₎ = 0.218 mm D ₍₃₀₎ = 0.311 mm D ₍₅₀₎ = 0.471 mm D ₍₆₀₎ = 0.777 mm D ₍₉₀₎ = 1.696 mm Dust Ratio = 1/24	% Gravel = 0.0% % Sand = 98.0% % Silt & Clay = 2.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.66 Coeff. of Uniformity, C _u = 4.15 Fineness Modulus = 2.40 Plastic Limit = n/a Moisture %, as sampled = 25.0% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		73%	100.0%	0.0%
#20	0.850		62%	100.0%	0.0%
#30	0.600		54%	100.0%	0.0%
#40	0.425	49%	49%	100.0%	0.0%
#50	0.300		28%	100.0%	0.0%
#60	0.250		20%	100.0%	0.0%
#80	0.180		9%	100.0%	0.0%
#100	0.150	4%	4%	100.0%	0.0%
#140	0.106		3%	100.0%	0.0%
#170	0.090		2%	100.0%	0.0%
#200	0.075	2.0%	2.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT39-GB-10.5-20.5 ft Sample#: B21-1952	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 4-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: grayish-brown	 ACCREDITED Certificate #: 1366.01
--	---	--	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.053 mm D ₍₁₀₎ = 0.121 mm D ₍₁₅₎ = 0.178 mm D ₍₃₀₎ = 0.313 mm D ₍₅₀₎ = 0.638 mm D ₍₆₀₎ = 0.919 mm D ₍₉₀₎ = 1.762 mm Dust Ratio = 1/6	% Gravel = 1.1% % Sand = 91.9% % Silt & Clay = 7.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.88 Coeff. of Uniformity, C _u = 7.60 Fineness Modulus = 2.45 Plastic Limit = n/a Moisture %, as sampled = 19.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		99%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36		99%	100.0%	0.0%
#10	2.00	98%	98%	100.0%	0.0%
#16	1.18		69%	100.0%	0.0%
#20	0.850		58%	100.0%	0.0%
#30	0.600		49%	100.0%	0.0%
#40	0.425	42%	42%	100.0%	0.0%
#50	0.300		29%	100.0%	0.0%
#60	0.250		23%	100.0%	0.0%
#80	0.180		15%	100.0%	0.0%
#100	0.150	12%	12%	100.0%	0.0%
#140	0.106		9%	100.0%	0.0%
#170	0.090		8%	100.0%	0.0%
#200	0.075	7.0%	7.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1952
 Sample Date: 7/16/2021
 Test Date: 10/4/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT39-GB-10.5-20.5 ft
 Visual Soil Description: grayish-brown sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	26.0	
	Initial	Post-Consolidation
Dry Density (PCF):	109.4	111.1
Void Ratio:	0.540	0.516
Porosity (%):	35.1	34.0
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	26.7	
	Initial	Post-Consolidation
Dry Density (PCF):	107.4	109.6
Void Ratio:	0.569	0.537
Porosity (%):	36.3	34.9
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	25.2	
	Initial	Post-Consolidation
Dry Density (PCF):	109.0	113.2
Void Ratio:	0.546	0.488
Porosity (%):	35.3	32.8
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	36	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	320	760	1430
Residual Horizontal Stress, τ_h (PSF):	260	640	1260



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT39-GB-20.5-30.5 ft Sample#: B21-1954	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 4-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: gray	 Certificate #: 1366.01
--	---	--	----------------------------

Specifications No Specs <p style="text-align: center;">Sample Meets Specs ? N/A</p>	ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281 D ₍₅₎ = 0.153 mm % Gravel = 2.1% D ₍₁₀₎ = 0.197 mm % Sand = 95.1% D ₍₁₅₎ = 0.241 mm % Silt & Clay = 2.8% D ₍₃₀₎ = 0.371 mm Liquid Limit = n/a D ₍₅₀₎ = 0.789 mm Plasticity Index = n/a D ₍₆₀₎ = 1.051 mm Sand Equivalent = n/a D ₍₉₀₎ = 1.839 mm Fracture %, 1 Face = n/a Dust Ratio = 1/13 Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.67 Coeff. of Uniformity, C _u = 5.34 Fineness Modulus = 2.73 Plastic Limit = n/a Moisture %, as sampled = 19.5% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =
---	---	--

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	99%	99%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30		98%	100.0%	0.0%
#4	4.75	98%	98%	100.0%	0.0%
#8	2.36		96%	100.0%	0.0%
#10	2.00	96%	96%	100.0%	0.0%
#16	1.18		65%	100.0%	0.0%
#20	0.850		52%	100.0%	0.0%
#30	0.600		43%	100.0%	0.0%
#40	0.425	36%	36%	100.0%	0.0%
#50	0.300		22%	100.0%	0.0%
#60	0.250		16%	100.0%	0.0%
#80	0.180		8%	100.0%	0.0%
#100	0.150	5%	5%	100.0%	0.0%
#140	0.106		4%	100.0%	0.0%
#170	0.090		3%	100.0%	0.0%
#200	0.075	2.8%	2.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT23-GB-0-8.2 ft Sample #: B21-1957	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: C. Kriss	Visual Identification Silt with Sand Sample Color brown
--	--	--


Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	33.87	31.07	35.40			
Weight of Dry Soils + Pan:	29.74	27.66	30.53			
Weight of Pan:	19.98	19.72	19.51			
Weight of Dry Soils:	9.76	7.94	11.02			
Weight of Moisture:	4.13	3.41	4.87			
% Moisture:	42.3 %	43.0 %	44.2 %			
Number of Blows:	25	20	13			

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:						
Weight of Dry Soils + Pan:	Unable to establish					
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						


Liquid Limit @ 25 Blows: 42 %

Plastic Limit: N/A


Plasticity Index, I_p: N/A



ACCREDITED
Certificate #: 1366.01, 1366.02 & 1366.04



Copyright Spears Engineering & Technical Services PS, 1996-98



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Unable to establish plastic limit as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Meghan Blodgett Carrillo


Reviewed by: _____
Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT23-GB-8.5-17.6 ft Sample#: B21-1959	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 4-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: grayish-brown	 Certificate #: 1366.01
---	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.056 mm D ₍₁₀₎ = 0.102 mm D ₍₁₅₎ = 0.142 mm D ₍₃₀₎ = 0.292 mm D ₍₅₀₎ = 0.667 mm D ₍₆₀₎ = 1.020 mm D ₍₉₀₎ = 2.624 mm Dust Ratio = 7/45	% Gravel = 2.5% % Sand = 90.8% % Silt & Clay = 6.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.82 Coeff. of Uniformity, C _u = 10.03 Fineness Modulus = 2.55 Plastic Limit = n/a Moisture %, as sampled = 18.0% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30	98%	98%	100.0%	0.0%
#4	4.75	97%	97%	100.0%	0.0%
#8	2.36	89%	89%	100.0%	0.0%
#10	2.00	88%	88%	100.0%	0.0%
#16	1.18	65%	65%	100.0%	0.0%
#20	0.850	55%	55%	100.0%	0.0%
#30	0.600	48%	48%	100.0%	0.0%
#40	0.425	43%	43%	100.0%	0.0%
#50	0.300	31%	31%	100.0%	0.0%
#60	0.250	26%	26%	100.0%	0.0%
#80	0.180	19%	19%	100.0%	0.0%
#100	0.150	16%	16%	100.0%	0.0%
#140	0.106	11%	11%	100.0%	0.0%
#170	0.090	9%	9%	100.0%	0.0%
#200	0.075	6.7%	6.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-1959
 Sample Date: 7/16/2021
 Test Date: 10/5/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT23-GB-8.5-17.6 ft
 Visual Soil Description: grayish-brown sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	22.6	
	Initial	Post-Consolidation
Dry Density (PCF):	109.4	111.1
Void Ratio:	0.539	0.517
Porosity (%):	35.0	34.1
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	22.2	
	Initial	Post-Consolidation
Dry Density (PCF):	110.1	111.8
Void Ratio:	0.531	0.507
Porosity (%):	34.7	33.7
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	23.3	
	Initial	Post-Consolidation
Dry Density (PCF):	109.0	114.1
Void Ratio:	0.545	0.476
Porosity (%):	35.3	32.3
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	39	33
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	440	820	1630
Residual Horizontal Stress, τ_h (PSF):	280	630	1330



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT23-GB-17.6-18.5 ft Sample#: B21-1960	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 4-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: grayish-brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.028 mm D ₍₁₀₎ = 0.059 mm D ₍₁₅₎ = 0.069 mm D ₍₃₀₎ = 0.100 mm D ₍₅₀₎ = 0.142 mm D ₍₆₀₎ = 0.189 mm D ₍₉₀₎ = 0.374 mm Dust Ratio = 2/11	% Gravel = 0.1% % Sand = 82.0% % Silt & Clay = 17.9% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.90 Coeff. of Uniformity, C _u = 3.20 Fineness Modulus = 0.72 Plastic Limit = n/a Moisture %, as sampled = 36.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		99%	100.0%	0.0%
#20	0.850		99%	100.0%	0.0%
#30	0.600		98%	100.0%	0.0%
#40	0.425	98%	98%	100.0%	0.0%
#50	0.300		78%	100.0%	0.0%
#60	0.250		70%	100.0%	0.0%
#80	0.180		59%	100.0%	0.0%
#100	0.150	54%	54%	100.0%	0.0%
#140	0.106		33%	100.0%	0.0%
#170	0.090		25%	100.0%	0.0%
#200	0.075	17.9%	17.9%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo




Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT23-GB-17.6-18.5 ft Sample#: B21-1960	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 4-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color grayish-brown																																																																					
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																					
Assumed Sp Gr : 2.65 Sample Weight: 75.28 grams Hydroscopic Moist.: 1.16% Adj. Sample Wgt : 74.42 grams		Sieve Analysis Grain Size Distribution																																																																					
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>98%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>54%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>17.9%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>17.4%</td><td>0.074 mm</td></tr> <tr><td></td><td>7.2%</td><td>0.050 mm</td></tr> <tr><td></td><td>4.1%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>1.6%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.3%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	98%	0.425 mm	#100	54%	0.150 mm	#200	17.9%	0.075 mm	Silts	17.4%	0.074 mm		7.2%	0.050 mm		4.1%	0.020 mm	Clays	1.6%	0.005 mm		1.3%	0.002 mm	Colloids	0.9%	0.001 mm
Sieve Size	Percent Passing	Soils Particle Diameter																																																																					
3.0"	100%	75.000 mm																																																																					
2.0"	100%	50.000 mm																																																																					
1.5"	100%	37.500 mm																																																																					
1.25"	100%	31.500 mm																																																																					
1.0"	100%	25.000 mm																																																																					
3/4"	100%	19.000 mm																																																																					
5/8"	100%	16.000 mm																																																																					
1/2"	100%	12.500 mm																																																																					
3/8"	100%	9.500 mm																																																																					
1/4"	100%	6.300 mm																																																																					
#4	100%	4.750 mm																																																																					
#10	100%	2.000 mm																																																																					
#20	99%	0.850 mm																																																																					
#40	98%	0.425 mm																																																																					
#100	54%	0.150 mm																																																																					
#200	17.9%	0.075 mm																																																																					
Silts	17.4%	0.074 mm																																																																					
	7.2%	0.050 mm																																																																					
	4.1%	0.020 mm																																																																					
Clays	1.6%	0.005 mm																																																																					
	1.3%	0.002 mm																																																																					
Colloids	0.9%	0.001 mm																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>5.5</td><td>7.4%</td><td>0.0537 mm</td></tr> <tr><td>2</td><td>4.5</td><td>6.0%</td><td>0.0381 mm</td></tr> <tr><td>5</td><td>3.5</td><td>4.7%</td><td>0.0243 mm</td></tr> <tr><td>15</td><td>2.5</td><td>3.3%</td><td>0.0141 mm</td></tr> <tr><td>30</td><td>2</td><td>2.7%</td><td>0.0100 mm</td></tr> <tr><td>60</td><td>1.5</td><td>2.0%</td><td>0.0071 mm</td></tr> <tr><td>240</td><td>1</td><td>1.3%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.3%</td><td>0.0014 mm</td></tr> </tbody> </table>		Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	5.5	7.4%	0.0537 mm	2	4.5	6.0%	0.0381 mm	5	3.5	4.7%	0.0243 mm	15	2.5	3.3%	0.0141 mm	30	2	2.7%	0.0100 mm	60	1.5	2.0%	0.0071 mm	240	1	1.3%	0.0035 mm	1440	1	1.3%	0.0014 mm																																		
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																				
1	5.5	7.4%	0.0537 mm																																																																				
2	4.5	6.0%	0.0381 mm																																																																				
5	3.5	4.7%	0.0243 mm																																																																				
15	2.5	3.3%	0.0141 mm																																																																				
30	2	2.7%	0.0100 mm																																																																				
60	1.5	2.0%	0.0071 mm																																																																				
240	1	1.3%	0.0035 mm																																																																				
1440	1	1.3%	0.0014 mm																																																																				
% Gravel: 0.1% Liquid Limit: n/a % Sand: 82.0% Plastic Limit: n/a % Silt: 16.3% Plasticity Index: n/a % Clay: 1.6%																																																																							
USDA Soil Textural Classification																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																														
	Particle Size																																																																						
% Sand:	2.0 - 0.05 mm																																																																						
% Silt:	0.05 - 0.002 mm																																																																						
% Clay:	< 0.002 mm																																																																						
USDA Soil Textural Classification																																																																							
Sand																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____

Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT23-GB-21.1-22.8 ft Sample #: B21-1962	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: C. Kriss	Visual Identification Sandy Silt Sample Color brown																																																								
Liquid Limit Determination																																																										
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>#1</th> <th>#2</th> <th>#3</th> <th>#4</th> <th>#5</th> <th>#6</th> </tr> </thead> <tbody> <tr> <td>Weight of Wet Soils + Pan:</td> <td colspan="6" style="background-color: yellow;">Unable to determine</td> </tr> <tr> <td>Weight of Dry Soils + Pan:</td> <td colspan="6" style="background-color: yellow;">Unable to determine</td> </tr> <tr> <td>Weight of Pan:</td> <td colspan="6" style="background-color: yellow;">Unable to determine</td> </tr> <tr> <td>Weight of Dry Soils:</td> <td colspan="6" style="background-color: yellow;">Unable to determine</td> </tr> <tr> <td>Weight of Moisture:</td> <td colspan="6" style="background-color: yellow;">Unable to determine</td> </tr> <tr> <td>% Moisture:</td> <td colspan="6" style="background-color: yellow;">Unable to determine</td> </tr> <tr> <td>Number of Blows:</td> <td colspan="6" style="background-color: yellow;">Unable to determine</td> </tr> </tbody> </table>				#1	#2	#3	#4	#5	#6	Weight of Wet Soils + Pan:	Unable to determine						Weight of Dry Soils + Pan:	Unable to determine						Weight of Pan:	Unable to determine						Weight of Dry Soils:	Unable to determine						Weight of Moisture:	Unable to determine						% Moisture:	Unable to determine						Number of Blows:	Unable to determine					
	#1	#2	#3	#4	#5	#6																																																				
Weight of Wet Soils + Pan:	Unable to determine																																																									
Weight of Dry Soils + Pan:	Unable to determine																																																									
Weight of Pan:	Unable to determine																																																									
Weight of Dry Soils:	Unable to determine																																																									
Weight of Moisture:	Unable to determine																																																									
% Moisture:	Unable to determine																																																									
Number of Blows:	Unable to determine																																																									
Plastic Limit Determination																																																										
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>#1</th> <th>#2</th> <th>#3</th> <th>#4</th> <th>#5</th> <th>#6</th> </tr> </thead> <tbody> <tr> <td>Weight of Wet Soils + Pan:</td> <td colspan="6" style="background-color: yellow;">Unable to establish</td> </tr> <tr> <td>Weight of Dry Soils + Pan:</td> <td colspan="6" style="background-color: yellow;">Unable to establish</td> </tr> <tr> <td>Weight of Pan:</td> <td colspan="6" style="background-color: yellow;">Unable to establish</td> </tr> <tr> <td>Weight of Dry Soils:</td> <td colspan="6" style="background-color: yellow;">Unable to establish</td> </tr> <tr> <td>Weight of Moisture:</td> <td colspan="6" style="background-color: yellow;">Unable to establish</td> </tr> <tr> <td>% Moisture:</td> <td colspan="6" style="background-color: yellow;">Unable to establish</td> </tr> </tbody> </table>				#1	#2	#3	#4	#5	#6	Weight of Wet Soils + Pan:	Unable to establish						Weight of Dry Soils + Pan:	Unable to establish						Weight of Pan:	Unable to establish						Weight of Dry Soils:	Unable to establish						Weight of Moisture:	Unable to establish						% Moisture:	Unable to establish												
	#1	#2	#3	#4	#5	#6																																																				
Weight of Wet Soils + Pan:	Unable to establish																																																									
Weight of Dry Soils + Pan:	Unable to establish																																																									
Weight of Pan:	Unable to establish																																																									
Weight of Dry Soils:	Unable to establish																																																									
Weight of Moisture:	Unable to establish																																																									
% Moisture:	Unable to establish																																																									
Plasticity Chart																																																										
Liquid Limit																																																										

Liquid Limit @ 25 Blows: N/A
 Plastic Limit: N/A
 Plasticity Index, I_p: N/A



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be determined as the material displays rapid dilation. At lower moistures the sample does not spread into the cup without tearing the soil cake. Unable to establish plastic limit as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT23-GB-22.8-26.8 ft Sample#: B21-1963	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 4-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	
--	---	---	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.011 mm D ₍₁₀₎ = 0.053 mm D ₍₁₅₎ = 0.063 mm D ₍₃₀₎ = 0.090 mm D ₍₅₀₎ = 0.126 mm D ₍₆₀₎ = 0.143 mm D ₍₉₀₎ = 0.353 mm Dust Ratio = 7/32	% Gravel = 0.0% % Sand = 78.3% % Silt & Clay = 21.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.05 Coeff. of Uniformity, C _u = 2.69 Fineness Modulus = 0.54 Plastic Limit = n/a Moisture %, as sampled = 32.1% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850		99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		83%	100.0%	0.0%
#60	0.250		77%	100.0%	0.0%
#80	0.180		68%	100.0%	0.0%
#100	0.150	64%	64%	100.0%	0.0%
#140	0.106		39%	100.0%	0.0%
#170	0.090		30%	100.0%	0.0%
#200	0.075	21.7%	21.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo



Hydrometer Report

<p>Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client: Anchor QEA Date Tested: 4-Oct-21 Source: LDW21-GT23-GB-22.8-26.8 ft Tested By: K. Mendez Sample#: B21-1963</p>	<p>Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown</p>																																																																																																																																							
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																																																							
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Assumed Sp Gr :</td> <td style="width: 20%;">2.65</td> <td style="width: 50%;"></td> </tr> <tr> <td>Sample Weight:</td> <td>76.06</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td>1.08%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td>75.25</td> <td>grams</td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>7.5</td><td>10.0%</td><td>0.0532 mm</td></tr> <tr><td>2</td><td>6.5</td><td>8.6%</td><td>0.0378 mm</td></tr> <tr><td>5</td><td>5.5</td><td>7.3%</td><td>0.0240 mm</td></tr> <tr><td>15</td><td>4.5</td><td>6.0%</td><td>0.0139 mm</td></tr> <tr><td>30</td><td>3.5</td><td>4.6%</td><td>0.0099 mm</td></tr> <tr><td>60</td><td>2</td><td>2.7%</td><td>0.0070 mm</td></tr> <tr><td>240</td><td>1.5</td><td>2.0%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.3%</td><td>0.0014 mm</td></tr> </tbody> </table> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 20%;">0.0%</td> <td style="width: 50%;">Liquid Limit: n/a</td> </tr> <tr> <td>% Sand:</td> <td>78.3%</td> <td>Plastic Limit: n/a</td> </tr> <tr> <td>% Silt:</td> <td>19.5%</td> <td>Plasticity Index: n/a</td> </tr> <tr> <td>% Clay:</td> <td>2.3%</td> <td></td> </tr> </table>	Assumed Sp Gr :	2.65		Sample Weight:	76.06	grams	Hydroscopic Moist.:	1.08%		Adj. Sample Wgt :	75.25	grams	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	7.5	10.0%	0.0532 mm	2	6.5	8.6%	0.0378 mm	5	5.5	7.3%	0.0240 mm	15	4.5	6.0%	0.0139 mm	30	3.5	4.6%	0.0099 mm	60	2	2.7%	0.0070 mm	240	1.5	2.0%	0.0035 mm	1440	1	1.3%	0.0014 mm	% Gravel:	0.0%	Liquid Limit: n/a	% Sand:	78.3%	Plastic Limit: n/a	% Silt:	19.5%	Plasticity Index: n/a	% Clay:	2.3%		<table style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3" style="text-align: center;">Sieve Analysis</th> </tr> <tr> <th colspan="3" style="text-align: center;">Grain Size Distribution</th> </tr> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>64%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>21.7%</td><td>0.075 mm</td></tr> <tr><td style="text-align: center;">Silts</td><td>21.2%</td><td>0.074 mm</td></tr> <tr><td></td><td>9.8%</td><td>0.050 mm</td></tr> <tr><td></td><td>6.8%</td><td>0.020 mm</td></tr> <tr><td style="text-align: center;">Clays</td><td>2.3%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.5%</td><td>0.002 mm</td></tr> <tr><td style="text-align: center;">Colloids</td><td>0.9%</td><td>0.001 mm</td></tr> </table>	Sieve Analysis			Grain Size Distribution			Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	99%	0.425 mm	#100	64%	0.150 mm	#200	21.7%	0.075 mm	Silts	21.2%	0.074 mm		9.8%	0.050 mm		6.8%	0.020 mm	Clays	2.3%	0.005 mm		1.5%	0.002 mm	Colloids	0.9%	0.001 mm
Assumed Sp Gr :	2.65																																																																																																																																							
Sample Weight:	76.06	grams																																																																																																																																						
Hydroscopic Moist.:	1.08%																																																																																																																																							
Adj. Sample Wgt :	75.25	grams																																																																																																																																						
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																																					
1	7.5	10.0%	0.0532 mm																																																																																																																																					
2	6.5	8.6%	0.0378 mm																																																																																																																																					
5	5.5	7.3%	0.0240 mm																																																																																																																																					
15	4.5	6.0%	0.0139 mm																																																																																																																																					
30	3.5	4.6%	0.0099 mm																																																																																																																																					
60	2	2.7%	0.0070 mm																																																																																																																																					
240	1.5	2.0%	0.0035 mm																																																																																																																																					
1440	1	1.3%	0.0014 mm																																																																																																																																					
% Gravel:	0.0%	Liquid Limit: n/a																																																																																																																																						
% Sand:	78.3%	Plastic Limit: n/a																																																																																																																																						
% Silt:	19.5%	Plasticity Index: n/a																																																																																																																																						
% Clay:	2.3%																																																																																																																																							
Sieve Analysis																																																																																																																																								
Grain Size Distribution																																																																																																																																								
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																																						
3.0"	100%	75.000 mm																																																																																																																																						
2.0"	100%	50.000 mm																																																																																																																																						
1.5"	100%	37.500 mm																																																																																																																																						
1.25"	100%	31.500 mm																																																																																																																																						
1.0"	100%	25.000 mm																																																																																																																																						
3/4"	100%	19.000 mm																																																																																																																																						
5/8"	100%	16.000 mm																																																																																																																																						
1/2"	100%	12.500 mm																																																																																																																																						
3/8"	100%	9.500 mm																																																																																																																																						
1/4"	100%	6.300 mm																																																																																																																																						
#4	100%	4.750 mm																																																																																																																																						
#10	100%	2.000 mm																																																																																																																																						
#20	99%	0.850 mm																																																																																																																																						
#40	99%	0.425 mm																																																																																																																																						
#100	64%	0.150 mm																																																																																																																																						
#200	21.7%	0.075 mm																																																																																																																																						
Silts	21.2%	0.074 mm																																																																																																																																						
	9.8%	0.050 mm																																																																																																																																						
	6.8%	0.020 mm																																																																																																																																						
Clays	2.3%	0.005 mm																																																																																																																																						
	1.5%	0.002 mm																																																																																																																																						
Colloids	0.9%	0.001 mm																																																																																																																																						
USDA Soil Textural Classification																																																																																																																																								
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 70%; text-align: center;">Particle Size</td> </tr> <tr> <td>% Sand:</td> <td style="text-align: center;">2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td style="text-align: center;">0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td style="text-align: center;">< 0.002 mm</td> </tr> </table> <p style="text-align: center;">USDA Soil Textural Classification Sand</p>		Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																																																
	Particle Size																																																																																																																																							
% Sand:	2.0 - 0.05 mm																																																																																																																																							
% Silt:	0.05 - 0.002 mm																																																																																																																																							
% Clay:	< 0.002 mm																																																																																																																																							

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 19, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-2050-2069
Date sampled: 8-4-21 & 8-5-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

Test(s) Performed:	Test Results	Test(s) Performed:	Test Results
<input checked="" type="checkbox"/> Sieve Analysis	Please See Attached Reports	Sulfate Soundness	
<input type="checkbox"/> Proctor		Bulk Density & Voids	
<input type="checkbox"/> Sand Equivalent		WSDOT Degradation	
<input type="checkbox"/> Fracture Count		LA Abrasion	
<input checked="" type="checkbox"/> Moisture Content	Please See Attached Report	<input checked="" type="checkbox"/> Direct Shear	Please See Attached Reports
<input type="checkbox"/> Specific Gravity, Coarse		<input checked="" type="checkbox"/> Specific Gravity, Soils	Please See Attached Reports
<input type="checkbox"/> Specific Gravity, Fine			
<input checked="" type="checkbox"/> Hydrometer Analysis	Please See Attached Reports		
<input checked="" type="checkbox"/> Atterberg Limits	Please See Attached Reports		

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician




Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: October 8, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-2050	LDW21-GT44-GB-0-5 ft	341.8	1294.0	1086.4	207.6	744.6	27.9%
B21-2051	LDW21-GT44-GB-5-6.1 ft	354.2	977.3	871.3	106.0	517.1	20.5%
B21-2052	LDW21-GT44-GB-6.1-6.5 ft	359.6	665.7	593.5	72.2	233.9	30.9%
B21-2053	LDW21-GT44-GB-5-10 ft	357.1	1289.6	1063.4	226.2	706.3	32.0%
B21-2054	LDW21-GT44-GB-10-11.5 ft	360.2	1379.9	1209.6	170.3	849.4	20.0%
B21-2055	LDW21-GT44-GB-10-15 ft	346.4	1230.1	1027.5	202.6	681.1	29.7%
B21-2056	LDW21-GT44-GB-15.5-16.5 ft	225.1	974.7	803.8	170.9	578.7	29.5%
B21-2057	LDW21-GT44-GB-15-20 ft	266.4	1004.4	805.9	198.5	539.5	36.8%
B21-2058	LDW21-GT44-GB-20-21.5 ft	301.2	1328.5	1051.3	277.2	750.1	37.0%
B21-2059	LDW21-GT44-GB-20-25 ft	224.4	1222.2	950.5	271.7	726.1	37.4%
B21-2060	LDW21-GT44-GB-25-28.7 ft	270.1	1116.1	1011.0	105.1	740.9	14.2%
B21-2061	LDW21-GT44-GB-28.7-30 ft	182.4	916.9	718.4	198.5	536.0	37.0%
B21-2062	LDW21-GT44-GB-30-31.5 ft	220.5	1200.8	943.4	257.4	722.9	35.6%
B21-2063	LDW21-GT48-GB-0-5 ft	234.7	1032.0	887.3	144.7	652.6	22.2%
B21-2064	LDW21-GT48-GB-5-6.5 ft	221.5	1216.7	1036.8	179.9	815.3	22.1%
B21-2065	LDW21-GT48-GB-5-10 ft	233.9	698.1	566.7	131.4	332.8	39.5%
B21-2066	LDW21-GT48-GB-10-15 ft	233.2	798.5	665.7	132.8	432.5	30.7%
B21-2067	LDW21-GT48-GB-15-18.2 ft	224.4	960.1	827.8	132.3	603.4	21.9%
B21-2068	LDW21-GT48-GB-18.2-19.5 ft	221.9	948.5	777.2	171.3	555.3	30.8%
B21-2069	LDW21-GT48-GB-20-21.6 ft	306.7	947.8	795.3	152.5	488.6	31.2%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 
 Meghan Blodgett-Carrillo



Moisture Content - ASTM D854

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: September 20, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Dry Soil + Tare	Mass of Dry Soil	Pycno ID	Mass of Pycno	Volume of Pycno	Density of Water @ Tx	Mass of Pycno filled w/ water & soils	Mass of Pycno filled w/ water	Temp. of Water, 0.1 *C	SpG of Soils	Temp. Correction Factor	Corrected SpG
B21-2055	LDW21-GT44-GB-10-15 ft	497.91	595.93	98.0	TSA-017	187.9	499.4	0.99858	747.34	686.58	18.1	2.630647	1.00037	2.6316204
B21-2066	LDW21-GT48-GB-10-15 ft	510.08	607.93	97.9	TSA-011	190.3	499.5	0.99856	749.61	689.15	18.2	2.6169635	1.00035	2.6178795

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.


Reviewed by: *Meghan Blodgett-Carrillo*
Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT44-GB-0-5 ft Sample#: B21-2050	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SW-SC, Well-graded Sand with Silty Clay Sample Color: brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.039$ mm $D_{(10)} = 0.083$ mm $D_{(15)} = 0.170$ mm $D_{(30)} = 0.352$ mm $D_{(50)} = 0.593$ mm $D_{(60)} = 0.724$ mm $D_{(90)} = 1.967$ mm Dust Ratio = 9/35	% Gravel = 4.2% % Sand = 86.2% % Silt & Clay = 9.6% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 2.07$ Coeff. of Uniformity, $C_u = 8.74$ Fineness Modulus = 2.51 Plastic Limit = n/a Moisture %, as sampled = 27.9% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		99%	100.0%	0.0%
1.00"	25.00	99%	99%	100.0%	0.0%
3/4"	19.00	99%	99%	100.0%	0.0%
5/8"	16.00		99%	100.0%	0.0%
1/2"	12.50	98%	98%	100.0%	0.0%
3/8"	9.50	98%	98%	100.0%	0.0%
1/4"	6.30		96%	100.0%	0.0%
#4	4.75	96%	96%	100.0%	0.0%
#8	2.36		91%	100.0%	0.0%
#10	2.00	91%	91%	100.0%	0.0%
#16	1.18		76%	100.0%	0.0%
#20	0.850	70%	70%	100.0%	0.0%
#30	0.600		51%	100.0%	0.0%
#40	0.425	37%	37%	100.0%	0.0%
#50	0.300		25%	100.0%	0.0%
#60	0.250	20%	20%	100.0%	0.0%
#80	0.180		16%	100.0%	0.0%
#100	0.150	14%	14%	100.0%	0.0%
#140	0.106		11%	100.0%	0.0%
#170	0.090		10%	100.0%	0.0%
#200	0.075	9.6%	9.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-2050
 Sample Date: 8/4/2021
 Test Date: 10/13/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT44-GB-0-5 ft
 Visual Soil Description: brown silty sand with gravel
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	24.6	
	Initial	Post-Consolidation
Dry Density (PCF):	109.7	110.8
Void Ratio:	0.536	0.520
Porosity (%):	34.9	34.2
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	23.8	
	Initial	Post-Consolidation
Dry Density (PCF):	110.7	113.4
Void Ratio:	0.523	0.486
Porosity (%):	34.3	32.7
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	23.8	
	Initial	Post-Consolidation
Dry Density (PCF):	110.9	114.3
Void Ratio:	0.520	0.473
Porosity (%):	34.2	32.1
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	37	33
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	380	770	1500
Residual Horizontal Stress, τ_h (PSF):	300	710	1290



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787


Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT44-GB-5-10 ft Sample#: B21-2053	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: dark brown	 Certificate #: 1366.01
---	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.031 mm D ₍₁₀₎ = 0.062 mm D ₍₁₅₎ = 0.081 mm D ₍₃₀₎ = 0.112 mm D ₍₅₀₎ = 0.154 mm D ₍₆₀₎ = 0.178 mm D ₍₉₀₎ = 0.247 mm Dust Ratio = 9/74	% Gravel = 0.0% % Sand = 88.0% % Silt & Clay = 12.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.14 Coeff. of Uniformity, C _u = 2.85 Fineness Modulus = 0.59 Plastic Limit = n/a Moisture %, as sampled = 32.0% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	93%	93%	100.0%	0.0%
#60	0.250	91%	91%	100.0%	0.0%
#80	0.180	61%	61%	100.0%	0.0%
#100	0.150	48%	48%	100.0%	0.0%
#140	0.106	27%	27%	100.0%	0.0%
#170	0.090	19%	19%	100.0%	0.0%
#200	0.075	12.0%	12.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT44-GB-10-15 ft Sample#: B21-2055	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: dark brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.032 mm D ₍₁₀₎ = 0.064 mm D ₍₁₅₎ = 0.082 mm D ₍₃₀₎ = 0.116 mm D ₍₅₀₎ = 0.164 mm D ₍₆₀₎ = 0.192 mm D ₍₉₀₎ = 0.404 mm Dust Ratio = 11/85	% Gravel = 0.0% % Sand = 88.2% % Silt & Clay = 11.8% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.11 Coeff. of Uniformity, C _u = 3.02 Fineness Modulus = 0.77 Plastic Limit = n/a Moisture %, as sampled = 29.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600		95%	100.0%	0.0%
#40	0.425	91%	91%	100.0%	0.0%
#50	0.300		84%	100.0%	0.0%
#60	0.250	81%	81%	100.0%	0.0%
#80	0.180		56%	100.0%	0.0%
#100	0.150	45%	45%	100.0%	0.0%
#140	0.106		25%	100.0%	0.0%
#170	0.090		18%	100.0%	0.0%
#200	0.075	11.8%	11.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo



Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT44-GB-15-20 ft Sample#: B21-2057	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Visual Identification Sandy Silt Sample Color: dark brown
--	---	--



ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.006 mm	% Gravel = 0.6%	Coeff. of Curvature, C _c = 1.50
D ₍₁₀₎ = 0.012 mm	% Sand = 36.7%	Coeff. of Uniformity, C _u = 6.00
D ₍₁₅₎ = 0.018 mm	% Silt & Clay = 62.6%	Fineness Modulus = 0.29
D ₍₃₀₎ = 0.036 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.060 mm	Plasticity Index = n/a	Moisture %, as sampled = 36.8%
D ₍₆₀₎ = 0.072 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.216 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 43/67	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30	99%	99%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	99%	99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	99%	99%	100.0%	0.0%
#20	0.850	98%	98%	100.0%	0.0%
#30	0.600	98%	98%	100.0%	0.0%
#40	0.425	98%	98%	100.0%	0.0%
#50	0.300	95%	95%	100.0%	0.0%
#60	0.250	94%	94%	100.0%	0.0%
#80	0.180	85%	85%	100.0%	0.0%
#100	0.150	81%	81%	100.0%	0.0%
#140	0.106	70%	70%	100.0%	0.0%
#170	0.090	66%	66%	100.0%	0.0%
#200	0.075	62.6%	62.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by:
 Meghan Blodgett-Carrillo



Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT44-GB-20-25 ft Sample#: B21-2059	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Visual Identification Sandy Silt with Clay Sample Color: brown	ACCREDITED Certificate #: 1366.01
--	---	---	--------------------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? N/A

D ₍₅₎ = 0.001 mm	% Gravel = 0.0%	Coeff. of Curvature, C _c = 1.61
D ₍₁₀₎ = 0.003 mm	% Sand = 21.5%	Coeff. of Uniformity, C _u = 17.87
D ₍₁₅₎ = 0.005 mm	% Silt & Clay = 78.5%	Fineness Modulus = 0.40
D ₍₃₀₎ = 0.014 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.032 mm	Plasticity Index = n/a	Moisture %, as sampled = 37.4%
D ₍₆₀₎ = 0.048 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.190 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 17/20	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		94%	100.0%	0.0%
#10	2.00	93%	93%	100.0%	0.0%
#16	1.18		93%	100.0%	0.0%
#20	0.850		93%	100.0%	0.0%
#30	0.600		93%	100.0%	0.0%
#40	0.425	92%	92%	100.0%	0.0%
#50	0.300		91%	100.0%	0.0%
#60	0.250		91%	100.0%	0.0%
#80	0.180		90%	100.0%	0.0%
#100	0.150	90%	90%	100.0%	0.0%
#140	0.106		83%	100.0%	0.0%
#170	0.090		81%	100.0%	0.0%
#200	0.075	78.5%	78.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client: Anchor QEA Date Tested: 8-Oct-21 Source: LDW21-GT44-GB-20-25 ft Tested By: A. Eifrig Sample#: B21-2059	Visual Identification Sandy Silt with Clay Sample Color brown																																																																																																																																	
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																																																	
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Assumed Sp Gr :</td> <td style="width: 20%;">2.65</td> <td style="width: 50%;"></td> </tr> <tr> <td>Sample Weight:</td> <td>75.15</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td>3.83%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td>72.38</td> <td>grams</td> </tr> </table> <div style="text-align: center; margin-top: 10px;"> </div> <table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>43</td><td>55.4%</td><td>0.0414 mm</td></tr> <tr><td>2</td><td>38</td><td>49.0%</td><td>0.0307 mm</td></tr> <tr><td>5</td><td>31</td><td>40.0%</td><td>0.0204 mm</td></tr> <tr><td>15</td><td>21</td><td>27.1%</td><td>0.0127 mm</td></tr> <tr><td>30</td><td>18</td><td>23.2%</td><td>0.0091 mm</td></tr> <tr><td>60</td><td>15</td><td>19.3%</td><td>0.0065 mm</td></tr> <tr><td>240</td><td>9</td><td>11.6%</td><td>0.0034 mm</td></tr> <tr><td>1440</td><td>5.5</td><td>7.1%</td><td>0.0014 mm</td></tr> </tbody> </table> <table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 20%;">0.0%</td> <td style="width: 50%;">Liquid Limit: n/a</td> </tr> <tr> <td>% Sand:</td> <td>21.5%</td> <td>Plastic Limit: n/a</td> </tr> <tr> <td>% Silt:</td> <td>63.0%</td> <td>Plasticity Index: n/a</td> </tr> <tr> <td>% Clay:</td> <td>15.5%</td> <td></td> </tr> </table>	Assumed Sp Gr :	2.65		Sample Weight:	75.15	grams	Hydroscopic Moist.:	3.83%		Adj. Sample Wgt :	72.38	grams	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	43	55.4%	0.0414 mm	2	38	49.0%	0.0307 mm	5	31	40.0%	0.0204 mm	15	21	27.1%	0.0127 mm	30	18	23.2%	0.0091 mm	60	15	19.3%	0.0065 mm	240	9	11.6%	0.0034 mm	1440	5.5	7.1%	0.0014 mm	% Gravel:	0.0%	Liquid Limit: n/a	% Sand:	21.5%	Plastic Limit: n/a	% Silt:	63.0%	Plasticity Index: n/a	% Clay:	15.5%		<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>93%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>93%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>92%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>90%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>78.5%</td><td>0.075 mm</td></tr> <tr><td style="padding-left: 20px;">Silts</td><td>77.8%</td><td>0.074 mm</td></tr> <tr><td></td><td>65.5%</td><td>0.050 mm</td></tr> <tr><td></td><td>39.3%</td><td>0.020 mm</td></tr> <tr><td style="padding-left: 20px;">Clays</td><td>15.5%</td><td>0.005 mm</td></tr> <tr><td></td><td>8.4%</td><td>0.002 mm</td></tr> <tr><td style="padding-left: 20px;">Colloids</td><td>5.0%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	93%	2.000 mm	#20	93%	0.850 mm	#40	92%	0.425 mm	#100	90%	0.150 mm	#200	78.5%	0.075 mm	Silts	77.8%	0.074 mm		65.5%	0.050 mm		39.3%	0.020 mm	Clays	15.5%	0.005 mm		8.4%	0.002 mm	Colloids	5.0%	0.001 mm
Assumed Sp Gr :	2.65																																																																																																																																	
Sample Weight:	75.15	grams																																																																																																																																
Hydroscopic Moist.:	3.83%																																																																																																																																	
Adj. Sample Wgt :	72.38	grams																																																																																																																																
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																															
1	43	55.4%	0.0414 mm																																																																																																																															
2	38	49.0%	0.0307 mm																																																																																																																															
5	31	40.0%	0.0204 mm																																																																																																																															
15	21	27.1%	0.0127 mm																																																																																																																															
30	18	23.2%	0.0091 mm																																																																																																																															
60	15	19.3%	0.0065 mm																																																																																																																															
240	9	11.6%	0.0034 mm																																																																																																																															
1440	5.5	7.1%	0.0014 mm																																																																																																																															
% Gravel:	0.0%	Liquid Limit: n/a																																																																																																																																
% Sand:	21.5%	Plastic Limit: n/a																																																																																																																																
% Silt:	63.0%	Plasticity Index: n/a																																																																																																																																
% Clay:	15.5%																																																																																																																																	
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																																
3.0"	100%	75.000 mm																																																																																																																																
2.0"	100%	50.000 mm																																																																																																																																
1.5"	100%	37.500 mm																																																																																																																																
1.25"	100%	31.500 mm																																																																																																																																
1.0"	100%	25.000 mm																																																																																																																																
3/4"	100%	19.000 mm																																																																																																																																
5/8"	100%	16.000 mm																																																																																																																																
1/2"	100%	12.500 mm																																																																																																																																
3/8"	100%	9.500 mm																																																																																																																																
1/4"	100%	6.300 mm																																																																																																																																
#4	100%	4.750 mm																																																																																																																																
#10	93%	2.000 mm																																																																																																																																
#20	93%	0.850 mm																																																																																																																																
#40	92%	0.425 mm																																																																																																																																
#100	90%	0.150 mm																																																																																																																																
#200	78.5%	0.075 mm																																																																																																																																
Silts	77.8%	0.074 mm																																																																																																																																
	65.5%	0.050 mm																																																																																																																																
	39.3%	0.020 mm																																																																																																																																
Clays	15.5%	0.005 mm																																																																																																																																
	8.4%	0.002 mm																																																																																																																																
Colloids	5.0%	0.001 mm																																																																																																																																
USDA Soil Textural Classification																																																																																																																																		
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 70%;">Particle Size</td> </tr> <tr> <td>% Sand:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </table> <p style="text-align: center; margin-top: 10px;"> USDA Soil Textural Classification Silt Loam </p>		Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																																										
	Particle Size																																																																																																																																	
% Sand:	2.0 - 0.05 mm																																																																																																																																	
% Silt:	0.05 - 0.002 mm																																																																																																																																	
% Clay:	< 0.002 mm																																																																																																																																	

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____

Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT44-GB-25-28.7 ft Sample#: B21-2060	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.370 mm D ₍₁₀₎ = 0.495 mm D ₍₁₅₎ = 0.577 mm D ₍₃₀₎ = 0.822 mm D ₍₅₀₎ = 1.264 mm D ₍₆₀₎ = 1.490 mm D ₍₉₀₎ = 14.510 mm Dust Ratio = 6/23	% Gravel = 11.1% % Sand = 87.4% % Silt & Clay = 1.5% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.92 Coeff. of Uniformity, C _u = 3.01 Fineness Modulus = 3.78 Plastic Limit = n/a Moisture %, as sampled = 14.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		98%	100.0%	0.0%
1.50"	37.50		95%	100.0%	0.0%
1.25"	31.50		93%	100.0%	0.0%
1.00"	25.00	91%	91%	100.0%	0.0%
3/4"	19.00	91%	91%	100.0%	0.0%
5/8"	16.00		90%	100.0%	0.0%
1/2"	12.50	90%	90%	100.0%	0.0%
3/8"	9.50	90%	90%	100.0%	0.0%
1/4"	6.30		89%	100.0%	0.0%
#4	4.75	89%	89%	100.0%	0.0%
#8	2.36		83%	100.0%	0.0%
#10	2.00	83%	83%	100.0%	0.0%
#16	1.18		46%	100.0%	0.0%
#20	0.850	32%	32%	100.0%	0.0%
#30	0.600		16%	100.0%	0.0%
#40	0.425	6%	6%	100.0%	0.0%
#50	0.300		4%	100.0%	0.0%
#60	0.250	3%	3%	100.0%	0.0%
#80	0.180		3%	100.0%	0.0%
#100	0.150	3%	3%	100.0%	0.0%
#140	0.106		2%	100.0%	0.0%
#170	0.090		2%	100.0%	0.0%
#200	0.075	1.5%	1.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT44-GB-28.7-30 ft Sample#: B21-2061	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Visual Identification Sandy Silt Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.005 mm	% Gravel = 3.2%	Coeff. of Curvature, C _c = 1.50
D ₍₁₀₎ = 0.009 mm	% Sand = 17.6%	Coeff. of Uniformity, C _u = 6.00
D ₍₁₅₎ = 0.014 mm	% Silt & Clay = 79.2%	Fineness Modulus = 0.41
D ₍₃₀₎ = 0.028 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.047 mm	Plasticity Index = n/a	Moisture %, as sampled = 37.0%
D ₍₆₀₎ = 0.057 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.144 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 51/59	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		99%	100.0%	0.0%
1/2"	12.50	98%	98%	100.0%	0.0%
3/8"	9.50	98%	98%	100.0%	0.0%
1/4"	6.30		97%	100.0%	0.0%
#4	4.75	97%	97%	100.0%	0.0%
#8	2.36		96%	100.0%	0.0%
#10	2.00	95%	95%	100.0%	0.0%
#16	1.18		94%	100.0%	0.0%
#20	0.850	93%	93%	100.0%	0.0%
#30	0.600		92%	100.0%	0.0%
#40	0.425	92%	92%	100.0%	0.0%
#50	0.300		91%	100.0%	0.0%
#60	0.250	91%	91%	100.0%	0.0%
#80	0.180		91%	100.0%	0.0%
#100	0.150	91%	91%	100.0%	0.0%
#140	0.106		84%	100.0%	0.0%
#170	0.090		82%	100.0%	0.0%
#200	0.075	79.2%	79.2%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by:
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-2065
 Sample Date: 8/5/2021
 Test Date: 10/15/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT48-GB-5-10 ft
 Visual Soil Description: brown silty sand with gravel
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	37.5	
	Initial	Post-Consolidation
Dry Density (PCF):	-4530.4	-4603.6
Void Ratio:	-1.037	-1.037
Porosity (%):	2789.0	2832.4
Degree of Saturation (%):	-97.6	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	34.3	
	Initial	Post-Consolidation
Dry Density (PCF):	100.8	104.7
Void Ratio:	0.672	0.610
Porosity (%):	40.2	37.9
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	35.3	
	Initial	Post-Consolidation
Dry Density (PCF):	100.6	106.4
Void Ratio:	0.675	0.584
Porosity (%):	40.3	36.9
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	37	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	380	810	1510
Residual Horizontal Stress, τ_h (PSF):	230	700	1210



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-0-5 ft Sample#: B21-2063	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.123 mm D ₍₁₀₎ = 0.234 mm D ₍₁₅₎ = 0.337 mm D ₍₃₀₎ = 0.655 mm D ₍₅₀₎ = 1.086 mm D ₍₆₀₎ = 1.301 mm D ₍₉₀₎ = 1.947 mm Dust Ratio = 7/39	% Gravel = 0.0% % Sand = 96.5% % Silt & Clay = 3.5% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.41 Coeff. of Uniformity, C _u = 5.55 Fineness Modulus = 3.06 Plastic Limit = n/a Moisture %, as sampled = 22.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		93%	100.0%	0.0%
#10	2.00	92%	92%	100.0%	0.0%
#16	1.18		54%	100.0%	0.0%
#20	0.850		39%	100.0%	0.0%
#30	0.600		27%	100.0%	0.0%
#40	0.425	19%	19%	100.0%	0.0%
#50	0.300		13%	100.0%	0.0%
#60	0.250		11%	100.0%	0.0%
#80	0.180		7%	100.0%	0.0%
#100	0.150	6%	6%	100.0%	0.0%
#140	0.106		4%	100.0%	0.0%
#170	0.090		4%	100.0%	0.0%
#200	0.075	3.5%	3.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-5-10 ft Sample#: B21-2065	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
---	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.026 mm D ₍₁₀₎ = 0.051 mm D ₍₁₅₎ = 0.076 mm D ₍₃₀₎ = 0.102 mm D ₍₅₀₎ = 0.137 mm D ₍₆₀₎ = 0.171 mm D ₍₉₀₎ = 0.386 mm Dust Ratio = 15/98	% Gravel = 0.7% % Sand = 84.7% % Silt & Clay = 14.6% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.19 Coeff. of Uniformity, C _u = 3.32 Fineness Modulus = 0.75 Plastic Limit = n/a Moisture %, as sampled = 39.5% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30	99%	99%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	99%	99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	97%	97%	100.0%	0.0%
#20	0.850	96%	96%	100.0%	0.0%
#30	0.600	96%	96%	100.0%	0.0%
#40	0.425	95%	95%	100.0%	0.0%
#50	0.300	78%	78%	100.0%	0.0%
#60	0.250	71%	71%	100.0%	0.0%
#80	0.180	61%	61%	100.0%	0.0%
#100	0.150	57%	57%	100.0%	0.0%
#140	0.106	32%	32%	100.0%	0.0%
#170	0.090	23%	23%	100.0%	0.0%
#200	0.075	14.6%	14.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-10-15 ft Sample#: B21-2066	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color: dark brown	 Certificate #: 1366.01
--	---	---	----------------------------

Specifications No Specs <p style="text-align: center;">Sample Meets Specs ? N/A</p>	ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281 D ₍₅₎ = 0.009 mm % Gravel = 0.1% D ₍₁₀₎ = 0.056 mm % Sand = 83.7% D ₍₁₅₎ = 0.071 mm % Silt & Clay = 16.2% D ₍₃₀₎ = 0.102 mm Liquid Limit = n/a D ₍₅₀₎ = 0.141 mm Plasticity Index = n/a D ₍₆₀₎ = 0.183 mm Sand Equivalent = n/a D ₍₉₀₎ = 0.369 mm Fracture %, 1 Face = n/a Dust Ratio = 8/49 Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.02 Coeff. of Uniformity, C _u = 3.29 Fineness Modulus = 0.68 Plastic Limit = n/a Moisture %, as sampled = 30.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =
---	--	--

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	99%	100.0%	0.0%
#20	0.850		99%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		79%	100.0%	0.0%
#60	0.250		71%	100.0%	0.0%
#80	0.180		60%	100.0%	0.0%
#100	0.150	55%	55%	100.0%	0.0%
#140	0.106		32%	100.0%	0.0%
#170	0.090		24%	100.0%	0.0%
#200	0.075	16.2%	16.2%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo



Hydrometer Report

<p>Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client: Anchor QEA Date Tested: 8-Oct-21 Source: LDW21-GT48-GB-10-15 ft Tested By: A. Eifrig Sample#: B21-2066</p>	<p>Unified Soils Classification System, ASTM D-2487 SM, Silty Sand Sample Color dark brown</p>																																																																																																									
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																									
<p>Sp Gr : 2.62 Sample Weight: 100.83 grams Hydroscopic Moist.: 3.02% Adj. Sample Wgt : 97.87 grams</p> <div style="text-align: center;">  Certificate #: 1366.01 </div> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>9</td><td>9.3%</td><td>0.0533 mm</td></tr> <tr><td>2</td><td>8</td><td>8.2%</td><td>0.0380 mm</td></tr> <tr><td>5</td><td>7</td><td>7.2%</td><td>0.0242 mm</td></tr> <tr><td>15</td><td>6.5</td><td>6.7%</td><td>0.0140 mm</td></tr> <tr><td>30</td><td>5.5</td><td>5.7%</td><td>0.0100 mm</td></tr> <tr><td>60</td><td>4</td><td>4.1%</td><td>0.0071 mm</td></tr> <tr><td>240</td><td>2</td><td>2.1%</td><td>0.0036 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.0%</td><td>0.0015 mm</td></tr> </tbody> </table> <p>% Gravel: 0.1% Liquid Limit: n/a % Sand: 83.7% Plastic Limit: n/a % Silt: 13.3% Plasticity Index: n/a % Clay: 2.9%</p>	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	9	9.3%	0.0533 mm	2	8	8.2%	0.0380 mm	5	7	7.2%	0.0242 mm	15	6.5	6.7%	0.0140 mm	30	5.5	5.7%	0.0100 mm	60	4	4.1%	0.0071 mm	240	2	2.1%	0.0036 mm	1440	1	1.0%	0.0015 mm	<p style="text-align: center;">Sieve Analysis Grain Size Distribution</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>99%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>55%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>16.2%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>15.9%</td><td>0.074 mm</td></tr> <tr><td></td><td>9.1%</td><td>0.050 mm</td></tr> <tr><td></td><td>7.0%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>2.9%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.3%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.7%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	99%	0.425 mm	#100	55%	0.150 mm	#200	16.2%	0.075 mm	Silts	15.9%	0.074 mm		9.1%	0.050 mm		7.0%	0.020 mm	Clays	2.9%	0.005 mm		1.3%	0.002 mm	Colloids	0.7%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																							
1	9	9.3%	0.0533 mm																																																																																																							
2	8	8.2%	0.0380 mm																																																																																																							
5	7	7.2%	0.0242 mm																																																																																																							
15	6.5	6.7%	0.0140 mm																																																																																																							
30	5.5	5.7%	0.0100 mm																																																																																																							
60	4	4.1%	0.0071 mm																																																																																																							
240	2	2.1%	0.0036 mm																																																																																																							
1440	1	1.0%	0.0015 mm																																																																																																							
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																								
3.0"	100%	75.000 mm																																																																																																								
2.0"	100%	50.000 mm																																																																																																								
1.5"	100%	37.500 mm																																																																																																								
1.25"	100%	31.500 mm																																																																																																								
1.0"	100%	25.000 mm																																																																																																								
3/4"	100%	19.000 mm																																																																																																								
5/8"	100%	16.000 mm																																																																																																								
1/2"	100%	12.500 mm																																																																																																								
3/8"	100%	9.500 mm																																																																																																								
1/4"	100%	6.300 mm																																																																																																								
#4	100%	4.750 mm																																																																																																								
#10	100%	2.000 mm																																																																																																								
#20	99%	0.850 mm																																																																																																								
#40	99%	0.425 mm																																																																																																								
#100	55%	0.150 mm																																																																																																								
#200	16.2%	0.075 mm																																																																																																								
Silts	15.9%	0.074 mm																																																																																																								
	9.1%	0.050 mm																																																																																																								
	7.0%	0.020 mm																																																																																																								
Clays	2.9%	0.005 mm																																																																																																								
	1.3%	0.002 mm																																																																																																								
Colloids	0.7%	0.001 mm																																																																																																								
USDA Soil Textural Classification																																																																																																										
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">% Sand:</td> <td>2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> </tr> </table> <p style="text-align: center;">USDA Soil Textural Classification Sand</p>	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																				
% Sand:	2.0 - 0.05 mm																																																																																																									
% Silt:	0.05 - 0.002 mm																																																																																																									
% Clay:	< 0.002 mm																																																																																																									

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 

Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-15-18.2 ft Sample#: B21-2067	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SP-SM, Poorly graded Sand with Silt Sample Color: dark brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.070 mm D ₍₁₀₎ = 0.104 mm D ₍₁₅₎ = 0.134 mm D ₍₃₀₎ = 0.194 mm D ₍₅₀₎ = 0.288 mm D ₍₆₀₎ = 0.377 mm D ₍₉₀₎ = 1.510 mm Dust Ratio = 4/49	% Gravel = 0.2% % Sand = 94.4% % Silt & Clay = 5.3% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.97 Coeff. of Uniformity, C _u = 3.64 Fineness Modulus = 1.77 Plastic Limit = n/a Moisture %, as sampled = 21.9% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		98%	100.0%	0.0%
#10	2.00	98%	98%	100.0%	0.0%
#16	1.18	80%	85%	100.0%	0.0%
#20	0.850	80%	80%	100.0%	0.0%
#30	0.600		71%	100.0%	0.0%
#40	0.425	65%	65%	100.0%	0.0%
#50	0.300		51%	100.0%	0.0%
#60	0.250	46%	46%	100.0%	0.0%
#80	0.180		26%	100.0%	0.0%
#100	0.150	18%	18%	100.0%	0.0%
#140	0.106		10%	100.0%	0.0%
#170	0.090		8%	100.0%	0.0%
#200	0.075	5.3%	5.3%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-18.2-19.5 ft Sample#: B21-2068	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Visual Identification Sandy Silt Sample Color: brown	 Certificate #: 1366.01
--	---	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.006 mm D ₍₁₀₎ = 0.011 mm D ₍₁₅₎ = 0.017 mm D ₍₃₀₎ = 0.033 mm D ₍₅₀₎ = 0.055 mm D ₍₆₀₎ = 0.066 mm D ₍₉₀₎ = 0.242 mm Dust Ratio = 37/51	% Gravel = 2.0% % Sand = 30.2% % Silt & Clay = 67.9% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.50 Coeff. of Uniformity, C _u = 6.00 Fineness Modulus = 0.42 Plastic Limit = n/a Moisture %, as sampled = 30.8% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30		98%	100.0%	0.0%
#4	4.75	98%	98%	100.0%	0.0%
#8	2.36		97%	100.0%	0.0%
#10	2.00	97%	97%	100.0%	0.0%
#16	1.18		96%	100.0%	0.0%
#20	0.850	95%	95%	100.0%	0.0%
#30	0.600		94%	100.0%	0.0%
#40	0.425	94%	94%	100.0%	0.0%
#50	0.300		91%	100.0%	0.0%
#60	0.250	91%	91%	100.0%	0.0%
#80	0.180		85%	100.0%	0.0%
#100	0.150	82%	82%	100.0%	0.0%
#140	0.106		74%	100.0%	0.0%
#170	0.090		71%	100.0%	0.0%
#200	0.075	67.9%	67.9%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-20-21.6 ft Sample#: B21-2069	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 8-Oct-21 Tested By: A. Eifrig	Unified Soils Classification System, ASTM D-2487 SP-SM, Poorly graded Sand with Silt Sample Color: dark brown	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.057 mm D ₍₁₀₎ = 0.087 mm D ₍₁₅₎ = 0.104 mm D ₍₃₀₎ = 0.153 mm D ₍₅₀₎ = 0.190 mm D ₍₆₀₎ = 0.208 mm D ₍₉₀₎ = 0.329 mm Dust Ratio = 6/91	% Gravel = 0.0% % Sand = 93.5% % Silt & Clay = 6.5% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.29 Coeff. of Uniformity, C _u = 2.40 Fineness Modulus = 0.85 Plastic Limit = n/a Moisture %, as sampled = 31.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	87%	87%	100.0%	0.0%
#60	0.250	83%	83%	100.0%	0.0%
#80	0.180	45%	45%	100.0%	0.0%
#100	0.150	28%	28%	100.0%	0.0%
#140	0.106	16%	16%	100.0%	0.0%
#170	0.090	11%	11%	100.0%	0.0%
#200	0.075	6.5%	6.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo



October 19, 2021
HWA Project No. 2012-002-23 Task 51

Materials Testing & Consulting, Inc.

777 Chrysler Drive
Burlington, WA 98233

Attention: Ms. Meghan Blodgett-Carrillo

Subject: **LABORATORY TESTING REPORT
QC - Lower Duwamish Waterway
MTC Project Number: 21B233**

Dear Ms. Blodgett-Carrillo;

In accordance with your request, HWA GeoSciences Inc. (HWA) performed laboratory testing for the above referenced project. Herein we present the results of our laboratory analyses, which are summarized on the attached Figures. The laboratory testing program was performed in general accordance with your instructions and appropriate ASTM Standards as outlined below.

SAMPLE DESCRIPTION: The subject samples were delivered to our laboratory on August 26, 2021 by MTC personnel. The samples were delivered in four Shelby tubes and were designated with exploration ID and depth of sampling. The soil samples were classified using visual-manual methods. The descriptions may be found on the attached Summary of Material Properties, Figure 1.

MOISTURE CONTENT OF SOIL: The moisture contents of the soil samples (percent by dry mass) were determined in general accordance with ASTM D2216. The results are shown on Figure 1.

SPECIFIC GRAVITY OF SOILS: The specific gravity of the selected samples was determined using method ASTM D854. The test results are shown on the attached Summary of Material Properties, Figure 1.

LIQUID LIMIT, PLASTIC LIMIT, AND PLASTICITY INDEX OF SOILS (ATTERBERG LIMITS): The plasticity index of each specified sample was tested using method ASTM D4318, multi-point method. The results are reported on the attached Liquid Limit, Plastic Limit, and Plasticity Index of Soils Report, Figure 2.

CONSOLIDATED UNDRAINED TRIAXIAL COMPRESSION OF SOILS: Selected samples were tested in general accordance with method ASTM D4767 to determine the shear strength characteristics of the soil. The samples were extruded from Shelby tubes, and the test specimens were trimmed to obtain a cylindrical test sample with a length to diameter ratio between 2:1 and 2.5:1. The specimens were carefully weighed and measured prior to testing.

Three trials were run at varying confining stresses specified by the client. Each sample was run using a single specimen to perform a multi-stage shear test.

The multi-stage method was performed by first consolidating the sample at the lowest specified confining pressure. The sample was then sheared until the change in pore pressure was at or near its estimated peak. After reaching the peak change in pore pressure, the shear phase was terminated, and the specimen was reconsolidated at the middle consolidation pressure. Under the second consolidation pressure the sample was again sheared until the change in pore pressure was at or near its estimated peak, at which point the shear was terminated. The sample was reconsolidated a third and final time under the highest confining pressure and shearing was performed to sample failure, concluding the test.

For sample LDW21-GT33-GB at 6.0-8.0', the test was terminated at 20.5% strain due to a spike in pore pressure caused by a perforation in the membrane encasing the sample. As a result, the final moisture content of the sample was affected due to the ingress of water from the surrounding water filled pressure cell. The final moisture content for this sample was determined to be 70.7%.

The Consolidated Undrained test results are summarized and plotted graphically in Figures 3-6.

ONE DIMENSIONAL CONSOLIDATION PROPERTIES OF SOIL: The consolidation properties of selected soil samples were measured in general accordance with ASTM D 2435. Saturation was maintained by inundation of the sample throughout the test. The samples were subjected to increasing increments of total stress, the duration of which was selected to exceed the time required for completion of primary consolidation as defined in the Standard, Method B. Unloading of the sample was carried out incrementally. The primary compression test results are presented on the attached Consolidation Test Reports, Figures 7-10.



CLOSURE: Experience has shown that test values on soil and other natural materials vary with each representative sample. As such, HWA has no knowledge as to the extent and quantity of material the tested samples may represent. HWA also makes no warranty as to how representative either the samples tested or the test results obtained are to actual field conditions. It is a well-established fact that sampling methods present varying degrees of disturbance that affect sample representativeness.

No copy should be made of this report except in its entirety.

We appreciate the opportunity to provide laboratory testing services on this project. Should you have any questions or comments, or if we may be of further service, please call.

Sincerely,

HWA GEOSCIENCES INC.

Greg Barker
Materials Laboratory Supervisor

Steven E. Greene, L.G., L.E.G.
Principal Engineering Geologist
Vice President

Attachments:

Figure 1
Figure 2
Figures 3-6
Figures 7-10

Summary of Material Properties
Liquid Limit, Plastic Limit and Plasticity Index of Soils
Consolidated Undrained Triaxial Compression Test for Cohesive Soils
Consolidation Test Report

EXPLORATION DESIGNATION	TOP DEPTH (feet)	BOTTOM DEPTH (feet)	MOISTURE CONTENT (%)	ORGANIC CONTENT (%)	SPECIFIC GRAVITY	ATTERBERG LIMITS (%)			% GRAVEL	% SAND	% FINES	ASTM SOIL CLASSIFICATION	SAMPLE DESCRIPTION
						LL	PL	PI					
LDW21-GT23-GB,	28.5	30.5	33.3		2.617	26	25	1				SM	Dark grayish-brown, silty SAND
LDW21-GT33-GB,	6.0	8.0	58.6		2.612	38	36	2				ML	Very dark grayish-brown, SILT with sand
LDW21-GT33-GB,	21.0	23.0	35.3		2.643	31	29	2				SM	Very dark grayish-brown, silty SAND
LDW21-GT53-SPT,	30.0	32.0	43.6		2.627	38	27	11				ML	Very dark grayish-brown, SILT with sand

Notes: 1. This table summarizes information presented elsewhere in the report and should be used in conjunction with the report test, other graphs and tables, and the exploration logs.
2. The soil classifications in this table are based on ASTM D2487 and D2488 as applicable.




MLT for MTC, Inc.
QC - Lower Duwamish Waterway
Client Project No.: 21B233

SUMMARY OF MATERIAL PROPERTIES

PAGE: 1 of 1

PROJECT NO.: 2012-002 T51 FIGURE: 1



SYMBOL	SAMPLE	DEPTH (ft)	CLASSIFICATION	% MC	LL	PL	PI	% Fines
●	LDW21-GT23-GB	28.5 - 30.5	(SM) Dark grayish-brown, silty SAND	33	26	25	1	
■	LDW21-GT33-GB	6.0 - 8.0	(ML) Very dark grayish-brown, SILT with sand	59	38	36	2	
▲	LDW21-GT33-GB	21.0 - 23.0	(SM) Very dark grayish-brown, silty SAND	35	31	29	2	
○	LDW21-GT53-SPT	30.0 - 32.0	(ML) Very dark grayish-brown, SILT with sand	44	38	27	11	



MLT for MTC, Inc.
 QC - Lower Duwamish Waterway
 Client Project No.: 21B233

LIQUID LIMIT, PLASTIC LIMIT AND
 PLASTICITY INDEX OF SOILS
 METHOD ASTM D4318




PROJECT NO.: 2012-002 T51 FIGURE: 2

HWA GeoSciences Inc - Materials Testing Laboratory

Consolidated-Undrained Triaxial Compression Test for Cohesive Soils (ASTM D 4767)

Project Name:	Lower Duwamish Waterway		Date:	8/27/2021		
Project No.:	2012-002-23 T51	Exploration ID:	LDW21-GT23-GB			
Technician:	DW	Sample No.:	n/a			
Sample Description:	Dark grayish-brown, silty SAND (SM)			Sample Depth, ft:	28.5-30.5'	
Confining Pressures:	10 psi	20 psi	40 psi	Consolidation T50 Values (minutes)		
Initial Moisture:	33.4%	Final Moisture:	32.4%	10 psi	20 psi	40 psi
Initial Wet Density, pcf:	115.2				0.6	0.6
Initial Dry Density, pcf:	86.3				0.6	1.0

Deviator Stress, Excess Pore Pressure and Effective Stress Ratio



Reviewed by: _____ SEG _____



Figure _____ 3 _____

HWA GeoSciences Inc - Materials Testing Laboratory

Consolidated-Undrained Triaxial Compression Test for Cohesive Soils (ASTM D 4767)

Project Name:	Lower Duwamish Waterway		Date:	8/28/2021		
Project No.:	2012-002-23 T51	Exploration ID:	LDW21-GT33-GB			
Technician:	GB	Sample No:	n/a			
Sample Description:	Very dark grayish-brown, SILT with sand (ML)		Sample Depth, ft:	6.0 - 8.0		
Confining Pressures:	2.5 psi	5.0 psi	10.0 psi	Consolidation T50 Values (minutes)		
Initial Moisture:	64.8%	Final Moisture:	see report	2.5 psi	5.0 psi	10.0 psi
Initial Wet Density, pcf:	93.4			91.13	83.21	162.0
Initial Dry Density, pcf:	56.7					

Deviator Stress, Excess Pore Pressure and Effective Stress Ratio



Reviewed by: _____ SEG




Figure _____ 4

HWA GeoSciences Inc - Materials Testing Laboratory

Consolidated-Undrained Triaxial Compression Test for Cohesive Soils (ASTM D 4767)

Project Name:	Lower Duwamish Waterway		Date:	9/7/2021		
Project No.:	2012-002-23 T51	Exploration ID:	LDW21-GT33-GB			
Technician:	GB		Sample No:	n/a		
Sample Description:	Very dark grayish-brown, silty SAND (SM)		Sample Depth, ft:	21.0-23.0		
Confining Pressures:	7 psi	14 psi	28 psi	Consolidation T50 Values (minutes)		
Initial Moisture:	35.3%	Final Moisture:	34.7%	7 psi	14 psi	28 psi
Initial Wet Density, pcf:	109.6			144.5	23.8	0.3
Initial Dry Density, pcf:	81.0					

Deviator Stress, Excess Pore Pressure and Effective Stress Ratio



Reviewed by: _____ SEG _____




Figure _____ 5 _____

HWA GeoSciences Inc - Materials Testing Laboratory

Consolidated-Undrained Triaxial Compression Test for Cohesive Soils (ASTM D 4767)

Project Name:	Lower Duwamish Waterway		Date:	9/16/2021		
Project No.:	2012-002-23 T51	Exploration ID:	LDW21-GT53-SPT			
Technician:	GB		Sample No:	n/a		
Sample Description:	Very dark grayish-brown, SILT with sand (ML)		Sample Depth, ft:	30.0-32.0		
Confining Pressures:	10 psi	20 psi	40 psi	Consolidation T50 Values (minutes)		
Initial Moisture:	43.6%	Final Moisture:	36.3%	10 psi	20 psi	40 psi
Initial Wet Density, pcf:	112.3			10.13	5.5	15.3
Initial Dry Density, pcf:	78.2					


Deviator Stress, Excess Pore Pressure and Effective Stress Ratio



Reviewed by: _____ SEG _____

Figure _____ 6 _____

CONSOLIDATION TEST REPORT



Natural								
Saturation	Moisture	Dry Dens. (pcf)	LL	PI	Sp. Gr.	USCS	AASHTO	Initial Void Ratio
89.4 %	33.3 %	82.8	26	1	2.617	SM		0.973

MATERIAL DESCRIPTION

Dark grayish-brown, Silty SAND

Project No. 2012-002 **Client:** MTC
Project: MLT for MTC
 Lower Duwamish River
Source of Sample: LDW21-GT23-GB **Depth:** 28.5

Remarks:
 Specific Gravity determined per ASTM D854




Figure 7

Tested By: AH/GB

Checked By: SEG

CONSOLIDATION TEST REPORT



Natural		Dry Dens. (pcf)	LL	PI	Sp. Gr.	USCS	AASHTO	Initial Void Ratio
Saturation	Moisture							
97.9 %	58.6 %	64.3	38	2	2.612	ML		1.564

MATERIAL DESCRIPTION

Very dark grayish-brown, SILT with sand

Project No. 2012-002 **Client:** MTC

Project: MLT for MTC
Lower Duwamish River

Source of Sample: LDW21-GT33-GB **Depth:** 6.0

Remarks:

Specific Gravity determined per ASTM D854




GEOSCIENCES INC.

DBE/MWBE

Figure 8

Tested By: GB

CONSOLIDATION TEST REPORT



Natural		Dry Dens. (pcf)	LL	PI	Sp. Gr.	USCS	AASHTO	Initial Void Ratio
Saturation								
96.4 %	35.3 %	87.0	31	2	2.643	SM		0.968

MATERIAL DESCRIPTION

Very dark grayish-brown, silty SAND

Project No. 2012-002 **Client:** MTC

Project: MLT for MTC
Lower Duwamish River

Source of Sample: LDW21-GT33-GB **Depth:** 21.0

Remarks:

Specific Gravity determined per ASTM D854



GEOSCIENCES INC.


DBE/MWBE

Figure 9

Tested By: GB

Checked By: SEG

CONSOLIDATION TEST REPORT



Natural		Dry Dens. (pcf)	LL	PI	Sp. Gr.	USCS	AASHTO	Initial Void Ratio
Saturation	Moisture	82.0	38	11	2.627	ML		1.058
108.4 %	43.6 %							

MATERIAL DESCRIPTION

Very dark grayish-brown, SILT with sand

Project No. 2012-002 **Client:** MTC
Project: MLT for MTC
 Lower Duwamish River
Source of Sample: LDW21-GT53-SPT **Depth:** 30.0

Remarks:
 Specific Gravity determined per ASTM D854



Figure 10

Tested By: GB

Checked By: SEG



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 22, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-2006 - 2020
Date sampled: 7-19-21 & 7-20-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician




Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: October 5, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: M. Carrillo

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-2006	LDW21-GT5-0-1.5 ft	233.4	758.3	626.0	132.3	392.6	33.7%
B21-2007	LDW21-GT5-0-7.5 ft	266.3	675.6	572.3	103.3	306.0	33.8%
B21-2008	LDW21-GT5-7.5-9 ft	270.2	918.2	773.3	144.9	503.1	28.8%
B21-2009	LDW21-GT5-7.5-17.2ft	215.7	960.7	862.1	98.6	646.4	15.3%
B21-2010	LDW21-GT5-17.2-17.5 ft	300.9	721.1	625.3	95.8	324.4	29.5%
B21-2011	LDW21-GT5-17.5-19 ft	346.3	836.3	746.0	90.3	399.7	22.6%
B21-2012	LDW21-GT5-17.5-27.5 ft	341.8	961.5	816.3	145.2	474.5	30.6%
B21-2013	LDW21-GT5-27.5-29 ft	356.9	833.5	719.1	114.4	362.2	31.6%
B21-2014	LDW21-GT35-0-1.5 ft	360.3	821.8	607.9	213.9	247.6	86.4%
B21-2015	LDW21-GT35-5-6.5 ft	354.1	572.7	469.6	103.1	115.5	89.3%
B21-2016	LDW21-GT35-10-11.5 ft	359.4	882.4	671.2	211.2	311.8	67.7%
B21-2017	LDW21-GT35-15-16.5 ft	236.6	466.5	417.1	49.4	180.5	27.4%
B21-2018	LDW21-GT35-20-21.5 ft	237.4	947.7	793.9	153.8	556.5	27.6%
B21-2019	LDW21-GT35-25-26.5 ft	224.2	733.1	614.5	118.6	390.3	30.4%
B21-2020	LDW21-GT35-30-31.5 ft	225.1	669.4	560.4	109.0	335.3	32.5%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.




Reviewed by: 
 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting




ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT5-GB-0-7.5 ft Sample #: B21-2007	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 14-Oct-21 Tested By: A. Eifrig	Visual Identification Sand with Silt Sample Color brown
Liquid Limit Determination		
	#1 #2 #3 #4 #5 #6	
Weight of Wet Soils + Pan:		
Weight of Dry Soils + Pan:	Liquid limit cannot be established	
Weight of Pan:		
Weight of Dry Soils:		
Weight of Moisture:		
% Moisture:		
Number of Blows:		
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I _p : N/A		
Plastic Limit Determination		
	#1 #2 #3 #4 #5 #6	
Weight of Wet Soils + Pan:		
Weight of Dry Soils + Pan:	Plastic limit cannot be determined	
Weight of Pan:		
Weight of Dry Soils:		
Weight of Moisture:		
% Moisture:		
		
<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center;">Plasticity Chart</p>  </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center;">Liquid Limit</p>  </div> </div>		

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.


Reviewed by: 
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT5-GB-7.5-17.2 ft Sample#: B21-2009	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SW-SM, Well-graded Sand with Silt and Gravel Sample Color: brown	
--	---	---	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.034 mm D ₍₁₀₎ = 0.068 mm D ₍₁₅₎ = 0.162 mm D ₍₃₀₎ = 0.370 mm D ₍₅₀₎ = 0.801 mm D ₍₆₀₎ = 1.580 mm D ₍₉₀₎ = 12.641 mm Dust Ratio = 23/72	% Gravel = 24.4% % Sand = 64.6% % Silt & Clay = 11.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.27 Coeff. of Uniformity, C _u = 23.13 Fineness Modulus = 3.41 Plastic Limit = n/a Moisture %, as sampled = 15.3% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	96%	96%	100.0%	0.0%
5/8"	16.00		93%	100.0%	0.0%
1/2"	12.50	90%	90%	100.0%	0.0%
3/8"	9.50	86%	86%	100.0%	0.0%
1/4"	6.30		79%	100.0%	0.0%
#4	4.75	76%	76%	100.0%	0.0%
#8	2.36		66%	100.0%	0.0%
#10	2.00	65%	65%	100.0%	0.0%
#16	1.18		56%	100.0%	0.0%
#20	0.850	52%	52%	100.0%	0.0%
#30	0.600		42%	100.0%	0.0%
#40	0.425	34%	34%	100.0%	0.0%
#50	0.300		24%	100.0%	0.0%
#60	0.250	20%	20%	100.0%	0.0%
#80	0.180		16%	100.0%	0.0%
#100	0.150	14%	14%	100.0%	0.0%
#140	0.106		12%	100.0%	0.0%
#170	0.090		12%	100.0%	0.0%
#200	0.075	11.0%	11.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-2009
 Sample Date: 7/19/2021
 Test Date: 10/12/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT5-GB-7.5-17.2 ft
 Visual Soil Description: brown sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	25.3	
	Initial	Post-Consolidation
Dry Density (PCF):	106.6	108.7
Void Ratio:	0.580	0.549
Porosity (%):	36.7	35.5
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	25.2	
	Initial	Post-Consolidation
Dry Density (PCF):	107.2	109.2
Void Ratio:	0.571	0.543
Porosity (%):	36.3	35.2
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	25.8	
	Initial	Post-Consolidation
Dry Density (PCF):	106.6	109.4
Void Ratio:	0.581	0.540
Porosity (%):	36.7	35.1
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	39	37
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	340	860	1590
Residual Horizontal Stress, τ_h (PSF):	330	750	1550



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT5-GB-17.2-17.5 ft Sample #: B21-2010	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 14-Oct-21 Tested By: A. Eifrig	Visual Identification Sand with Silt Sample Color brown
Liquid Limit Determination		
	#1 #2 #3 #4 #5 #6	
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture: Number of Blows:	Liquid limit cannot be established	
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A		
Plastic Limit Determination		
	#1 #2 #3 #4 #5 #6	
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture:	Plastic limit cannot be determined	



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT5-GB-17.5-27.5 ft Sample#: B21-2012	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: brown	 Certificate #: 1366.01
---	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.022$ mm $D_{(10)} = 0.068$ mm $D_{(15)} = 0.088$ mm $D_{(30)} = 0.136$ mm $D_{(50)} = 0.239$ mm $D_{(60)} = 0.297$ mm $D_{(90)} = 1.161$ mm Dust Ratio = 2/15	% Gravel = 0.6% % Sand = 88.5% % Silt & Clay = 11.0% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 0.91$ Coeff. of Uniformity, $C_u = 4.38$ Fineness Modulus = 1.33 Plastic Limit = n/a Moisture %, as sampled = 30.6% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	99%	99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	90%	90%	100.0%	0.0%
#20	0.850	87%	87%	100.0%	0.0%
#30	0.600	84%	84%	100.0%	0.0%
#40	0.425	82%	82%	100.0%	0.0%
#50	0.300	61%	61%	100.0%	0.0%
#60	0.250	52%	52%	100.0%	0.0%
#80	0.180	40%	40%	100.0%	0.0%
#100	0.150	35%	35%	100.0%	0.0%
#140	0.106	21%	21%	100.0%	0.0%
#170	0.090	16%	16%	100.0%	0.0%
#200	0.075	11.0%	11.0%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT5-GB-17.5-27.5 ft Sample#: B21-2012		Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: K. Mendez		Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color brown																																																																																																								
ASTM D7928, HYDROMETER ANALYSIS				ASTM D6913																																																																																																								
Sp Gr. 2.56 Sample Weight: 100.01 grams Hydroscopic Moist.: 1.52% Adj. Sample Wgt : 98.51 grams				Sieve Analysis Grain Size Distribution																																																																																																								
<table border="1"> <thead> <tr> <th>Hydrometer Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>8</td><td>8.2%</td><td>0.0545 mm</td></tr> <tr><td>2</td><td>6</td><td>6.1%</td><td>0.0389 mm</td></tr> <tr><td>5</td><td>5</td><td>5.1%</td><td>0.0248 mm</td></tr> <tr><td>15</td><td>4.5</td><td>4.6%</td><td>0.0144 mm</td></tr> <tr><td>30</td><td>4</td><td>4.1%</td><td>0.0102 mm</td></tr> <tr><td>60</td><td>3</td><td>3.1%</td><td>0.0072 mm</td></tr> <tr><td>240</td><td>1.5</td><td>1.5%</td><td>0.0036 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.0%</td><td>0.0015 mm</td></tr> </tbody> </table>		Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	8	8.2%	0.0545 mm	2	6	6.1%	0.0389 mm	5	5	5.1%	0.0248 mm	15	4.5	4.6%	0.0144 mm	30	4	4.1%	0.0102 mm	60	3	3.1%	0.0072 mm	240	1.5	1.5%	0.0036 mm	1440	1	1.0%	0.0015 mm	<table border="1"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>99%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>99%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>87%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>82%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>35%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>11.0%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>10.8%</td><td>0.074 mm</td></tr> <tr><td></td><td>6.9%</td><td>0.050 mm</td></tr> <tr><td></td><td>4.9%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>2.1%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.1%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.7%</td><td>0.001 mm</td></tr> </tbody> </table>		Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	99%	4.750 mm	#10	99%	2.000 mm	#20	87%	0.850 mm	#40	82%	0.425 mm	#100	35%	0.150 mm	#200	11.0%	0.075 mm	Silts	10.8%	0.074 mm		6.9%	0.050 mm		4.9%	0.020 mm	Clays	2.1%	0.005 mm		1.1%	0.002 mm	Colloids	0.7%	0.001 mm
Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																									
1	8	8.2%	0.0545 mm																																																																																																									
2	6	6.1%	0.0389 mm																																																																																																									
5	5	5.1%	0.0248 mm																																																																																																									
15	4.5	4.6%	0.0144 mm																																																																																																									
30	4	4.1%	0.0102 mm																																																																																																									
60	3	3.1%	0.0072 mm																																																																																																									
240	1.5	1.5%	0.0036 mm																																																																																																									
1440	1	1.0%	0.0015 mm																																																																																																									
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																										
3.0"	100%	75.000 mm																																																																																																										
2.0"	100%	50.000 mm																																																																																																										
1.5"	100%	37.500 mm																																																																																																										
1.25"	100%	31.500 mm																																																																																																										
1.0"	100%	25.000 mm																																																																																																										
3/4"	100%	19.000 mm																																																																																																										
5/8"	100%	16.000 mm																																																																																																										
1/2"	100%	12.500 mm																																																																																																										
3/8"	100%	9.500 mm																																																																																																										
1/4"	100%	6.300 mm																																																																																																										
#4	99%	4.750 mm																																																																																																										
#10	99%	2.000 mm																																																																																																										
#20	87%	0.850 mm																																																																																																										
#40	82%	0.425 mm																																																																																																										
#100	35%	0.150 mm																																																																																																										
#200	11.0%	0.075 mm																																																																																																										
Silts	10.8%	0.074 mm																																																																																																										
	6.9%	0.050 mm																																																																																																										
	4.9%	0.020 mm																																																																																																										
Clays	2.1%	0.005 mm																																																																																																										
	1.1%	0.002 mm																																																																																																										
Colloids	0.7%	0.001 mm																																																																																																										
% Gravel: 0.6% % Sand: 88.5% % Silt: 8.9% % Clay: 2.1%		Liquid Limit: n/a Plastic Limit: n/a Plasticity Index: n/a																																																																																																										
USDA Soil Textural Classification																																																																																																												
% Sand: % Silt: % Clay:		Particle Size 2.0 - 0.05 mm 0.05 - 0.002 mm < 0.002 mm																																																																																																										
USDA Soil Textural Classification Sand																																																																																																												

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT35-GB-5-6.5 ft Sample #: B21-2015	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 14-Oct-21 Tested By: K. Mendez	Visual Identification Clay Sample Color brown
---	--	--


Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	30.42	27.71	26.95			
Weight of Dry Soils + Pan:	27.89	24.44	23.66			
Weight of Pan:	19.88	15.05	14.81			
Weight of Dry Soils:	8.01	9.39	8.85			
Weight of Moisture:	2.53	3.27	3.29			
% Moisture:	31.6 %	34.8 %	37.2 %			
Number of Blows:	25	20	15			

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	37.34	36.36				
Weight of Dry Soils + Pan:	36.82	35.86				
Weight of Pan:	31.03	30.33				
Weight of Dry Soils:	5.79	5.53				
Weight of Moisture:	0.52	0.50				
% Moisture:	9.0 %	9.0 %				


Liquid Limit @ 25 Blows: 32 %

Plastic Limit: 9 %


Plasticity Index, I_p: 23 %



Certificate #: 1366.01, 1366.02 & 1366.04



Copyright Spears Engineering & Technical Services PS, 1996-98



All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by: 
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT35-GB-15-16.5 ft Sample#: B21-2017	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: gray	 Certificate #: 1366.01
--	---	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.004 mm D ₍₁₀₎ = 0.009 mm D ₍₁₅₎ = 0.017 mm D ₍₃₀₎ = 0.057 mm D ₍₅₀₎ = 0.119 mm D ₍₆₀₎ = 0.148 mm D ₍₉₀₎ = 0.320 mm Dust Ratio = 11/31	% Gravel = 0.0% % Sand = 64.9% % Silt & Clay = 35.1% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 2.36 Coeff. of Uniformity, C _u = 16.11 Fineness Modulus = 0.52 Plastic Limit = n/a Moisture %, as sampled = 27.4% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	88%	88%	100.0%	0.0%
#60	0.250	84%	84%	100.0%	0.0%
#80	0.180	68%	68%	100.0%	0.0%
#100	0.150	61%	61%	100.0%	0.0%
#140	0.106	46%	46%	100.0%	0.0%
#170	0.090	40%	40%	100.0%	0.0%
#200	0.075	35.1%	35.1%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT35-GB-15-16.5 ft Sample#: B21-2017	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color gray																																																																																																																																								
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																																																																								
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Sp Gr.</td> <td style="width: 10%; text-align: center;">2.59</td> <td style="width: 60%;"></td> </tr> <tr> <td>Sample Weight:</td> <td style="text-align: center;">102.29</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td style="text-align: center;">1.10%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td style="text-align: center;">101.18</td> <td>grams</td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td style="text-align: center;">27.5</td><td style="text-align: center;">27.7%</td><td style="text-align: center;">0.0486 mm</td></tr> <tr><td>2</td><td style="text-align: center;">23</td><td style="text-align: center;">23.2%</td><td style="text-align: center;">0.0352 mm</td></tr> <tr><td>5</td><td style="text-align: center;">18</td><td style="text-align: center;">18.1%</td><td style="text-align: center;">0.0230 mm</td></tr> <tr><td>15</td><td style="text-align: center;">13</td><td style="text-align: center;">13.1%</td><td style="text-align: center;">0.0137 mm</td></tr> <tr><td>30</td><td style="text-align: center;">10.5</td><td style="text-align: center;">10.6%</td><td style="text-align: center;">0.0099 mm</td></tr> <tr><td>60</td><td style="text-align: center;">8</td><td style="text-align: center;">8.1%</td><td style="text-align: center;">0.0070 mm</td></tr> <tr><td>240</td><td style="text-align: center;">5</td><td style="text-align: center;">5.0%</td><td style="text-align: center;">0.0036 mm</td></tr> <tr><td>1440</td><td style="text-align: center;">3</td><td style="text-align: center;">3.0%</td><td style="text-align: center;">0.0015 mm</td></tr> </tbody> </table> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 30%; text-align: center;">0.0%</td> <td style="width: 30%;">Liquid Limit:</td> <td style="width: 10%; text-align: center;">n/a</td> </tr> <tr> <td>% Sand:</td> <td style="text-align: center;">64.9%</td> <td>Plastic Limit:</td> <td style="text-align: center;">n/a</td> </tr> <tr> <td>% Silt:</td> <td style="text-align: center;">28.8%</td> <td>Plasticity Index:</td> <td style="text-align: center;">n/a</td> </tr> <tr> <td>% Clay:</td> <td style="text-align: center;">6.3%</td> <td></td> <td></td> </tr> </table>	Sp Gr.	2.59		Sample Weight:	102.29	grams	Hydroscopic Moist.:	1.10%		Adj. Sample Wgt :	101.18	grams	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	27.5	27.7%	0.0486 mm	2	23	23.2%	0.0352 mm	5	18	18.1%	0.0230 mm	15	13	13.1%	0.0137 mm	30	10.5	10.6%	0.0099 mm	60	8	8.1%	0.0070 mm	240	5	5.0%	0.0036 mm	1440	3	3.0%	0.0015 mm	% Gravel:	0.0%	Liquid Limit:	n/a	% Sand:	64.9%	Plastic Limit:	n/a	% Silt:	28.8%	Plasticity Index:	n/a	% Clay:	6.3%			 <p style="font-size: small;">ACCREDITED Certificate #: 1366.01</p>	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3" style="text-align: center;">Sieve Analysis</th> </tr> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td style="text-align: center;">100%</td><td style="text-align: center;">75.000 mm</td></tr> <tr><td>2.0"</td><td style="text-align: center;">100%</td><td style="text-align: center;">50.000 mm</td></tr> <tr><td>1.5"</td><td style="text-align: center;">100%</td><td style="text-align: center;">37.500 mm</td></tr> <tr><td>1.25"</td><td style="text-align: center;">100%</td><td style="text-align: center;">31.500 mm</td></tr> <tr><td>1.0"</td><td style="text-align: center;">100%</td><td style="text-align: center;">25.000 mm</td></tr> <tr><td>3/4"</td><td style="text-align: center;">100%</td><td style="text-align: center;">19.000 mm</td></tr> <tr><td>5/8"</td><td style="text-align: center;">100%</td><td style="text-align: center;">16.000 mm</td></tr> <tr><td>1/2"</td><td style="text-align: center;">100%</td><td style="text-align: center;">12.500 mm</td></tr> <tr><td>3/8"</td><td style="text-align: center;">100%</td><td style="text-align: center;">9.500 mm</td></tr> <tr><td>1/4"</td><td style="text-align: center;">100%</td><td style="text-align: center;">6.300 mm</td></tr> <tr><td>#4</td><td style="text-align: center;">100%</td><td style="text-align: center;">4.750 mm</td></tr> <tr><td>#10</td><td style="text-align: center;">100%</td><td style="text-align: center;">2.000 mm</td></tr> <tr><td>#20</td><td style="text-align: center;">100%</td><td style="text-align: center;">0.850 mm</td></tr> <tr><td>#40</td><td style="text-align: center;">99%</td><td style="text-align: center;">0.425 mm</td></tr> <tr><td>#100</td><td style="text-align: center;">61%</td><td style="text-align: center;">0.150 mm</td></tr> <tr><td>#200</td><td style="text-align: center;">35.1%</td><td style="text-align: center;">0.075 mm</td></tr> <tr><td>Silts</td><td style="text-align: center;">34.8%</td><td style="text-align: center;">0.074 mm</td></tr> <tr><td></td><td style="text-align: center;">30.4%</td><td style="text-align: center;">0.050 mm</td></tr> <tr><td></td><td style="text-align: center;">16.5%</td><td style="text-align: center;">0.020 mm</td></tr> <tr><td>Clays</td><td style="text-align: center;">6.3%</td><td style="text-align: center;">0.005 mm</td></tr> <tr><td></td><td style="text-align: center;">3.5%</td><td style="text-align: center;">0.002 mm</td></tr> <tr><td>Colloids</td><td style="text-align: center;">2.0%</td><td style="text-align: center;">0.001 mm</td></tr> </tbody> </table>	Sieve Analysis			Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	100%	0.850 mm	#40	99%	0.425 mm	#100	61%	0.150 mm	#200	35.1%	0.075 mm	Silts	34.8%	0.074 mm		30.4%	0.050 mm		16.5%	0.020 mm	Clays	6.3%	0.005 mm		3.5%	0.002 mm	Colloids	2.0%	0.001 mm
Sp Gr.	2.59																																																																																																																																									
Sample Weight:	102.29	grams																																																																																																																																								
Hydroscopic Moist.:	1.10%																																																																																																																																									
Adj. Sample Wgt :	101.18	grams																																																																																																																																								
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																																							
1	27.5	27.7%	0.0486 mm																																																																																																																																							
2	23	23.2%	0.0352 mm																																																																																																																																							
5	18	18.1%	0.0230 mm																																																																																																																																							
15	13	13.1%	0.0137 mm																																																																																																																																							
30	10.5	10.6%	0.0099 mm																																																																																																																																							
60	8	8.1%	0.0070 mm																																																																																																																																							
240	5	5.0%	0.0036 mm																																																																																																																																							
1440	3	3.0%	0.0015 mm																																																																																																																																							
% Gravel:	0.0%	Liquid Limit:	n/a																																																																																																																																							
% Sand:	64.9%	Plastic Limit:	n/a																																																																																																																																							
% Silt:	28.8%	Plasticity Index:	n/a																																																																																																																																							
% Clay:	6.3%																																																																																																																																									
Sieve Analysis																																																																																																																																										
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																																								
3.0"	100%	75.000 mm																																																																																																																																								
2.0"	100%	50.000 mm																																																																																																																																								
1.5"	100%	37.500 mm																																																																																																																																								
1.25"	100%	31.500 mm																																																																																																																																								
1.0"	100%	25.000 mm																																																																																																																																								
3/4"	100%	19.000 mm																																																																																																																																								
5/8"	100%	16.000 mm																																																																																																																																								
1/2"	100%	12.500 mm																																																																																																																																								
3/8"	100%	9.500 mm																																																																																																																																								
1/4"	100%	6.300 mm																																																																																																																																								
#4	100%	4.750 mm																																																																																																																																								
#10	100%	2.000 mm																																																																																																																																								
#20	100%	0.850 mm																																																																																																																																								
#40	99%	0.425 mm																																																																																																																																								
#100	61%	0.150 mm																																																																																																																																								
#200	35.1%	0.075 mm																																																																																																																																								
Silts	34.8%	0.074 mm																																																																																																																																								
	30.4%	0.050 mm																																																																																																																																								
	16.5%	0.020 mm																																																																																																																																								
Clays	6.3%	0.005 mm																																																																																																																																								
	3.5%	0.002 mm																																																																																																																																								
Colloids	2.0%	0.001 mm																																																																																																																																								
USDA Soil Textural Classification																																																																																																																																										
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Sand:</td> <td style="width: 70%; text-align: center;">Particle Size 2.0 - 0.05 mm</td> </tr> <tr> <td>% Silt:</td> <td style="text-align: center;">0.05 - 0.002 mm</td> </tr> <tr> <td>% Clay:</td> <td style="text-align: center;">< 0.002 mm</td> </tr> </table> <p style="text-align: center;">USDA Soil Textural Classification Sandy Loam</p>	% Sand:	Particle Size 2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																																																				
% Sand:	Particle Size 2.0 - 0.05 mm																																																																																																																																									
% Silt:	0.05 - 0.002 mm																																																																																																																																									
% Clay:	< 0.002 mm																																																																																																																																									

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-2017
 Sample Date: 7/20/2021
 Test Date: 10/6/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT35-GB-15-16.5 ft
 Visual Soil Description: gray sand
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	29.5	
	Initial	Post-Consolidation
Dry Density (PCF):	109.5	110.5
Void Ratio:	0.539	0.525
Porosity (%):	35.0	34.4
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	30.1	
	Initial	Post-Consolidation
Dry Density (PCF):	108.1	110.4
Void Ratio:	0.559	0.527
Porosity (%):	35.8	34.5
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	32.2	
	Initial	Post-Consolidation
Dry Density (PCF):	107.5	110.7
Void Ratio:	0.567	0.522
Porosity (%):	36.2	34.3
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	36	32
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	310	720	1470
Residual Horizontal Stress, τ_h (PSF):	280	650	1230



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT35-GB-20-21.5 ft Sample#: B21-2018	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 6-Oct-21 Tested By: K. Mendez	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 ACCREDITED Certificate #: 1366.01
--	---	---	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.019 mm	% Gravel = 0.0%	Coeff. of Curvature, C _c = 1.60
D ₍₁₀₎ = 0.038 mm	% Sand = 80.5%	Coeff. of Uniformity, C _u = 4.92
D ₍₁₅₎ = 0.058 mm	% Silt & Clay = 19.5%	Fineness Modulus = 0.68
D ₍₃₀₎ = 0.108 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.166 mm	Plasticity Index = n/a	Moisture %, as sampled = 27.6%
D ₍₆₀₎ = 0.189 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.304 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 13/66	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600		99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300		90%	100.0%	0.0%
#60	0.250	86%	86%	100.0%	0.0%
#80	0.180		56%	100.0%	0.0%
#100	0.150	43%	43%	100.0%	0.0%
#140	0.106		29%	100.0%	0.0%
#170	0.090		24%	100.0%	0.0%
#200	0.075	19.5%	19.5%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments:

Reviewed by:
Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT35-GB-30-31.5 ft Sample #: B21-2020	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 14-Oct-21 Tested By: A. Eifrig	Visual Identification Silty Sand Sample Color brown
Liquid Limit Determination		
	#1 #2 #3 #4 #5 #6	
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture: Number of Blows:	Liquid limit cannot be established	
Liquid Limit @ 25 Blows: N/A Plastic Limit: N/A Plasticity Index, I_p: N/A		
Plastic Limit Determination		
	#1 #2 #3 #4 #5 #6	
Weight of Wet Soils + Pan: Weight of Dry Soils + Pan: Weight of Pan: Weight of Dry Soils: Weight of Moisture: % Moisture:	Plastic limit cannot be determined	
Plasticity Chart 		
Liquid Limit 		

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation upon spreading into the cup. At lower moistures the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the material does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:
 Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 25, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-2143-2162
Date sampled: August 5, 2021

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: October 15, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-2143	LDW21-GT48-GB-21.6-25 ft	234.6	512.3	437.5	74.8	202.9	36.9%
B21-2144	LDW21-GT48-GB-25-30 ft	221.6	1232.1	959.0	273.1	737.4	37.0%
B21-2145	LDW21-GT48-GB-30-35 ft	215.3	1034.5	826.3	208.2	611.0	34.1%
B21-2146	LDW21-GT48-GB-35-36.5 ft	235.3	1073.2	832.7	240.5	597.4	40.3%
B21-2147	LDW21-GT53-GB-0-1.5 ft	228.9	845.1	638.7	206.4	409.8	50.4%
B21-2148	LDW21-GT53-GB-0-5 ft	208.5	682.6	526.4	156.2	317.9	49.1%
B21-2149	LDW21-GT53-GB-5-6.5 ft	222.9	1006.1	801.8	204.3	578.9	35.3%
B21-2150	LDW21-GT53-GB-5-10 ft	229.4	762.5	595.5	167.0	366.1	45.6%
B21-2151	LDW21-GT53-GB-10-15 ft	221.1	1092.3	749.6	342.7	528.5	64.8%
B21-2152	LDW21-GT53-GB-15-20 ft	220.4	805.0	678.3	126.7	457.9	27.7%
B21-2153	LDW21-GT53-GB-20-23.5 ft	222.9	998.0	819.4	178.6	596.5	29.9%
B21-2154	LDW21-GT53-GB-23.5-25 ft	217.3	990.1	795.4	194.7	578.1	33.7%
B21-2155	LDW21-GT53-GB-25-28.6 ft	222.6	807.8	656.4	151.4	433.8	34.9%
B21-2156	LDW21-GT53-GB-28.6-30 ft	224.3	929.6	800.4	129.2	576.1	22.4%
B21-2157	LDW21-GT48-SPT-0-0.7 ft	268.9	742.1	658.8	83.3	389.9	21.4%
B21-2158	LDW21-GT48-SPT-0.7-1.5 ft	310.9	685.1	612.8	72.3	301.9	23.9%
B21-2159	LDW21-GT48-SPT-10-11.5 ft	319.8	870.6	717.8	152.8	398.0	38.4%
B21-2160	LDW21-GT48-SPT-15-16.5 ft	301.0	852.0	723.3	128.7	422.3	30.5%
B21-2161	LDW21-GT48-SPT-20-20.6 ft	302.0	675.6	567.7	107.9	265.7	40.6%
B21-2162	LDW21-GT48-SPT-20.6-21.5 ft	303.2	829.7	715.1	114.6	411.9	27.8%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: 
 Meghan Blodgett-Carrillo



Moisture Content - ASTM D854

Project: Q.C. - Lower Duwamish Waterway
 Project #: 21B233
 Date Received: July 29, 2021
 Date Tested: October 16, 2021

Client: Anchor QEA
 Sampled by: Client
 Tested by: A. Eifrig

Sample #	Location	Tare	Dry Soil + Tare	Mass of Dry Soil	Pycno ID	Mass of Pycno	Volume of Pycno	Density of Water @ Tx	Mass of Pycno filled w/ water & soils	Mass of Pycno filled w/ water	Temp. of Water, 0.1 *C	SpG of Soils	Temp. Correction Factor	Corrected SpG
B21-2143	LDW21-GT48-GB-21.6-25 ft	420.68	495.04	74.4	TSA-010	180.3	499.5	0.99854	725.29	679.12	18.3	2.6377506	1.00034	2.6386475
B21-2148	LDW21-GT53-GB-0-5 ft	413.74	512.57	98.8	TSA-011	190.3	499.5	0.99856	747.85	689.15	18.3	2.4627054	1.00035	2.4635674
B21-2152	LDW21-GT53-GB-15-20 ft	379.63	483.20	103.6	TSA-017	187.9	499.4	0.99841	751.03	686.50	19.1	2.6531994	1.00020	2.65373
B21-2155	LDW21-GT53-GB-25-28.6 ft	394.13	472.87	78.7	TSA-022	198.0	499.5	0.99856	743.69	696.72	18.3	2.478377	1.00035	2.4792444

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.


Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-21.6-25 ft Sample#: B21-2143	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Visual Identification Silt with Sand and Clay Sample Color: brown	 ACCREDITED Certificate #: 1366.01
--	--	--	--

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.001 mm D ₍₁₀₎ = 0.003 mm D ₍₁₅₎ = 0.004 mm D ₍₃₀₎ = 0.010 mm D ₍₅₀₎ = 0.023 mm D ₍₆₀₎ = 0.040 mm D ₍₉₀₎ = 0.090 mm Dust Ratio = 29/33	% Gravel = 0.0% % Sand = 12.3% % Silt & Clay = 87.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 0.94 Coeff. of Uniformity, C _u = 14.64 Fineness Modulus = 0.02 Plastic Limit = n/a Moisture %, as sampled = 36.9% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	100%	100%	100.0%	0.0%
#40	0.425	100%	100%	100.0%	0.0%
#50	0.300	100%	100%	100.0%	0.0%
#60	0.250	99%	99%	100.0%	0.0%
#80	0.180	99%	99%	100.0%	0.0%
#100	0.150	99%	99%	100.0%	0.0%
#140	0.106	92%	92%	100.0%	0.0%
#170	0.090	90%	90%	100.0%	0.0%
#200	0.075	87.7%	87.7%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client : Anchor QEA Source: LDW21-GT48-GB-21.6-25 ft Sample#: B21-2143		Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig		Visual Identification Silt with Sand and Clay Sample Color brown																																																																																																										
ASTM D7928, HYDROMETER ANALYSIS				ASTM D6913																																																																																																										
Sp. Gr 2.64 Sample Weight: 50.35 grams Hydroscopic Moist.: 2.46% Adj. Sample Wgt : 49.14 grams				Sieve Analysis Grain Size Distribution																																																																																																										
<table border="1"> <thead> <tr> <th>Hydrometer Reading</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>31</td><td>63.7%</td><td>0.0464 mm</td></tr> <tr><td>2</td><td>27.5</td><td>56.5%</td><td>0.0338 mm</td></tr> <tr><td>5</td><td>24</td><td>49.3%</td><td>0.0218 mm</td></tr> <tr><td>15</td><td>17.5</td><td>36.0%</td><td>0.0131 mm</td></tr> <tr><td>30</td><td>14</td><td>28.8%</td><td>0.0095 mm</td></tr> <tr><td>60</td><td>11.5</td><td>23.6%</td><td>0.0068 mm</td></tr> <tr><td>240</td><td>6</td><td>12.3%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>3</td><td>6.2%</td><td>0.0015 mm</td></tr> </tbody> </table>		Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	31	63.7%	0.0464 mm	2	27.5	56.5%	0.0338 mm	5	24	49.3%	0.0218 mm	15	17.5	36.0%	0.0131 mm	30	14	28.8%	0.0095 mm	60	11.5	23.6%	0.0068 mm	240	6	12.3%	0.0035 mm	1440	3	6.2%	0.0015 mm			<table border="1"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>100%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>100%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>99%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>87.7%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>86.8%</td><td>0.074 mm</td></tr> <tr><td></td><td>73.1%</td><td>0.050 mm</td></tr> <tr><td></td><td>46.5%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>17.5%</td><td>0.005 mm</td></tr> <tr><td></td><td>7.8%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>4.2%</td><td>0.001 mm</td></tr> </tbody> </table>		Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	100%	0.850 mm	#40	100%	0.425 mm	#100	99%	0.150 mm	#200	87.7%	0.075 mm	Silts	86.8%	0.074 mm		73.1%	0.050 mm		46.5%	0.020 mm	Clays	17.5%	0.005 mm		7.8%	0.002 mm	Colloids	4.2%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																											
1	31	63.7%	0.0464 mm																																																																																																											
2	27.5	56.5%	0.0338 mm																																																																																																											
5	24	49.3%	0.0218 mm																																																																																																											
15	17.5	36.0%	0.0131 mm																																																																																																											
30	14	28.8%	0.0095 mm																																																																																																											
60	11.5	23.6%	0.0068 mm																																																																																																											
240	6	12.3%	0.0035 mm																																																																																																											
1440	3	6.2%	0.0015 mm																																																																																																											
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																												
3.0"	100%	75.000 mm																																																																																																												
2.0"	100%	50.000 mm																																																																																																												
1.5"	100%	37.500 mm																																																																																																												
1.25"	100%	31.500 mm																																																																																																												
1.0"	100%	25.000 mm																																																																																																												
3/4"	100%	19.000 mm																																																																																																												
5/8"	100%	16.000 mm																																																																																																												
1/2"	100%	12.500 mm																																																																																																												
3/8"	100%	9.500 mm																																																																																																												
1/4"	100%	6.300 mm																																																																																																												
#4	100%	4.750 mm																																																																																																												
#10	100%	2.000 mm																																																																																																												
#20	100%	0.850 mm																																																																																																												
#40	100%	0.425 mm																																																																																																												
#100	99%	0.150 mm																																																																																																												
#200	87.7%	0.075 mm																																																																																																												
Silts	86.8%	0.074 mm																																																																																																												
	73.1%	0.050 mm																																																																																																												
	46.5%	0.020 mm																																																																																																												
Clays	17.5%	0.005 mm																																																																																																												
	7.8%	0.002 mm																																																																																																												
Colloids	4.2%	0.001 mm																																																																																																												
% Gravel: 0.0% % Sand: 12.3% % Silt: 70.2% % Clay: 17.5%		Liquid Limit: n/a Plastic Limit: n/a Plasticity Index: n/a																																																																																																												
USDA Soil Textural Classification																																																																																																														
<table border="1"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																					
	Particle Size																																																																																																													
% Sand:	2.0 - 0.05 mm																																																																																																													
% Silt:	0.05 - 0.002 mm																																																																																																													
% Clay:	< 0.002 mm																																																																																																													
USDA Soil Textural Classification Silt Loam																																																																																																														

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-21.6-25 ft Sample #: B21-2143	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Visual Identification Silt with Sand and Clay Sample Color brown				
Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Unable to establish liquid limit					
Weight of Dry Soils + Pan:	Unable to establish liquid limit					
Weight of Pan:	Unable to establish liquid limit					
Weight of Dry Soils:	Unable to establish liquid limit					
Weight of Moisture:	Unable to establish liquid limit					
% Moisture:	Unable to establish liquid limit					
Number of Blows:	Unable to establish liquid limit					
Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Cannot determined plastic limit					
Weight of Dry Soils + Pan:	Cannot determined plastic limit					
Weight of Pan:	Cannot determined plastic limit					
Weight of Dry Soils:	Cannot determined plastic limit					
Weight of Moisture:	Cannot determined plastic limit					
% Moisture:	Cannot determined plastic limit					

Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures, the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT48-GB-25-30 ft Sample #: B21-2144	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Visual Identification Silt with Sand and Clay Sample Color brown
---	--	---

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Unable to establish liquid limit					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Cannot determined plastic limit					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures, the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by: _____
 Meghan Blodgett-Carrillo

Materials Testing & Consulting, Inc.

Geotechnical Engineering • Special Inspections • Materials Testing • Environmental Consulting



ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA, LLC Source: LDW21-GT48-GB-30-35 ft Sample #: B21-2145	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 18-Oct-21 Tested By: C. Kirk-Patterson	Visual Identification Silt with Clay Sample Color brown
--	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	29.11	30.59	34.12			
Weight of Dry Soils + Pan:	25.96	26.90	30.59			
Weight of Pan:	15.19	14.77	19.81			
Weight of Dry Soils:	10.77	12.13	10.78			
Weight of Moisture:	3.15	3.69	3.53			
% Moisture:	29.3 %	30.4 %	32.8 %			
Number of Blows:	30	23	18			

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	34.58	35.80				
Weight of Dry Soils + Pan:	33.37	34.35				
Weight of Pan:	28.28	28.60				
Weight of Dry Soils:	5.09	5.75				
Weight of Moisture:	1.21	1.45				
% Moisture:	23.8 %	25.2 %				

<p style="text-align: center;">Plasticity Chart</p>	<p style="text-align: center;">Liquid Limit</p>
--	--

Liquid Limit @ 25 Blows: 30 %
 Plastic Limit: 24 %
 Plasticity Index, I_p: 6 %



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett Carrillo*
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils



Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-0-5 ft Sample #: B21-2148	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Visual Identification Silt with Clay Sample Color brown
---	--	--

Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Unable to establish liquid limit					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						
Number of Blows:						



Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Cannot determined plastic limit					
Weight of Dry Soils + Pan:						
Weight of Pan:						
Weight of Dry Soils:						
Weight of Moisture:						
% Moisture:						



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures, the material does not spread into the liquid limit device without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by: _____
 Meghan Blodgett-Carrillo


Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-5-10 ft Sample#: B21-2150	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
---	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.005 mm D ₍₁₀₎ = 0.028 mm D ₍₁₅₎ = 0.056 mm D ₍₃₀₎ = 0.081 mm D ₍₅₀₎ = 0.113 mm D ₍₆₀₎ = 0.129 mm D ₍₉₀₎ = 0.335 mm Dust Ratio = 10/37	% Gravel = 0.0% % Sand = 73.4% % Silt & Clay = 26.6% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.81 Coeff. of Uniformity, C _u = 4.67 Fineness Modulus = 0.43 Plastic Limit = n/a Moisture %, as sampled = 45.6% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	99%	100%	100.0%	0.0%
#20	0.850	99%	100%	100.0%	0.0%
#30	0.600	99%	100%	100.0%	0.0%
#40	0.425	98%	98%	100.0%	0.0%
#50	0.300	87%	87%	100.0%	0.0%
#60	0.250	82%	82%	100.0%	0.0%
#80	0.180	76%	76%	100.0%	0.0%
#100	0.150	73%	73%	100.0%	0.0%
#140	0.106	46%	46%	100.0%	0.0%
#170	0.090	36%	36%	100.0%	0.0%
#200	0.075	26.6%	26.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.


Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo




Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client : Anchor QEA Source: LDW21-GT53-GB-5-10 ft Sample#: B21-2150	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																																																									
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																																									
Assumed Sp. Gr: 2.65 Sample Weight: 100.03 grams Hydroscopic Moist.: 2.23% Adj. Sample Wgt : 97.85 grams		Sieve Analysis Grain Size Distribution																																																																																																									
																																																																																																											
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>12</td><td>12.3%</td><td>0.0516 mm</td></tr> <tr><td>2</td><td>11.5</td><td>11.8%</td><td>0.0368 mm</td></tr> <tr><td>5</td><td>9</td><td>9.2%</td><td>0.0235 mm</td></tr> <tr><td>15</td><td>8</td><td>8.2%</td><td>0.0137 mm</td></tr> <tr><td>30</td><td>7</td><td>7.2%</td><td>0.0097 mm</td></tr> <tr><td>60</td><td>6.5</td><td>6.6%</td><td>0.0069 mm</td></tr> <tr><td>240</td><td>3</td><td>3.1%</td><td>0.0035 mm</td></tr> <tr><td>1440</td><td>2</td><td>2.0%</td><td>0.0014 mm</td></tr> </tbody> </table>	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	12	12.3%	0.0516 mm	2	11.5	11.8%	0.0368 mm	5	9	9.2%	0.0235 mm	15	8	8.2%	0.0137 mm	30	7	7.2%	0.0097 mm	60	6.5	6.6%	0.0069 mm	240	3	3.1%	0.0035 mm	1440	2	2.0%	0.0014 mm	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>99%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>98%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>73%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>26.6%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>26.0%</td><td>0.074 mm</td></tr> <tr><td></td><td>14.3%</td><td>0.050 mm</td></tr> <tr><td></td><td>8.8%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>4.6%</td><td>0.005 mm</td></tr> <tr><td></td><td>2.3%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>1.4%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	99%	0.850 mm	#40	98%	0.425 mm	#100	73%	0.150 mm	#200	26.6%	0.075 mm	Silts	26.0%	0.074 mm		14.3%	0.050 mm		8.8%	0.020 mm	Clays	4.6%	0.005 mm		2.3%	0.002 mm	Colloids	1.4%	0.001 mm
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																								
1	12	12.3%	0.0516 mm																																																																																																								
2	11.5	11.8%	0.0368 mm																																																																																																								
5	9	9.2%	0.0235 mm																																																																																																								
15	8	8.2%	0.0137 mm																																																																																																								
30	7	7.2%	0.0097 mm																																																																																																								
60	6.5	6.6%	0.0069 mm																																																																																																								
240	3	3.1%	0.0035 mm																																																																																																								
1440	2	2.0%	0.0014 mm																																																																																																								
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																									
3.0"	100%	75.000 mm																																																																																																									
2.0"	100%	50.000 mm																																																																																																									
1.5"	100%	37.500 mm																																																																																																									
1.25"	100%	31.500 mm																																																																																																									
1.0"	100%	25.000 mm																																																																																																									
3/4"	100%	19.000 mm																																																																																																									
5/8"	100%	16.000 mm																																																																																																									
1/2"	100%	12.500 mm																																																																																																									
3/8"	100%	9.500 mm																																																																																																									
1/4"	100%	6.300 mm																																																																																																									
#4	100%	4.750 mm																																																																																																									
#10	100%	2.000 mm																																																																																																									
#20	99%	0.850 mm																																																																																																									
#40	98%	0.425 mm																																																																																																									
#100	73%	0.150 mm																																																																																																									
#200	26.6%	0.075 mm																																																																																																									
Silts	26.0%	0.074 mm																																																																																																									
	14.3%	0.050 mm																																																																																																									
	8.8%	0.020 mm																																																																																																									
Clays	4.6%	0.005 mm																																																																																																									
	2.3%	0.002 mm																																																																																																									
Colloids	1.4%	0.001 mm																																																																																																									
USDA Soil Textural Classification																																																																																																											
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>		Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																		
	Particle Size																																																																																																										
% Sand:	2.0 - 0.05 mm																																																																																																										
% Silt:	0.05 - 0.002 mm																																																																																																										
% Clay:	< 0.002 mm																																																																																																										
USDA Soil Textural Classification																																																																																																											
Loamy Sand																																																																																																											

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-2150
 Sample Date: 8/5/2021
 Test Date: 10/18/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT53-GB-5-10 ft
 Visual Soil Description: brown silty sand with gravel
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
	Initial Moisture Content (%)	
	Initial	Post-Consolidation
Dry Density (PCF):	109.7	110.6
Void Ratio:	0.536	0.523
Porosity (%):	34.9	34.3
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
	Initial Moisture Content (%)	
	Initial	Post-Consolidation
Dry Density (PCF):	110.2	112.7
Void Ratio:	0.529	0.495
Porosity (%):	34.6	33.1
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
	Initial Moisture Content (%)	
	Initial	Post-Consolidation
Dry Density (PCF):	110.5	114.2
Void Ratio:	0.524	0.475
Porosity (%):	34.4	32.2
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	35	34
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	340	810	1370
Residual Horizontal Stress, τ_h (PSF):	270	730	1320



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-10-15 ft Sample#: B21-2151	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.022 mm D ₍₁₀₎ = 0.044 mm D ₍₁₅₎ = 0.066 mm D ₍₃₀₎ = 0.118 mm D ₍₅₀₎ = 0.199 mm D ₍₆₀₎ = 0.246 mm D ₍₉₀₎ = 0.735 mm Dust Ratio = 13/61	% Gravel = 3.1% % Sand = 79.8% % Silt & Clay = 17.1% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.30 Coeff. of Uniformity, C _u = 5.62 Fineness Modulus = 1.23 Plastic Limit = n/a Moisture %, as sampled = 64.8% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	98%	98%	100.0%	0.0%
1/4"	6.30		97%	100.0%	0.0%
#4	4.75	97%	97%	100.0%	0.0%
#8	2.36		96%	100.0%	0.0%
#10	2.00	96%	96%	100.0%	0.0%
#16	1.18		94%	100.0%	0.0%
#20	0.850	94%	94%	100.0%	0.0%
#30	0.600		86%	100.0%	0.0%
#40	0.425	80%	80%	100.0%	0.0%
#50	0.300		66%	100.0%	0.0%
#60	0.250	61%	61%	100.0%	0.0%
#80	0.180		46%	100.0%	0.0%
#100	0.150	40%	40%	100.0%	0.0%
#140	0.106		26%	100.0%	0.0%
#170	0.090		22%	100.0%	0.0%
#200	0.075	17.1%	17.1%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-15-20 ft Sample#: B21-2152	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: brown	 Certificate #: 1366.01
--	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.055$ mm $D_{(10)} = 0.087$ mm $D_{(15)} = 0.106$ mm $D_{(30)} = 0.158$ mm $D_{(50)} = 0.203$ mm $D_{(60)} = 0.226$ mm $D_{(90)} = 0.376$ mm Dust Ratio = 3/43	% Gravel = 0.1% % Sand = 93.2% % Silt & Clay = 6.8% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 1.27$ Coeff. of Uniformity, $C_u = 2.59$ Fineness Modulus = 0.98 Plastic Limit = n/a Moisture %, as sampled = 27.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850	99%	99%	100.0%	0.0%
#30	0.600		98%	100.0%	0.0%
#40	0.425	97%	97%	100.0%	0.0%
#50	0.300		78%	100.0%	0.0%
#60	0.250	71%	71%	100.0%	0.0%
#80	0.180		40%	100.0%	0.0%
#100	0.150	26%	26%	100.0%	0.0%
#140	0.106		15%	100.0%	0.0%
#170	0.090		11%	100.0%	0.0%
#200	0.075	6.8%	6.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____


Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-20-23.5 ft Sample#: B21-2153	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: brown	 Certificate #: 1366.01
--	--	--	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.060 mm D ₍₁₀₎ = 0.091 mm D ₍₁₅₎ = 0.112 mm D ₍₃₀₎ = 0.166 mm D ₍₅₀₎ = 0.217 mm D ₍₆₀₎ = 0.243 mm D ₍₉₀₎ = 0.522 mm Dust Ratio = 7/99	% Gravel = 0.6% % Sand = 93.2% % Silt & Clay = 6.2% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.24 Coeff. of Uniformity, C _u = 2.67 Fineness Modulus = 1.20 Plastic Limit = n/a Moisture %, as sampled = 29.9% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	99%	99%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	97%	97%	100.0%	0.0%
#20	0.850	96%	96%	100.0%	0.0%
#30	0.600	92%	92%	100.0%	0.0%
#40	0.425	88%	88%	100.0%	0.0%
#50	0.300	70%	70%	100.0%	0.0%
#60	0.250	63%	63%	100.0%	0.0%
#80	0.180	36%	36%	100.0%	0.0%
#100	0.150	24%	24%	100.0%	0.0%
#140	0.106	14%	14%	100.0%	0.0%
#170	0.090	10%	10%	100.0%	0.0%
#200	0.075	6.2%	6.2%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:


 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-23.5-25 ft Sample#: B21-2154	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.008 mm D ₍₁₀₎ = 0.015 mm D ₍₁₅₎ = 0.023 mm D ₍₃₀₎ = 0.046 mm D ₍₅₀₎ = 0.077 mm D ₍₆₀₎ = 0.098 mm D ₍₉₀₎ = 0.186 mm Dust Ratio = 39/79	% Gravel = 0.0% % Sand = 51.1% % Silt & Clay = 48.9% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.41 Coeff. of Uniformity, C _u = 6.38 Fineness Modulus = 0.17 Plastic Limit = n/a Moisture %, as sampled = 33.7% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	98%	98%	100.0%	0.0%
#60	0.250	98%	98%	100.0%	0.0%
#80	0.180	89%	89%	100.0%	0.0%
#100	0.150	85%	85%	100.0%	0.0%
#140	0.106	64%	64%	100.0%	0.0%
#170	0.090	56%	56%	100.0%	0.0%
#200	0.075	48.9%	48.9%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-25-28.6 ft Sample#: B21-2155	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 ACCREDITED Certificate #: 1366.01
--	--	--	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.003 mm	% Gravel = 0.0%	Coeff. of Curvature, C _c = 2.78
D ₍₁₀₎ = 0.008 mm	% Sand = 57.7%	Coeff. of Uniformity, C _u = 15.33
D ₍₁₅₎ = 0.013 mm	% Silt & Clay = 42.3%	Fineness Modulus = 0.37
D ₍₃₀₎ = 0.049 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.093 mm	Plasticity Index = n/a	Moisture %, as sampled = 34.9%
D ₍₆₀₎ = 0.116 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 0.316 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 11/26	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00		100%	100.0%	0.0%
1.50"	37.50		100%	100.0%	0.0%
1.25"	31.50		100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00		100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30		100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36		100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		100%	100.0%	0.0%
#20	0.850		100%	100.0%	0.0%
#30	0.600		100%	100.0%	0.0%
#40	0.425	100%	100%	100.0%	0.0%
#50	0.300		89%	100.0%	0.0%
#60	0.250		84%	100.0%	0.0%
#80	0.180		78%	100.0%	0.0%
#100	0.150	75%	75%	100.0%	0.0%
#140	0.106		56%	100.0%	0.0%
#170	0.090		49%	100.0%	0.0%
#200	0.075	42.3%	42.3%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client : Anchor QEA Source: LDW21-GT53-GB-25-28.6 ft Sample#: B21-2155	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																																	
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																	
<table style="width: 100%;"> <tr> <td style="width: 30%;">Sp. Gr</td> <td style="width: 20%;">2.48</td> <td style="width: 50%;"></td> </tr> <tr> <td>Sample Weight:</td> <td>75.36</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td>0.35%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td>75.10</td> <td>grams</td> </tr> </table>		Sp. Gr	2.48		Sample Weight:	75.36	grams	Hydroscopic Moist.:	0.35%		Adj. Sample Wgt :	75.10	grams																																																																						
Sp. Gr	2.48																																																																																		
Sample Weight:	75.36	grams																																																																																	
Hydroscopic Moist.:	0.35%																																																																																		
Adj. Sample Wgt :	75.10	grams																																																																																	
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>22</td><td>30.8%</td><td>0.0519 mm</td></tr> <tr><td>2</td><td>19</td><td>26.6%</td><td>0.0374 mm</td></tr> <tr><td>5</td><td>17</td><td>23.8%</td><td>0.0239 mm</td></tr> <tr><td>15</td><td>12</td><td>16.8%</td><td>0.0142 mm</td></tr> <tr><td>30</td><td>9</td><td>12.6%</td><td>0.0102 mm</td></tr> <tr><td>60</td><td>7</td><td>9.8%</td><td>0.0073 mm</td></tr> <tr><td>240</td><td>4</td><td>5.6%</td><td>0.0037 mm</td></tr> <tr><td>1440</td><td>2</td><td>2.8%</td><td>0.0015 mm</td></tr> </tbody> </table> <table style="width: 100%;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 20%;">0.0%</td> <td style="width: 50%;">Liquid Limit: n/a</td> </tr> <tr> <td>% Sand:</td> <td>57.7%</td> <td>Plastic Limit: n/a</td> </tr> <tr> <td>% Silt:</td> <td>35.2%</td> <td>Plasticity Index: n/a</td> </tr> <tr> <td>% Clay:</td> <td>7.1%</td> <td></td> </tr> </table>		Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	22	30.8%	0.0519 mm	2	19	26.6%	0.0374 mm	5	17	23.8%	0.0239 mm	15	12	16.8%	0.0142 mm	30	9	12.6%	0.0102 mm	60	7	9.8%	0.0073 mm	240	4	5.6%	0.0037 mm	1440	2	2.8%	0.0015 mm	% Gravel:	0.0%	Liquid Limit: n/a	% Sand:	57.7%	Plastic Limit: n/a	% Silt:	35.2%	Plasticity Index: n/a	% Clay:	7.1%																																			
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																
1	22	30.8%	0.0519 mm																																																																																
2	19	26.6%	0.0374 mm																																																																																
5	17	23.8%	0.0239 mm																																																																																
15	12	16.8%	0.0142 mm																																																																																
30	9	12.6%	0.0102 mm																																																																																
60	7	9.8%	0.0073 mm																																																																																
240	4	5.6%	0.0037 mm																																																																																
1440	2	2.8%	0.0015 mm																																																																																
% Gravel:	0.0%	Liquid Limit: n/a																																																																																	
% Sand:	57.7%	Plastic Limit: n/a																																																																																	
% Silt:	35.2%	Plasticity Index: n/a																																																																																	
% Clay:	7.1%																																																																																		
USDA Soil Textural Classification		Sieve Analysis																																																																																	
<table style="width: 100%;"> <tr> <td style="width: 30%;"></td> <td style="width: 20%; text-align: center;">Particle Size</td> <td style="width: 50%;"></td> </tr> <tr> <td>% Sand:</td> <td>2.0 - 0.05 mm</td> <td></td> </tr> <tr> <td>% Silt:</td> <td>0.05 - 0.002 mm</td> <td></td> </tr> <tr> <td>% Clay:</td> <td>< 0.002 mm</td> <td></td> </tr> </table>			Particle Size		% Sand:	2.0 - 0.05 mm		% Silt:	0.05 - 0.002 mm		% Clay:	< 0.002 mm		<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>100%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>100%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>75%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>42.3%</td><td>0.075 mm</td></tr> <tr><td style="padding-left: 20px;">Silts</td><td>41.8%</td><td>0.074 mm</td></tr> <tr><td></td><td>29.2%</td><td>0.050 mm</td></tr> <tr><td></td><td>20.9%</td><td>0.020 mm</td></tr> <tr><td style="padding-left: 20px;">Clays</td><td>7.1%</td><td>0.005 mm</td></tr> <tr><td></td><td>3.4%</td><td>0.002 mm</td></tr> <tr><td style="padding-left: 20px;">Colloids</td><td>1.8%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	100%	0.850 mm	#40	100%	0.425 mm	#100	75%	0.150 mm	#200	42.3%	0.075 mm	Silts	41.8%	0.074 mm		29.2%	0.050 mm		20.9%	0.020 mm	Clays	7.1%	0.005 mm		3.4%	0.002 mm	Colloids	1.8%	0.001 mm
	Particle Size																																																																																		
% Sand:	2.0 - 0.05 mm																																																																																		
% Silt:	0.05 - 0.002 mm																																																																																		
% Clay:	< 0.002 mm																																																																																		
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																	
3.0"	100%	75.000 mm																																																																																	
2.0"	100%	50.000 mm																																																																																	
1.5"	100%	37.500 mm																																																																																	
1.25"	100%	31.500 mm																																																																																	
1.0"	100%	25.000 mm																																																																																	
3/4"	100%	19.000 mm																																																																																	
5/8"	100%	16.000 mm																																																																																	
1/2"	100%	12.500 mm																																																																																	
3/8"	100%	9.500 mm																																																																																	
1/4"	100%	6.300 mm																																																																																	
#4	100%	4.750 mm																																																																																	
#10	100%	2.000 mm																																																																																	
#20	100%	0.850 mm																																																																																	
#40	100%	0.425 mm																																																																																	
#100	75%	0.150 mm																																																																																	
#200	42.3%	0.075 mm																																																																																	
Silts	41.8%	0.074 mm																																																																																	
	29.2%	0.050 mm																																																																																	
	20.9%	0.020 mm																																																																																	
Clays	7.1%	0.005 mm																																																																																	
	3.4%	0.002 mm																																																																																	
Colloids	1.8%	0.001 mm																																																																																	
USDA Soil Textural Classification																																																																																			
Sandy Loam																																																																																			

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: _____

Meghan Blodgett-Carrillo




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT53-GB-28.6-30 ft Sample#: B21-2156	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 15-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP-SM, Poorly graded Sand with Silt Sample Color: grayish-brown	ACCREDITED Certificate #: 1366.01
--	--	--	--------------------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.055 mm D ₍₁₀₎ = 0.088 mm D ₍₁₅₎ = 0.109 mm D ₍₃₀₎ = 0.160 mm D ₍₅₀₎ = 0.197 mm D ₍₆₀₎ = 0.216 mm D ₍₉₀₎ = 0.348 mm Dust Ratio = 2/29	% Gravel = 0.0% % Sand = 93.2% % Silt & Clay = 6.8% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 1.34 Coeff. of Uniformity, C _u = 2.44 Fineness Modulus = 0.92 Plastic Limit = n/a Moisture %, as sampled = 22.4% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18	100%	100%	100.0%	0.0%
#20	0.850	100%	100%	100.0%	0.0%
#30	0.600	99%	99%	100.0%	0.0%
#40	0.425	99%	99%	100.0%	0.0%
#50	0.300	84%	84%	100.0%	0.0%
#60	0.250	78%	78%	100.0%	0.0%
#80	0.180	41%	41%	100.0%	0.0%
#100	0.150	25%	25%	100.0%	0.0%
#140	0.106	14%	14%	100.0%	0.0%
#170	0.090	10%	10%	100.0%	0.0%
#200	0.075	6.8%	6.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo



Client: Anchor QEA
Address: 21328 2nd Drive SE
Bothell, WA 98021
Attn: Garrett Timm
Revised on: _____

Date: October 25, 2021
Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Sample #: B21-2164-2174
Date sampled: 8-3-21 & 8-5-21

As requested MTC, Inc. has performed the following test(s) on the sample referenced above. The testing was performed in accordance with current applicable AASHTO or ASTM standards as indicated below. The results obtained in our laboratory were as follows below or on the attached pages:

	Test(s) Performed:	Test Results		Test(s) Performed:	Test Results
X	Sieve Analysis	Please See Attached Reports		Sulfate Soundness	
	Proctor			Bulk Density & Voids	
	Sand Equivalent			WSDOT Degradation	
	Fracture Count			LA Abrasion	
X	Moisture Content	Please See Attached Report	X	Direct Shear	Please See Attached Reports
	Specific Gravity, Coarse		X	Specific Gravity, Soils	Please See Attached Reports
	Specific Gravity, Fine				
X	Hydrometer Analysis	Please See Attached Reports			
X	Atterberg Limits	Please See Attached Reports			

If you have any questions concerning the test results, the procedures used, or if we can be of any further assistance please call on us at the number below.

Respectfully Submitted,
 Meghan Blodgett-Carrillo
 WABO Supervising Laboratory Technician



Moisture Content - ASTM C566, ASTM D2216

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: October 18, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Sample #	Location	Tare	Wet + Tare	Dry + Tare	Wgt. Of Moisture	Wgt. Of Soil	% Moisture
B21-2164	LDW21-GT48-SPT-25-26.5 ft	233.1	1048.4	832.6	215.8	599.5	36.0%
B21-2165	LDW21-GT48-SPT-30-31.5 ft	182.3	1308.3	1004.2	304.1	821.9	37.0%
B21-2166	LDW21-GT53-SPT-10-11.5 ft	260.3	653.6	537.2	116.4	276.9	42.0%
B21-2167	LDW21-GT53-SPT-15-16.5 ft	270.1	1295.8	1089.8	206.0	819.7	25.1%
B21-2168	LDW21-GT53-SPT-20-21.5 ft	266.3	1049.6	853.9	195.7	587.6	33.3%
B21-2169	LDW21-GT53-SPT-25-26.5 ft	360.2	1271.6	1074.8	196.8	714.6	27.5%
B21-2170	LDW21-GT41-GH-0-1.3 ft	359.4	527.4	488.8	38.6	129.4	29.8%
B21-2171	LDW21-GT41-GH-1.3-2 ft	354.2	2105.6	1668.8	436.8	1314.6	33.2%
B21-2172	LWD21-GT42-GH-0-0.3 ft	341.5	409.5	366.7	42.8	25.2	169.8%
B21-2173	LWD21-GT42-GH-0.3-1.5 ft	356.9	581.1	525.1	56.0	168.2	33.3%
B21-2174	LWD21-GT42-GH-1.5-2.3 ft	224.0	439.0	407.7	31.3	183.7	17.0%

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Reviewed by: *Meghan Blodgett-Carrillo*
 Meghan Blodgett-Carrillo



Specific Gravity - ASTM D854

Project: Q.C. - Lower Duwamish Waterway
Project #: 21B233
Date Received: July 29, 2021
Date Tested: October 18, 2021

Client: Anchor QEA
Sampled by: Client
Tested by: A. Eifrig

Table with 15 columns: Sample #, Location, Tare, Dry Soil + Tare, Mass of Dry Soil, Pycno ID, Mass of Pycno, Volume of Pycno, Density of Water @ Tx, Mass of Pycno filled w/ water & soils, Mass of Pycno filled w/ water, Temp. of Water, 0.1 °C, SpG of Soils, Temp. Correction Factor, Corrected SpG. Contains two rows of data for samples B21-2170 and B21-2174.

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.


Reviewed by: [Signature]
Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT41-GH-0-1.3 ft Sample#: B21-2170	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 18-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.008 mm D ₍₁₀₎ = 0.022 mm D ₍₁₅₎ = 0.068 mm D ₍₃₀₎ = 0.152 mm D ₍₅₀₎ = 0.264 mm D ₍₆₀₎ = 0.320 mm D ₍₉₀₎ = 1.271 mm Dust Ratio = 1/5	% Gravel = 0.0% % Sand = 84.3% % Silt & Clay = 15.7% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 3.31 Coeff. of Uniformity, C _u = 14.63 Fineness Modulus = 1.44 Plastic Limit = n/a Moisture %, as sampled = 29.8% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	100%	100%	100.0%	0.0%
#16	1.18		89%	100.0%	0.0%
#20	0.850		84%	100.0%	0.0%
#30	0.600		81%	100.0%	0.0%
#40	0.425	79%	79%	100.0%	0.0%
#50	0.300		56%	100.0%	0.0%
#60	0.250		48%	100.0%	0.0%
#80	0.180		35%	100.0%	0.0%
#100	0.150	30%	30%	100.0%	0.0%
#140	0.106		21%	100.0%	0.0%
#170	0.090		19%	100.0%	0.0%
#200	0.075	15.7%	15.7%	100.0%	0.0%




Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client : Anchor QEA Source: LDW21-GT41-GH-0-1.3 ft Sample#: B21-2170	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 18-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color brown																																																																																																									
ASTM D7928, HYDROMETER ANALYSIS		ASTM D6913																																																																																																									
Sp Gr : 2.52 Sample Weight: 100.37 grams Hydroscopic Moist.: 0.83% Adj. Sample Wgt : 99.54 grams																																																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Hydrometer Reading Minutes</th> <th>Corrected Reading</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td>13</td><td>13.4%</td><td>0.0539 mm</td></tr> <tr><td>2</td><td>11.5</td><td>11.9%</td><td>0.0385 mm</td></tr> <tr><td>5</td><td>10.5</td><td>10.8%</td><td>0.0245 mm</td></tr> <tr><td>15</td><td>7.5</td><td>7.7%</td><td>0.0144 mm</td></tr> <tr><td>30</td><td>6.5</td><td>6.7%</td><td>0.0102 mm</td></tr> <tr><td>60</td><td>4.5</td><td>4.6%</td><td>0.0073 mm</td></tr> <tr><td>240</td><td>2.5</td><td>2.6%</td><td>0.0037 mm</td></tr> <tr><td>1440</td><td>1</td><td>1.0%</td><td>0.0015 mm</td></tr> </tbody> </table>		Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter	1	13	13.4%	0.0539 mm	2	11.5	11.9%	0.0385 mm	5	10.5	10.8%	0.0245 mm	15	7.5	7.7%	0.0144 mm	30	6.5	6.7%	0.0102 mm	60	4.5	4.6%	0.0073 mm	240	2.5	2.6%	0.0037 mm	1440	1	1.0%	0.0015 mm	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sieve Size</th> <th>Percent Passing</th> <th>Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>3.0"</td><td>100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td>100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td>100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td>100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td>100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td>100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td>100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td>100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td>100%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td>100%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td>100%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td>100%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td>84%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td>79%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td>30%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td>15.7%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td>15.6%</td><td>0.074 mm</td></tr> <tr><td></td><td>12.7%</td><td>0.050 mm</td></tr> <tr><td></td><td>9.4%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td>3.3%</td><td>0.005 mm</td></tr> <tr><td></td><td>1.4%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td>0.7%</td><td>0.001 mm</td></tr> </tbody> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	100%	9.500 mm	1/4"	100%	6.300 mm	#4	100%	4.750 mm	#10	100%	2.000 mm	#20	84%	0.850 mm	#40	79%	0.425 mm	#100	30%	0.150 mm	#200	15.7%	0.075 mm	Silts	15.6%	0.074 mm		12.7%	0.050 mm		9.4%	0.020 mm	Clays	3.3%	0.005 mm		1.4%	0.002 mm	Colloids	0.7%	0.001 mm
Hydrometer Reading Minutes	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																								
1	13	13.4%	0.0539 mm																																																																																																								
2	11.5	11.9%	0.0385 mm																																																																																																								
5	10.5	10.8%	0.0245 mm																																																																																																								
15	7.5	7.7%	0.0144 mm																																																																																																								
30	6.5	6.7%	0.0102 mm																																																																																																								
60	4.5	4.6%	0.0073 mm																																																																																																								
240	2.5	2.6%	0.0037 mm																																																																																																								
1440	1	1.0%	0.0015 mm																																																																																																								
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																									
3.0"	100%	75.000 mm																																																																																																									
2.0"	100%	50.000 mm																																																																																																									
1.5"	100%	37.500 mm																																																																																																									
1.25"	100%	31.500 mm																																																																																																									
1.0"	100%	25.000 mm																																																																																																									
3/4"	100%	19.000 mm																																																																																																									
5/8"	100%	16.000 mm																																																																																																									
1/2"	100%	12.500 mm																																																																																																									
3/8"	100%	9.500 mm																																																																																																									
1/4"	100%	6.300 mm																																																																																																									
#4	100%	4.750 mm																																																																																																									
#10	100%	2.000 mm																																																																																																									
#20	84%	0.850 mm																																																																																																									
#40	79%	0.425 mm																																																																																																									
#100	30%	0.150 mm																																																																																																									
#200	15.7%	0.075 mm																																																																																																									
Silts	15.6%	0.074 mm																																																																																																									
	12.7%	0.050 mm																																																																																																									
	9.4%	0.020 mm																																																																																																									
Clays	3.3%	0.005 mm																																																																																																									
	1.4%	0.002 mm																																																																																																									
Colloids	0.7%	0.001 mm																																																																																																									
USDA Soil Textural Classification																																																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Particle Size</th> </tr> </thead> <tbody> <tr><td>% Sand:</td><td>2.0 - 0.05 mm</td></tr> <tr><td>% Silt:</td><td>0.05 - 0.002 mm</td></tr> <tr><td>% Clay:</td><td>< 0.002 mm</td></tr> </tbody> </table>			Particle Size	% Sand:	2.0 - 0.05 mm	% Silt:	0.05 - 0.002 mm	% Clay:	< 0.002 mm																																																																																																		
	Particle Size																																																																																																										
% Sand:	2.0 - 0.05 mm																																																																																																										
% Silt:	0.05 - 0.002 mm																																																																																																										
% Clay:	< 0.002 mm																																																																																																										
USDA Soil Textural Classification																																																																																																											
Sand																																																																																																											

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:  _____
 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-2170
 Sample Date: 8/3/2021
 Test Date: 10/18/2021
 Technician: M. Carrillo


Sample Source: LDW21-GT41-GH-0-1.3 ft
 Visual Soil Description: brown sand with silt and gravel
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0208
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
	28.1	
	Initial	Post-Consolidation
Initial Moisture Content (%):	109.2	111.5
Dry Density (PCF):	0.543	0.510
Void Ratio:	35.2	33.8
Porosity (%):	saturated	saturated
Degree of Saturation (%):		



Summary of Sample Data: $\sigma_n=1000$ PSF		
	27.3	
	Initial	Post-Consolidation
Initial Moisture Content (%):	110.2	115.1
Dry Density (PCF):	0.529	0.464
Void Ratio:	34.6	31.7
Porosity (%):	saturated	saturated
Degree of Saturation (%):		

Summary of Sample Data: $\sigma_n=2000$ PSF		
	28.4	
	Initial	Post-Consolidation
Initial Moisture Content (%):	109.1	119.9
Dry Density (PCF):	0.545	0.405
Void Ratio:	35.3	28.8
Porosity (%):	saturated	saturated
Degree of Saturation (%):		

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	37	33
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	370	800	1520
Residual Horizontal Stress, τ_h (PSF):	280	570	1330



Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787


Visit our website: www.mtc-inc.net

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT41-GH-1.3-2.0 ft Sample#: B21-2171	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 18-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SM, Silty Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	D ₍₅₎ = 0.022 mm D ₍₁₀₎ = 0.044 mm D ₍₁₅₎ = 0.066 mm D ₍₃₀₎ = 0.170 mm D ₍₅₀₎ = 0.277 mm D ₍₆₀₎ = 0.330 mm D ₍₉₀₎ = 0.824 mm Dust Ratio = 7/32	% Gravel = 1.1% % Sand = 81.8% % Silt & Clay = 17.1% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, C _c = 2.00 Coeff. of Uniformity, C _u = 7.51 Fineness Modulus = 1.48 Plastic Limit = n/a Moisture %, as sampled = 33.2% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	99%	99%	100.0%	0.0%
#4	4.75	99%	99%	100.0%	0.0%
#8	2.36	97%	97%	100.0%	0.0%
#10	2.00	97%	97%	100.0%	0.0%
#16	1.18	92%	92%	100.0%	0.0%
#20	0.850	91%	91%	100.0%	0.0%
#30	0.600	83%	83%	100.0%	0.0%
#40	0.425	78%	78%	100.0%	0.0%
#50	0.300	54%	54%	100.0%	0.0%
#60	0.250	45%	45%	100.0%	0.0%
#80	0.180	32%	32%	100.0%	0.0%
#100	0.150	26%	26%	100.0%	0.0%
#140	0.106	21%	21%	100.0%	0.0%
#170	0.090	19%	19%	100.0%	0.0%
#200	0.075	17.1%	17.1%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:
 Meghan Blodgett-Carrillo

ASTM D4318 - Liquid Limit, Plastic Limit and Plasticity Index of Soils

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT42-GH-0-0.3 ft Sample #: B21-2172	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 18-Oct-21 Tested By: A. Eifrig	Visual Identification Silt with Organics Sample Color brown				
Liquid Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Unable to establish liquid limit					
Weight of Dry Soils + Pan:	Unable to establish liquid limit					
Weight of Pan:	Unable to establish liquid limit					
Weight of Dry Soils:	Unable to establish liquid limit					
Weight of Moisture:	Unable to establish liquid limit					
% Moisture:	Unable to establish liquid limit					
Number of Blows:	Unable to establish liquid limit					
Plastic Limit Determination						
	#1	#2	#3	#4	#5	#6
Weight of Wet Soils + Pan:	Cannot determined plastic limit					
Weight of Dry Soils + Pan:	Cannot determined plastic limit					
Weight of Pan:	Cannot determined plastic limit					
Weight of Dry Soils:	Cannot determined plastic limit					
Weight of Moisture:	Cannot determined plastic limit					
% Moisture:	Cannot determined plastic limit					

Liquid Limit @ 25 Blows: N/A
Plastic Limit: N/A
Plasticity Index, I_p: N/A

Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: Liquid limit cannot be established as the material displays rapid dilation. At lower moistures the material does not spread into the cup without tearing the soil cake. Plastic limit cannot be determined as the sample does not roll down to 1/8" threads before cracking or crumbling. Non-plastic.

Reviewed by:

 Meghan Blodgett-Carrillo

Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT42-GH-0.3-1.5 ft Sample#: B21-2173	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 18-Oct-21 Tested By: A. Eifrig	Visual Identification Sandy Silt with Clay Sample Color: brown	 Certificate #: 1366.01
--	--	---	----------------------------

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281

Specifications


No Specs

Sample Meets Specs ? **N/A**

D ₍₅₎ = 0.000 mm	% Gravel = 4.1%	Coeff. of Curvature, C _c = 0.79
D ₍₁₀₎ = 0.001 mm	% Sand = 32.0%	Coeff. of Uniformity, C _u = 37.10
D ₍₁₅₎ = 0.002 mm	% Silt & Clay = 63.8%	Fineness Modulus = 0.92
D ₍₃₀₎ = 0.005 mm	Liquid Limit = n/a	Plastic Limit = n/a
D ₍₅₀₎ = 0.017 mm	Plasticity Index = n/a	Moisture %, as sampled = 33.3%
D ₍₆₀₎ = 0.037 mm	Sand Equivalent = n/a	Req'd Sand Equivalent =
D ₍₉₀₎ = 1.643 mm	Fracture %, 1 Face = n/a	Req'd Fracture %, 1 Face =
Dust Ratio = 39/50	Fracture %, 2+ Faces = n/a	Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117

Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	99%	99%	100.0%	0.0%
1/4"	6.30	97%	97%	100.0%	0.0%
#4	4.75	96%	96%	100.0%	0.0%
#8	2.36	93%	93%	100.0%	0.0%
#10	2.00	92%	92%	100.0%	0.0%
#16	1.18	87%	87%	100.0%	0.0%
#20	0.850	85%	85%	100.0%	0.0%
#30	0.600	83%	83%	100.0%	0.0%
#40	0.425	82%	82%	100.0%	0.0%
#50	0.300	78%	78%	100.0%	0.0%
#60	0.250	76%	76%	100.0%	0.0%
#80	0.180	74%	74%	100.0%	0.0%
#100	0.150	73%	73%	100.0%	0.0%
#140	0.106	67%	67%	100.0%	0.0%
#170	0.090	66%	66%	100.0%	0.0%
#200	0.075	63.8%	63.8%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Hydrometer Report

Project: Q.C. - Lower Duwamish Waterway Date Received: 29-Jul-21 Project #: 21B233 Sampled By: Client Client : Anchor QEA Date Tested: 18-Oct-21 Source: LDW21-GT42-GH-0.3-1.5 ft Tested By: A. Eifrig Sample#: B21-2173	Visual Identification Sandy Silt with Clay Sample Color brown																																																																																																																																				
ASTM D7928, HYDROMETER ANALYSIS	ASTM D6913																																																																																																																																				
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Assumed Sp Gr :</td> <td style="width: 20%; text-align: center;">2.65</td> <td style="width: 50%;"></td> </tr> <tr> <td>Sample Weight:</td> <td style="text-align: center;">75.38</td> <td>grams</td> </tr> <tr> <td>Hydroscopic Moist.:</td> <td style="text-align: center;">1.68%</td> <td></td> </tr> <tr> <td>Adj. Sample Wgt :</td> <td style="text-align: center;">74.13</td> <td>grams</td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Hydrometer Reading</th> <th style="text-align: left;">Corrected Reading</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> </thead> <tbody> <tr><td>1</td><td style="text-align: center;">49</td><td style="text-align: center;">61.1%</td><td>0.0393 mm</td></tr> <tr><td>2</td><td style="text-align: center;">45</td><td style="text-align: center;">56.1%</td><td>0.0288 mm</td></tr> <tr><td>5</td><td style="text-align: center;">42.5</td><td style="text-align: center;">53.0%</td><td>0.0187 mm</td></tr> <tr><td>15</td><td style="text-align: center;">34.5</td><td style="text-align: center;">43.0%</td><td>0.0115 mm</td></tr> <tr><td>30</td><td style="text-align: center;">30.5</td><td style="text-align: center;">38.0%</td><td>0.0084 mm</td></tr> <tr><td>60</td><td style="text-align: center;">26</td><td style="text-align: center;">32.4%</td><td>0.0061 mm</td></tr> <tr><td>240</td><td style="text-align: center;">18</td><td style="text-align: center;">22.4%</td><td>0.0032 mm</td></tr> <tr><td>1440</td><td style="text-align: center;">11</td><td style="text-align: center;">13.7%</td><td>0.0014 mm</td></tr> </tbody> </table> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">% Gravel:</td> <td style="width: 20%; text-align: center;">4.1%</td> <td style="width: 50%;"></td> </tr> <tr> <td>% Sand:</td> <td style="text-align: center;">32.0%</td> <td></td> </tr> <tr> <td>% Silt:</td> <td style="text-align: center;">35.2%</td> <td></td> </tr> <tr> <td>% Clay:</td> <td style="text-align: center;">28.6%</td> <td></td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 20%;"></td> <td style="width: 50%;"> Liquid Limit: n/a Plastic Limit: n/a Plasticity Index: n/a </td> </tr> </table>	Assumed Sp Gr :	2.65		Sample Weight:	75.38	grams	Hydroscopic Moist.:	1.68%		Adj. Sample Wgt :	74.13	grams	Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter	1	49	61.1%	0.0393 mm	2	45	56.1%	0.0288 mm	5	42.5	53.0%	0.0187 mm	15	34.5	43.0%	0.0115 mm	30	30.5	38.0%	0.0084 mm	60	26	32.4%	0.0061 mm	240	18	22.4%	0.0032 mm	1440	11	13.7%	0.0014 mm	% Gravel:	4.1%		% Sand:	32.0%		% Silt:	35.2%		% Clay:	28.6%				Liquid Limit: n/a Plastic Limit: n/a Plasticity Index: n/a	<table style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left;">Sieve Size</th> <th style="text-align: left;">Percent Passing</th> <th style="text-align: left;">Soils Particle Diameter</th> </tr> <tr><td>3.0"</td><td style="text-align: center;">100%</td><td>75.000 mm</td></tr> <tr><td>2.0"</td><td style="text-align: center;">100%</td><td>50.000 mm</td></tr> <tr><td>1.5"</td><td style="text-align: center;">100%</td><td>37.500 mm</td></tr> <tr><td>1.25"</td><td style="text-align: center;">100%</td><td>31.500 mm</td></tr> <tr><td>1.0"</td><td style="text-align: center;">100%</td><td>25.000 mm</td></tr> <tr><td>3/4"</td><td style="text-align: center;">100%</td><td>19.000 mm</td></tr> <tr><td>5/8"</td><td style="text-align: center;">100%</td><td>16.000 mm</td></tr> <tr><td>1/2"</td><td style="text-align: center;">100%</td><td>12.500 mm</td></tr> <tr><td>3/8"</td><td style="text-align: center;">99%</td><td>9.500 mm</td></tr> <tr><td>1/4"</td><td style="text-align: center;">97%</td><td>6.300 mm</td></tr> <tr><td>#4</td><td style="text-align: center;">96%</td><td>4.750 mm</td></tr> <tr><td>#10</td><td style="text-align: center;">92%</td><td>2.000 mm</td></tr> <tr><td>#20</td><td style="text-align: center;">85%</td><td>0.850 mm</td></tr> <tr><td>#40</td><td style="text-align: center;">82%</td><td>0.425 mm</td></tr> <tr><td>#100</td><td style="text-align: center;">73%</td><td>0.150 mm</td></tr> <tr><td>#200</td><td style="text-align: center;">63.8%</td><td>0.075 mm</td></tr> <tr><td>Silts</td><td style="text-align: center;">63.8%</td><td>0.074 mm</td></tr> <tr><td></td><td style="text-align: center;">62.3%</td><td>0.050 mm</td></tr> <tr><td></td><td style="text-align: center;">53.4%</td><td>0.020 mm</td></tr> <tr><td>Clays</td><td style="text-align: center;">28.6%</td><td>0.005 mm</td></tr> <tr><td></td><td style="text-align: center;">16.7%</td><td>0.002 mm</td></tr> <tr><td>Colloids</td><td style="text-align: center;">10.0%</td><td>0.001 mm</td></tr> </table>	Sieve Size	Percent Passing	Soils Particle Diameter	3.0"	100%	75.000 mm	2.0"	100%	50.000 mm	1.5"	100%	37.500 mm	1.25"	100%	31.500 mm	1.0"	100%	25.000 mm	3/4"	100%	19.000 mm	5/8"	100%	16.000 mm	1/2"	100%	12.500 mm	3/8"	99%	9.500 mm	1/4"	97%	6.300 mm	#4	96%	4.750 mm	#10	92%	2.000 mm	#20	85%	0.850 mm	#40	82%	0.425 mm	#100	73%	0.150 mm	#200	63.8%	0.075 mm	Silts	63.8%	0.074 mm		62.3%	0.050 mm		53.4%	0.020 mm	Clays	28.6%	0.005 mm		16.7%	0.002 mm	Colloids	10.0%	0.001 mm
Assumed Sp Gr :	2.65																																																																																																																																				
Sample Weight:	75.38	grams																																																																																																																																			
Hydroscopic Moist.:	1.68%																																																																																																																																				
Adj. Sample Wgt :	74.13	grams																																																																																																																																			
Hydrometer Reading	Corrected Reading	Percent Passing	Soils Particle Diameter																																																																																																																																		
1	49	61.1%	0.0393 mm																																																																																																																																		
2	45	56.1%	0.0288 mm																																																																																																																																		
5	42.5	53.0%	0.0187 mm																																																																																																																																		
15	34.5	43.0%	0.0115 mm																																																																																																																																		
30	30.5	38.0%	0.0084 mm																																																																																																																																		
60	26	32.4%	0.0061 mm																																																																																																																																		
240	18	22.4%	0.0032 mm																																																																																																																																		
1440	11	13.7%	0.0014 mm																																																																																																																																		
% Gravel:	4.1%																																																																																																																																				
% Sand:	32.0%																																																																																																																																				
% Silt:	35.2%																																																																																																																																				
% Clay:	28.6%																																																																																																																																				
		Liquid Limit: n/a Plastic Limit: n/a Plasticity Index: n/a																																																																																																																																			
Sieve Size	Percent Passing	Soils Particle Diameter																																																																																																																																			
3.0"	100%	75.000 mm																																																																																																																																			
2.0"	100%	50.000 mm																																																																																																																																			
1.5"	100%	37.500 mm																																																																																																																																			
1.25"	100%	31.500 mm																																																																																																																																			
1.0"	100%	25.000 mm																																																																																																																																			
3/4"	100%	19.000 mm																																																																																																																																			
5/8"	100%	16.000 mm																																																																																																																																			
1/2"	100%	12.500 mm																																																																																																																																			
3/8"	99%	9.500 mm																																																																																																																																			
1/4"	97%	6.300 mm																																																																																																																																			
#4	96%	4.750 mm																																																																																																																																			
#10	92%	2.000 mm																																																																																																																																			
#20	85%	0.850 mm																																																																																																																																			
#40	82%	0.425 mm																																																																																																																																			
#100	73%	0.150 mm																																																																																																																																			
#200	63.8%	0.075 mm																																																																																																																																			
Silts	63.8%	0.074 mm																																																																																																																																			
	62.3%	0.050 mm																																																																																																																																			
	53.4%	0.020 mm																																																																																																																																			
Clays	28.6%	0.005 mm																																																																																																																																			
	16.7%	0.002 mm																																																																																																																																			
Colloids	10.0%	0.001 mm																																																																																																																																			
USDA Soil Textural Classification																																																																																																																																					
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 20%;"></td> <td style="width: 50%;"> Particle Size % Sand: 2.0 - 0.05 mm % Silt: 0.05 - 0.002 mm % Clay: < 0.002 mm </td> </tr> </table> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 20%;"></td> <td style="width: 50%; text-align: center;"> USDA Soil Textural Classification Loam </td> </tr> </table>			Particle Size % Sand: 2.0 - 0.05 mm % Silt: 0.05 - 0.002 mm % Clay: < 0.002 mm			USDA Soil Textural Classification Loam																																																																																																																															
		Particle Size % Sand: 2.0 - 0.05 mm % Silt: 0.05 - 0.002 mm % Clay: < 0.002 mm																																																																																																																																			
		USDA Soil Textural Classification Loam																																																																																																																																			

All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by:

 Meghan Blodgett-Carrillo

Direct Shear Test Results:

ASTM D-3080



Project: Q.C. - Lower Duwamish Waterway
 Project Number: 21B233
 Laboratory Sample ID: B21-2173
 Sample Date: 8/3/2021
 Test Date: 10-19-21 through 10-21-21
 Technician: M. Carrillo


Sample Source: LDW21-GT42-GH-0.3-1.5 ft
 Visual Soil Description: brown clay with silt
 Type of Specimen: Remolded Cylindrical Shear Box
 Specimen Diameter (in): 2.5
 Specimen Height (in): 1
 Rate of Strain (in/min): 0.0012
 Estimated Specific Gravity of Solids: 2.65

Summary of Sample Data: $\sigma_n=500$ PSF		
Initial Moisture Content (%):	34.0	
	Initial	Post-Consolidation
Dry Density (PCF):	102.5	106.8
Void Ratio:	0.644	0.578
Porosity (%):	39.2	36.6
Degree of Saturation (%):	saturated	saturated



Summary of Sample Data: $\sigma_n=1000$ PSF		
Initial Moisture Content (%):	31.5	
	Initial	Post-Consolidation
Dry Density (PCF):	104.6	114.9
Void Ratio:	0.611	0.467
Porosity (%):	37.9	31.8
Degree of Saturation (%):	saturated	saturated

Summary of Sample Data: $\sigma_n=2000$ PSF		
Initial Moisture Content (%):	28.9	
	Initial	Post-Consolidation
Dry Density (PCF):	107.0	120.1
Void Ratio:	0.574	0.403
Porosity (%):	36.5	28.7
Degree of Saturation (%):	saturated	saturated

ESTIMATED STRENGTH PARAMETERS		
	PEAK	RESIDUAL
Angle of Internal Friction, ϕ (°):	33	31
Cohesion (PSF):	0	0



Failure Envelope Test Values:			
Normal Stress, σ_n (PSF):	500	1000	2000
Peak Horizontal Stress, τ_h (PSF):	290	590	1310
Residual Horizontal Stress, τ_h (PSF):	290	550	1250




Corporate • 777 Chrysler Drive • Burlington, WA 98233 • Phone 360.755.1990 • Fax 360.755.1980
 SW Region • 2118 Black Lake Blvd. S.W. • Olympia, WA 98512 • Phone 360.534.9777 • Fax 360.534.9779
 NW Region • 805 Dupont, Suite #5 • Bellingham, WA 98225 • Phone 360.647.6061 • Fax 360.647.8111
 Kitsap Region • 5451 N.W. Newberry Hill Road, Suite 101 • Silverdale, WA 98383 • Phone/Fax 360.698.6787

Visit our website: www.mtc-inc.net




Sieve Report

Project: Q.C. - Lower Duwamish Waterway Project #: 21B233 Client: Anchor QEA Source: LDW21-GT42-GH-1.5-2.3 ft Sample#: B21-2174	Date Received: 29-Jul-21 Sampled By: Client Date Tested: 18-Oct-21 Tested By: A. Eifrig	Unified Soil Classification System, ASTM-2487 SP, Poorly graded Sand Sample Color: brown	 Certificate #: 1366.01
--	--	---	---

ASTM D2216, ASTM D2419, ASTM D4318, ASTM D5281			
Specifications No Specs Sample Meets Specs ? N/A	$D_{(5)} = 0.075$ mm $D_{(10)} = 0.150$ mm $D_{(15)} = 0.167$ mm $D_{(30)} = 0.251$ mm $D_{(50)} = 0.334$ mm $D_{(60)} = 0.376$ mm $D_{(90)} = 0.733$ mm Dust Ratio = 3/47	% Gravel = 0.0% % Sand = 95.4% % Silt & Clay = 4.6% Liquid Limit = n/a Plasticity Index = n/a Sand Equivalent = n/a Fracture %, 1 Face = n/a Fracture %, 2+ Faces = n/a	Coeff. of Curvature, $C_c = 1.29$ Coeff. of Uniformity, $C_u = 2.90$ Fineness Modulus = 1.67 Plastic Limit = n/a Moisture %, as sampled = 17.0% Req'd Sand Equivalent = Req'd Fracture %, 1 Face = Req'd Fracture %, 2+ Faces =

ASTM C136, ASTM D6913, ASTM C117					
Sieve Size		Actual Cumulative Percent Passing	Interpolated Cumulative Percent Passing	Specs Max	Specs Min
US	Metric				
12.00"	300.00		100%	100.0%	0.0%
10.00"	250.00		100%	100.0%	0.0%
8.00"	200.00		100%	100.0%	0.0%
6.00"	150.00		100%	100.0%	0.0%
4.00"	100.00		100%	100.0%	0.0%
3.00"	75.00		100%	100.0%	0.0%
2.50"	63.00		100%	100.0%	0.0%
2.00"	50.00	100%	100%	100.0%	0.0%
1.75"	45.00	100%	100%	100.0%	0.0%
1.50"	37.50	100%	100%	100.0%	0.0%
1.25"	31.50	100%	100%	100.0%	0.0%
1.00"	25.00	100%	100%	100.0%	0.0%
3/4"	19.00	100%	100%	100.0%	0.0%
5/8"	16.00	100%	100%	100.0%	0.0%
1/2"	12.50	100%	100%	100.0%	0.0%
3/8"	9.50	100%	100%	100.0%	0.0%
1/4"	6.30	100%	100%	100.0%	0.0%
#4	4.75	100%	100%	100.0%	0.0%
#8	2.36	100%	100%	100.0%	0.0%
#10	2.00	99%	99%	100.0%	0.0%
#16	1.18	97%	97%	100.0%	0.0%
#20	0.850	97%	97%	100.0%	0.0%
#30	0.600	82%	82%	100.0%	0.0%
#40	0.425	72%	72%	100.0%	0.0%
#50	0.300	42%	42%	100.0%	0.0%
#60	0.250	30%	30%	100.0%	0.0%
#80	0.180	17%	17%	100.0%	0.0%
#100	0.150	12%	12%	100.0%	0.0%
#140	0.106	8%	8%	100.0%	0.0%
#170	0.090	6%	6%	100.0%	0.0%
#200	0.075	4.6%	4.6%	100.0%	0.0%



Copyright Spears Engineering & Technical Services PS, 1996-98
 All results apply only to actual locations and materials tested. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Comments: _____

Reviewed by: 
 Meghan Blodgett-Carrillo